

PORT INFO INDONESIA
BATAM PORT - BATU AMPAR/ KABIL/ SEKUPANG/ TANJUNG UNCANG

GENERAL INFORMATION		
A.	NAME OF PORT	: BATU AMPAR
A.1	PUBLIC WHARF	
	ANCHORAGE POSITION /	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE	: COMPULSORY 24 HRS
	TUGGAGE	: COMPULSORY
	CHANNEL DRAFT	: 9 MTR LWS
	DRAFT AT ALONGSIDE	: 8 MTR LWS
	LENGTH OF WHARF	: 1250 MTR
		250 MTR = MAX DRAFT 8 MTR (SOUTH JETTY)
		1000 MTR = MAX DRAFT 5 - 7 MTR
	MAX. LOA	: 180 M
	MAX. DWT	: DWT 35,000
	CARGO	: CONTAINER, GENERAL CARGO, PROJECT VESSEL/OFF SHORE SUPPORT; SUPPLY, CREW CHANGE
		STEEL PLATE, H BEAM, CEMENTS, ETC.
	FRESH WATER SUPPLY	: AVAILABLE
	BUNKER SUPPLY	: AVAILABLE
A.2	MC. DERMOTT (PRIVATE PORT)	
	ANCHORAGE POSITION /	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE	: COMPULSORY / DAY LIGHT ONLY
	TUGGAGE	: COMPULSORY
	CHANNEL DRAFT	: 9 MTR LWS
	DRAFT AT ALONGSIDE	: 10 MTR LWS
	LENGTH OF WHARF	: 600 MTR
		PRIVATE PORT FOR OIL RIG / FACTORY MC DERMOTT
	FRESH WATER + BUNKER SUPPLY	: NOT AVAILABLE
A.3	BATU MERAH / PT. BANGUN ADYA BAHAN (PRIVATE PORT)	
	ANCHORAGE POSITION /	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE	: COMPULSORY / DAY LIGHT ONLY
	TUGGAGE	: COMPULSORY
	DRAFT AT ALONGSIDE	: 5.5 MTR
	LENGTH OF WHARF	: 110 MTR
		PRIVATE PORT FOR PT. BANGUN ADYA BAHAN
		LOADING/UNLOADING FOR FACTORY MATERIAL AND OFF SHORE SUPPORT; SUPPLY, CREW CHANGE
	FRESH WATER + BUNKER SUPPLY	: AVAILABLE
A.4	BATU MERAH / PT. PROFAB (PRIVATE PORT)	
	ANCHORAGE POSITION /	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND	: 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE	: COMPULSORY / DAY LIGHT ONLY
	TUGGAGE	: COMPULSORY
	DRAFT AT ALONGSIDE	: 4.5 MTR
	LENGTH OF WHARF	: 100 MTR
		PRIVATE PORT FOR LOADING/UNLOADING PRODUCT PT. PROFAB
	FRESH WATER + BUNKER SUPPLY	: AVAILABLE
B.	NAME OF PORT	: KABIL
B.1	KABIL - PTK	
	ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
	BOARDING POS	
	PILOTAGE	: COMPULSORY 24 HRS
	TUGGAGE	: COMPULSORY
	LENGTH OF WHARF	: 75 METERS

MAXIMUM DWT	: 5,000 DWT
MAXIMUM A/SIDE DRAFT	: 6 METERS
CARGO	: GENERAL CARGO, FLOATING REPAIR WITH SPECIAL PERMISSION
OFF SHORE SUPPORTING, CREW CHANGE, SUPPLY	
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
B.2 KABIL - CPPI	
PORT POSITION	: 01 - 06 - 30 N / 104 - 08 - 25 E
PILOT BOARDING GROUND	: 01 - 07 - 00 N / 104 - 10 - 30 E
ANCHORAGE POSITION	: 01 - 06 - 00 N / 104 - 10 - 00 E
	: 01 - 06 - 00 N / 104 - 11 - 18 E
	: 01 - 06 - 48 N / 104 - 11 - 18 E
	: 01 - 06 - 48 N / 104 - 10 - 00 E
PILOTAGE	: COMPULSORY
IN/OUT BERTHING & UNBERTHING	: 24 HRS
TUG BOAT	: COMPULSORY
STANDART TIME	: GMT + 7 HRS
COMMUNICATION	: VHF CH 16 / CH 8
	: CITRA PORT CONTROL : TEL (0778) 7202111
RAIN SEASON	: MAY TO SEPTEMBER, WORST IN OCTOBER TO FEBRUARY
TIDAL RISE	: MHWS 320 CM / LWS/ZO 160 CM
WATER DENSITY	: 1.025
PORT RESTRCITION	
OUTER ROAD DEPTH	: 10 - 15 MTRS (MLWS)
INNER ROAD DEPTH	: 13 MTRS (MLWS)
CHANNEL DEPTH	: 13 MTRS (MLWS)
BERTH:	
1. BERTH PARTICULARS (EXPORT/IMPORT)	
COORDINATE	: 01 - 06 - 35.4 N / 104 - 08 - 57.8 E
TYPE	: MARGINAL / PILLING CONCRETE FLOOR CONSTRUCTION
DIMENSION	: 176 X 29 M2
DEPTH	: 10 MTR LWS
MAX DWT	: 30,000 MT DWT
2. SPECIAL BERTH (SMALL CRAFT)	
COORDINATE	: 01 - 06 - 43.3 N / 104 - 08 - 45.1 E
TYPE	: JETTY / PILLING CONCRETE FLOOR CONSTRUCTION
BREASTING DOLPHIN	: 2 UNITS OF 5,4 X 3 M2 AND 2 UNITS OF 3,4 X 2,4 M2
MOORING DOLPHIN	: 2 UNITS OF 3,5 X 3,5 M2
DEPTH	: 5 MTR LWS
MAX DWT	: 2,000 MT DWT
3. LANDING CRAFT (RORO)	
COORDINATE	: 01 - 06 - 46.3 N / 104 - 08 - 46.8 E
TYPE	: JETTY / PILLING CONCRETE FLOOR CONSTRUCTION
BREASTING DOLPHIN	: 2 UNITS OF 5,6 X 4,7 M2
MOORING DOLPHIN	: 2 UNITS OF 4,2 X 4,2 M2
DEPTH	: 5 MTR LWS
FOR VESSEL	: LCT / RORO
4. JETTY NO 5 & 6 / EXTENTION JETTY	
COORDINATE	: 01 - 06 - 35.4 N / 104 - 08 - 57.8 E
TYPE	: MARGINAL / PILLING CONCRETE FLOOR CONSTRUCTION
DIMENSION	: 290 X 36 M2
DEPTH	: 12.5 MTR LWS
MAX DWT	: 40,000 MT DWT
STEVEDORE WORKING HRS	: 3 SHIFT 24 HRS
CRANE & FORKLIFT	: MOBILE CRANE 50 - 80 MT
	: CRAWLER CRANES 100 - 250 MT
	: FORKLIFT AVAILABLE 2 - 7 MT
FRESH WATER SUPPLY	: 80 MT / HOUR BY PIPE LINE
BUNKER SUPPLY	: AVAILABLE
WATCHMAN	: ISPS CODE COMPLIANCE
CARGO	: GENERAL CARGO, PROJECT VESSEL FOR SUPPLY/CREW CHANGE, IRON ORE, STEEL PIPE, STEEL PLATE, RO/RO VESSEL

B.3 KABIL - CPO	
PORT POSITION	: 01 - 04 - 05 N / 104 - 09 - 00 E
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOATRDING POS	
PILOTAGE	: COMPULSORY 24 HRS
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 410 METERS
MAX CHANNEL DRAFT	: 13 MTR ON HIGH TIDE
MAXIMUM A/SIDE DRAFT	: 13 METERS (Can berth in day and night time)
MAXIMUM DWT	: 40,000 DWT
MAXIMUM LOA	: 200 METERS
CARGO	: FOR LIQUID CARGO
SHIPPER	: SYNERGI OIL NUSANTARA, PATRA NIAGA. MUSIMAS, ECO GREEN.
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
B.4 KABIL - BOSOWA	
PORT POSITION	-
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOARDING POS	
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 110 METERS Available dophinS 2 unit with 150 mtr of range, vessel with LOA 180 also can alongside
MAX ALONGSIDE DRAFT	: 10.5 MTR ON HIGH TIDE
CARGO	: CEMENT / CLINKER IN BULK
SHIPPER	: SEMEN BATAM / BOSOWA
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
B.5 KABIL - SHIPYARD	
PORT POSITION	:
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOARDING POS	
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
BUNKER SUPPLY	: AVAILABLE
FRESH WATER SUPPLY	: AVAILABLE
WHARF	:
NINDA PRA TAMA	: LENGTH OF WHARF 400 MTR / DRAFT 5 - 7 MTR
ANGGREK HITAM/JSE	: MAX DRAFT 3 - 5 MTR ON HIGH TIDE
NEXUS	: MAX DRAFT 3 - 5 MTR ON HIGH TIDE / 110 MTR LENGTH OF WHARF
ETC....	
C. NAME OF PORT	: SEKUPANG
C.1 PASSANGER / PELNI TERMINAL	
PILOT BOARDING POSITION	: 01 - 10 - 00 N / 103 - 56 - 05 E (SAMBU PSTN)
PORT POSITION	: 01 - 07 - 30 N / 103 - 55 - 22 E
ANCHORAGE POSITION /	: 01 - 07 - 36 N / 103 - 53 - 42 E
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 180 METERS
MAXIMUM DWT	: 10,000 DWT
MAXIMUM LOA	: 170 METERS
MAXIMUM A/SIDE DRAFT	: 8 - 9 METERS
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
C.2 PRIVATE PORT FOR SHIPYARD	
ANCHORAGE POSITION	: 01 - 09 - 05 N / 103 - 55 - 01 E
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
LENGTH OF WHARF	: PRIVATE JETTY / VARIOUS SHIPYARD WITH DRAFT 2 - 7 MTR
BRITOIL	: 7 MTR

		NINDA PRATAMA : 7 MTR ETC.....
D. NAME OF PORT	:	TANJUNG UNCANG PORT (PRIVATE PORT FOR SHIPYARD)
PILOT BOARDING POSITION	:	01 - 10 - 00 N / 103 - 56 - 05 E (SAMBU PSTN)
ANCHORAGE POSITION	:	01 - 09 - 05 N / 103 - 55 - 01 E
MAXIMUM ANCHORAGE DRAFT	:	20 MTR
PILOTAGE	:	COMPULSORY DAY LIGHT ONLY
TUGGAGE	:	COMPULSORY
FRESH WATER SUPPLY	:	AVAILABLE
BUNKER SUPPLY	:	AVAILABLE
LENGTH OF WHARF	:	PRIVATE JETTY / VARIOUS SHIPYARD WITH DRAFT 2 - 8 MTR
		ASL : 7.5 MTR
		BATAMEC : 7.0 MTR
		DDW GRAHA : 4.5 MTR
		DDW NANINDAH : 6 MTR
		DDW PERTAMA : 8 MTR
		ETC.....
DDW PERTAMA PORT POSITION	:	01 - 05 - 22 N / 103 - 53 - 13 E 01 - 05 - 63 N / 103 - 53 - 55 E
OTHER USEFUL INFORMATION		
LOCAL TIME	:	GMT + 7 HRS (SPORE-1 HR)
WHEATHER CONDITION	:	SPEED WIND 15 Bft PEAK 3kph BEARING 30 ° , TEMPERATURE 31°C / 87°F WITH CLOUDS,MIST
WORKING HOURS	:	24 HRS (0600-0700 HRS, 1200-1300 HRS, 1800-1900 HRS AND 2400-0100 HRS IS MEAL TIME)
TYPE OF TERMINAL	:	PUBLIC TERMINAL EXCEPT TANJUNG UNCANG PORT, SEKUPANG PORT, MC. DERMOTT AND BATU MERAH
SHORE CRANE HIRE AT BATAM		
Crance Capacity (tons)		
45-50	:	AVAILABLE
80 - 100	:	AVAILABLE
125	:	AVAILABLE
150	:	AVAILABLE
250	:	AVAILABLE

ALL INFORMATION ABOVE PROVIDED IN GOOD FAITH BY BBI AGENCY.

BBI AGENCY - AS AGENTS ONLY