

# PT BANDAR BERLAYAR INTERNASIONAL

12th Floor, Menara Batavia, Jl. KH Mas Mansyur, Kav 126, Jakarta 10220, Indonesia. Tel: +62 21 2528 613, 614, 615, 616 | Fax: +62 21

2528 613 | Phone: +62 811 1609 711

Email: marketing@smartin.agency | bbi@smartin.id Website: https://smartin.agency | https://bbi.smartin.id

### **PORT INFO INDONESIA** T.P.P.I TERMINAL TUBAN (EAST JAVA)

GENERAL INFORMATION

LOCATION Lat. 06 45' 48" South, Long. 111 57' 18" East

PILOT POSITION Lat. 06-38-24 S Long. 111-55-41 E

LENGTH OF WATER 1.450 M MAX. DRAFT 13.5 M

PILOTAGE/TUGGAGE

PILOT STATION VHF Channel - 72 General and 16 Safety & Distress

CALL SIGN TPPI PORT CONTROL LENGTH OF WHARE 275 Meter MAX. DWT 40,000 DWT MAX. LOA 200 Meter MAX. DRAFT

SINGLE POINT MOORING (SPM) TERMINAL

50.000 DWT - 185.00 DWT MAX. DWT MIN. DWT 35.000 DWT

MAX.LOA 180 M - 310 M DEPTH OF WATER 27.5 M MAX. DRAFT 19.0 M

В	E	F	?T	Ή	S	

DEKTINO						
NAME/NO	RANGE OF SHIP'S LOA	MAXIMUM DRAFT	WATER DEPTH	CAPACITY	REMARKS	
JETTY NO.3	91 M - 140 M	9.8 M	13.50 M	10,000 DWT		
JETTY NO.4 & NO.5	76 M - 187 M	10.6 M	13.5 M	3,000 - 40,000 DWT		-

#### NOTES:

- MANIFOLD STANDARD : ANSI B 16.5 CLASS 150 (JETTY NO.3)
- I . DISTANCE CENTRE MANIFOLD TO SHIP DECK (MIN) 700 MM
- II . DISTANCE CENTRE MANIFOLD TO DRIP TRAY (MIN) 900 MM
- III. DISTANCE MANIFOLD TO SHIP RAILLING/SIDE (MIN) 2,000 MM
- IV. DISTANCE BETWEEN MANIFOLD CENTER TO CENTER 1.500 MM - MANIFOLD STANDARD: ANSI B 16.5 CLASS 150 (JETTY NO.3)
- I . DISTANCE CENTRE MANIFOLD TO SHIP DECK (MIN) 1,300 MM
- II . DISTANCE CENTRE MANIFOLD TO DRIP TRAY (MIN) 900 MM
- III. DISTANCE MANIFOLD TO SHIP RAILLING/SIDE (MIN) 2,500 MM
- IV. DISTANCE BETWEEN MANIFOLD CENTER TO CENTER 1,200 MM
- V. DISTANCE FREE AREA BEHIND FLANGE NECK 350 MM

# LOADING METHOD / RATE AND PORT WORKING TIMES

LOADING AND UNLOADING METHOD DIRECT TO SHIP'S MANIFOLD. HOWEVER THIS PORT JUST REQUIRE ALL SHIPS SHOULD HAVE SHIP'S CRANE FOR

LIFTING SHORE HOSES TO PUT INTO SHIP'S MANIFOLD.COMMODITY SERVES INTEGRATED AROMATIC PLANT IN HANDLING CONDENSATE AS RAW MATERIALS AND VARIOUS PETROLEUM AND PETROCHEMICAL PRODUCT LIQUID IN BUILK

LOADING METHOD FOR CEMENT IN BULK USING ONE FIX CONVEYOR, FOR CEMENT IN BAG USING SLING ROPE, FOR CLINKER IN BULK USING SHORE GRAB.

### OTHER USEFUL INFORMATION

LOCAL TIME GMT + 7 HRS (SPORE-1 HR)

WORKING HOURS 24 HOURS

Sct T-Storms, 50% CHANCE OF PRECIPITATION, WINDS 11mph from W. HUMIDITY 77% S WEATHER

TYPE OF TERMINAL PUBLIC TERMINAL ALL INFORMATION ABOVE PROIVIDED IN GOOD FAITH BY BBI AGENCY

WE ACCEPT NO LIABLTY FOR INACURATE INFORMATION

BBI AGENCY - AS AGENTS ONLY