



Sleep Mode	I Feel	Turbo	Dry Anti-Mildew Design	Anti-Cold Air	Anti-Corrosion	Auto Defrosting	LED Display	Timer
Child Lock	Auto Restart	Self-Diagnosis	Filter Cleaning reminder	0.5W Standby	Low Voltage Startup	Low Ambient Cooling=-20°C	Low Ambient Heating=-20°C	

● SUPREME Series

Model Name	SUPREME inverter 9R		SUPREME inverter 12R		SUPREME inverter 18R		SUPREME inverter 24R	
Function	Heat Pump		Heat Pump		Heat Pump		Heat Pump	
Capacity	Cooling	BTU/h	8871	11942	17504	22007		
	Heating	BTU/h	9554	13648	17981	22519		
Capacity range	Cooling	BTU/h	1365~11260	1877~13648	3412~22860	4777~23884		
	Heating	BTU/h	1365~13989	2047~17504	3753~23202	5118~26955		
PdesignC		kW	2.6	3.5	5.2	6.4		
PdesignH		kW	2.6	3.2	5.0	6.2		
SEER/SCOP		W/W	6.7/4.0	6.5/4.0	6.3/4.0	6.4/4.0		
Energy level			A++/A+	A++/A+	A++/A+	A++/A+		
Power Supply		Ph,V,Hz	1ph,220V-240V,50Hz	1ph,220V-240V,50Hz	1ph,220V-240V,50Hz	1ph,220V-240V,50Hz		
Power Input	Cooling	W	750	1010	1540	1840		
	Heating	W	745	970	1480	1750		
Rated Current	Cooling	A	3.6	4.8	7.0	8.9		
	Heating	A	3.4	4.4	6.3	8.4		
	Refrigerant		R32	R32	R32	R32		
	Airflow Volume	m³/h	520/440/230/150	580/500/300/230	850/760/570/480	1090/930/670/560		
Indoor Unit	Sound Pressure Level	dB(A)(SH/H/M/L)	39/34/21/19	40/35/22/20	47/44/31/29	48/44/35/33		
	Outline Dimension	W×H×D	821x283x200	884x298x205	1003x310x222	1109x331x250		
	Package Dimension	W×H×D	898x291x353	951x298x369	1080x314x383	1181x354x417		
	Net Weight/Gross Weight	kg	9.5/11.5	10.5/12.5	14/16.5	16.5/19.5		
	Sound Pressure Level	dB(A)	52	53	55	59		
Outdoor Unit	Piping Connection	Gas	φ9.52	φ9.52	φ12	φ16		
		Liquid	φ6	φ6	φ6	φ6		
	Outline Dimension	W×H×D	830X540X325	830X540X325	890x598x372	960×700×396		
	Package Dimension	W×H×D	879×605×366	879×605×366	941x663x412	1011x763x455		
	Net Weight/Gross Weight	kg	29/32	30/33	40/43	43.5/48		
Loading Quantity	40'GP	sets	224	205	162	116		
	40'HQ	sets	249	242	182	130		