



Compliance with relevant ASTM and ISO Standards as well as Industry Engineering specifications

Labino AB LED UV Lights	Built in White Light LED	UV Intensity at 38 cm (15") (µW/cm ²)	COMPLIES WITH ASTM E3022-2018 Standard	COMPLIES WITH Rolls-Royce RRES90061 Specification	COMPLIES WITH Airbus AITM6-1001 Testing Method	COMPLIES WITH Pratt & Whitney Requirements	COMPLIES WITH The Boeing Co Requirements	COMPLIES WITH ISO 3059-12 Standard	COMPLIES WITH USAF Requirements
GX SERIES – OVERHEAD LIGHT									
GX Orion REMOTE	✓	1 500-7 000	✓	-	-	-	-	✓	-
GX Orion UV & WH	✓	≈ 7 000	✓	✓	✓	✓	-	✓	-
GX Orion UV	-	≈ 4 500	✓	✓	✓	✓	✓	✓	✓
BB 2.0 SERIES – HANDHELD LIGHT									
BB 2.0 Helios	-	≈ 9 000	✓	-	✓	✓	-	✓	✓
BB 2.0 Ikaros	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
BB 2.0 Artemis	-	≈ 22 000	✓	-	-	-	-	✓	-
MB 3.0 SERIES – HANDHELD LIGHT									
Hercules Ex	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
MB 3.0 Zeus	✓	≈ 4 500	✓	✓	✓	✓	✓	✓	-
MB 3.0 Zeus with Athena	✓	≈ 4 500	✓	✓	✓	✓	✓	✓	-
MB 3.0 Hermes	-	≈ 4 500	✓	✓	✓	✓	✓	✓	✓
MB 3.0 Hermes with Athena	-	≈ 4 500	✓	✓	✓	✓	✓	✓	✓
MB 3.0 Selene	✓	≈ 9 000	✓	-	✓	✓	-	✓	-
MB 3.0 Selene with Athena	✓	≈ 9 000	✓	-	✓	✓	-	✓	-
MB 3.0 Atlas	-	≈ 9 000	✓	-	✓	✓	-	✓	✓
MB 3.0 Atlas with Athena	-	≈ 9 000	✓	-	✓	✓	-	✓	✓
MB 2.0 SERIES – FLASHLIGHT / HEADLIGHT									
UVG3 2.0 Spotlight	-	≈ 80 000	✓	-	-	-	-	✓	-
UVG3 2.0 Midlight	-	≈ 9 000	✓	-	✓	✓	-	✓	✓
UVG3 2.0 Floodlight	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
UVG5 2.0 Spotlight	optional	≈ 80 000	✓	-	-	-	-	✓	-
UVG5 2.0 Midlight	optional	≈ 9 000	✓	-	✓	✓	-	✓	✓
UVG5 2.0 Floodlight	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓

PLEASE NOTE: The above models are in compliance with the above ASTM and ISO standards as well as industry specifications as indicated on the table above irrespective of the power source (Battery or Mains).