

M37 Plus DAILY MAINTENANCE RECOMMENDATION

IN THE MORNING:

- ✓ Close the wash tank drain.
- ✓ Turn on water supply to the processor.
- ✓ Close the top cover to the processor.
- ✓ Switch on the processor and check error codes.
- ✓ Clean the feed tray (T2 Max).
- ✓ Wait for the “**READY**” message on the processor.
- ✓ Check replenishment tank developer & fixer levels while processor is warming up.
- ✓ Check developer & fixer waste containers (if applicable).
- ✓ Once processor says “**READY**” feed through a minimum of two green cleaning films (14” x 17”), if processor sat for the weekend feed through a minimum of five green cleaning films.

IN THE EVENING:

- ✓ Turn off the water supply.
- ✓ Switch off the processor.
- ✓ Open the wash tank drain to prevent algae growth.
- ✓ Open the top cover of the processor (1).
- ✓ Use a water spray bottle to spray the drive gears above solution level with warm water.
- ✓ Place the top cover (1) back on the processor either at an angle or elevated allowing the processor to vent which will prevent chemical condensation and leave top cover lid (2) open.



1	top cover
2	top cover lid



M37 Plus WEEKLY MAINTENANCE RECOMMENDATION

- ✓ Wipe external surfaces of Processor / Enclosures / Panels with a wet cloth to remove any chemical / dirt deposits.
- ✓ Check and, if appropriate, clean (T2 Max) the Wash Rack / Wash Tank to remove any bio-slime.
- ✓ Check all Crossover Rollers (Dev & Fix Rack) and, if appropriate, remove rack and clean (T2 Max) to remove any chemical / dirt deposits. Do **NOT** use abrasive materials to clean the rollers.