




TATSUNO Made in Japan

Highly reliable popular dispenser equipped with global-standard components

Sunny-Ell/Lever.

Dispensing Pump PAT.PEND.



Long-lasting, A fine display uses high-visibility bright red LED backlight



Large, easy-to-read characters and compact layout

 Supports up to 5-digit unit price and 7-digit money amount & volume

Standard-equipped with user-friendly preset keypad



Secure, password-protected registration

Standard-equipped with over-voltage protector (OVP) to protect electrical device from high voltage


- Supported by full range of options
 - Electromaginetic Totalizaer
 - Sight Glass
 - POS Interface








Types



Dimensions



Specifications

Specifications	
Delivery Speed	Standard speed (Gasoline/Diesel) : 45 L/min **Manual drive is not provided **Delivery speed is fluctuate by installed components (Suction Type)
Suction Head (Suction Type)	4 m (Gasoline Column)
Measuring Accuracy	+/- 2.5/1000
Display Type	Micro-computer type electronic counter at non-hazardous area
Price and Volume Indication	Price : 7 digits 0.01~ 99,999.99 Volume : 7 digits 0.01~ 99,999.99 Unit Price : 5 digits 0.01~ 999.99
	*Decimal places is possible to change according to each local specification.
Size of Display Character	Price Readout : 30H × 120W mm Volume Readot : 30H × 120W mm Unit Price Readout : 24H × 98W mm
Color of Display Character	Black characters with LED backlight. (LCD)
Reset	Automatic Reset
Totalizer	Electronic: 10 digits 99 999 999.99 Liters (Displayed on counter)
Daily Totalizer	Electronic: 10 digits 99 999 999.99 Liters (Displayed on counter)
Keypad	Volume and amount preset can be set up from dispenser. Numeric key only
Over Voltage Protector	Standard support
Self-Diagnosis	Standard support
Initial-setting Method	By using keypad
Pulser	0.01 L/pulse
Pump (Suction Type)	Internal Silent Gear Pump with air separator, by-pass valves, suction strainer and check valves
Meter	4-Piston Type Positive Displacement Meter with electronic calibration system
Flow Control Valve	Solenoid Valve
Motor (Suction Type)	Explosionproof, Continuous duty motor with over load Protection 3-Phase 1 HP (380 V)
Hose	3/4" x 16 ft (15ft. long with 1ft short hose for safety breakaway coupling)
Nozzle	3/4" Automatic stop nozzle
Swivel	Single Swivel

Note: The delivery speed of the pump may change due to the following conditions if it is used beyond Tatsuno's installation and operational instructions:

- Size and length of hose
 Size and type of nozzle/swivel

3) Oil products, suction condition, and local piping conditions
 Specifications are subject to change with or without prior notice.



TATSUNO CORPORATION

International Marketing Dept.

Head office: 12-13, Shibaura 2-chome, Minato-ku, Tokyo108-8520, Japan

Telephone: +81-(0)50-90000-0555 Fax: +81-(0)3-3452-6082

http://www.tatsuno.co.jp/