

# PT-DLR-B-4I-5C3P

## 4" LED Baffle Retrofit Recessed Downlight with CCT and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------

Why stock three different color temperatures when you can have 5-in-1? Retrofit residential downlights are taking the market by storm! Available in 4" and featuring color selectable technology that lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K.


Ideal use for residential housings, high-rise condominiums, the healthcare industry, universities/campuses, shopping centers and hospitality.

**CCT**  
SELECTABLE

**WATTAGE**  
SELECTOR



### TUNABLE 5-1 CCT SELECTOR



Easily flip the switch for desired CCT. It's that simple!

### CONSTRUCTION

PC driver housing and aluminum reflector with architectural white finish. Easy clip-in to existing can housing. Standard gasket included to ensure proper seal. E26/GU24 base.

### ELECTRICAL

Luminaire is built with the highest quality 120V drivers, ensuring energy efficiency.

### ENERGY SAVINGS

80% more energy savings than halogen lamps. Low heat production requires less air-conditioning requirements, further increasing energy cost savings.

### DIMMING

Triac dimmable down to 5%. Compatible with most major brands of dimmers.

### LISTING

ETL Listed, FCC, RoHS, CE & Energy Star Listed

NOMINAL WATTAGE	DELIVERED LUMENS	EFFICACY
8W	550 LM	up to 70 lm/W
10W	700 LM	
12W	850 LM	

Based on 4000K setting. Actual lumens may vary.

### TECHNICAL SPECIFICATION

VOLTAGE	120V
POWER FREQUENCY	60 Hz
CRI	90
CCT	2700K   3000K   3500K   4000K   5000K
BEAM ANGLE	100°
IP RATING	IP40, Suitable for damp locations
DIMMABLE	Triac dimming
POWER FACTOR	>0.9
WARRANTY	5 year limited



### MODEL NUMBER(S)

MODEL#	WATTS	LUMENS	LM/WATT	CCT	CRI	VOLTAGE
PT-DLR-B-4I-5C3P	8W/10W/12W	550/700/850	up to 70	2700K/3000K/3500K/ 4000K/5000K	>90	120V, 60Hz

# PT-DLR-B-4I-5C3P

## 4" LED Baffle Retrofit Recessed Downlight with CCT and Wattage Selector

Catalog Number:	Project Name:	Note:	Date:	Type:
-----------------	---------------	-------	-------	-------



Change color temperature with the simple flip of a switch

2700K | 3000K | 3500K | 4000K | 5000K

Change lumen output for desired application

**8W**  
550 Lm


**10W**  
700 Lm

**12W**  
850 Lm



Product weight: .28 lb

### DIMENSION



- Fits most 4" recessed housings
- Sealing gasket standard

### ACCESSORY



E26 Adapter included for easy retrofitting

### COMPATIBLE DIMMERS

LUTRON	LEVITON
<ul style="list-style-type: none"> <li>• CT-600PR</li> <li>• MSCL-0P153MH</li> <li>• DVWCL-153PH</li> <li>• TGCL-153PR</li> <li>• MA-RR</li> <li>• DVCL-153PR</li> <li>• SCL-153PR</li> <li>• P-PKG1W-WH-R</li> <li>• MACL-153MH</li> </ul>	<ul style="list-style-type: none"> <li>• R00-RNL06-TW</li> <li>• R50-IPL06-10M</li> </ul>


### TRIM RING REPLACEMENT (SOLD SEPARATELY)



**TR-DLR-4I-BK**  
4" Black Trim Ring Replacement



**TR-DLR-4I-BN**  
4" Brush Nickel Trim Ring Replacement



**TR-DLR-4I-BZ**  
4" Bronze Trim Ring Replacement