











COUNTER TOP GAS STOVE







▲ GB-2Y













Corrosion Resistance



The Performance Characteristics Of

• The pot stove USES the direct fire to avoid cleaning the stove head, the electronic spark valve body, the extra-thick stainless steel shell, the electronic assembly air supply, the energy saving stove, when the water boils quickly, until the boiling, you will find the bottom of the pot is full of bubbles, not just in the middle. Heating is uniform, suspended combustion, carbon monoxide emissions are only 0.032%, far below the national environmental standards. No smoking pot, no rust, no blockage, safety insurance.

Model:	Machine Size(mm):	Thermal Power:	GAS Type:
GB-2Y	375x800x360	5KW x 2	LPG, Natural Gas
GB-4Y	765x800x360	5KW x 2	LPG, Natural Gas







Model:	GBS-1YC
Dimension:	380x460x215mm
Thermal Power:	5KW x 1
GAS Type:	LPG, Natural Gas



Model:	GBS-2YC
Dimension:	760x460x215mm
Thermal Power:	5KW x 2
GAS Type:	LPG, Natural Gas



Model:	GBS-2Y
Dimension:	660x490x360mm
Thermal Power:	5KW x 2
GAS Type:	LPG, Natural Gas



Model:	GBS-3Y
Dimension:	990x490x360mm
Thermal Power:	5KW x 3
GAS Type:	LPG, Natural Gas

079 080