

USG SECUROCK® BRAND

SALES AND INFORMATION QUICK REFERENCE

GYPSUM-FIBER ROOF BOARD



GLASS-MAT ROOF BOARD



CEMENT ROOF BOARD



GYPSUM- CONCRETE PATCH



CONCRETE ROOF DECK



- **USED FOR ADHERED OR TORCH APPLIED ROOFING SYSTEMS**
 - EXCEPTIONAL BOND AND LOW ABSORPTION OF ADHESIVE
 - MOISTURE AND MOLD RESISTANT, NON-IRRITATING SURFACE
 - EXCELLENT WIND UPLIFT RESISTANCE, NO FACER DELAMINATION
 - MANUFACTURED FROM 97% RECYCLED MATERIAL
 - 1,800 PSI COMPRESSIVE STRENGTH AND CLASS A - UL 790 RATED
 - IDEAL FOR A THERMAL BARRIER ON NON-RATED DECKS
- **USED FOR MECHANICALLY ATTACHED SINGLE PLY ROOF SYSTEMS**
 - SUPPORTS ROOF MEMBRANE FROM HAIL AND FOOT TRAFFIC
 - TIGHT GLASS MAT SURFACE = BETTER CUTTING, LESS ITCH
 - 700-1,000 COMPRESSIVE STRENGTH, FAR EXCEEDS COMPETITIVE BOARDS
- **IDEAL FOR USE AS A COVER BOARD FOR LIQUID APPLIED SYSTEMS**
 - LIGHTEST CEMENT BOARD AVAILABLE, WATER DURABLE, MOLD RESISTANT
 - WILL NOT ROT, WARP, DELAMINATE OR DISINTEGRATE
 - NON-COMBUSTIBLE AND EASY TO CUT AND FASTEN
 - 1,000 PSI COMPRESSIVE STRENGTH
- **FOR REPAIRING POURED IN PLACE DECKS – GYPSUM AND LIGHT WEIGHT CONCRETE**
 - FAST INSTALLATION, MIXED ON THE ROOF WITH WATER
 - NONCOMBUSTIBLE, EDGE CAN BE FEATHER TROWELED
 - DURABLE, OVER 500 PSI COMPRESSIVE STRENGTH
 - ONE GALLON CLEAN WATER-ONE BAG YIELDS-ONE CUBIC FOOT
- **STRONG, DURABLE CONCRETE PANEL; GREAT UPLIFTS**
 - DIMENSIONALLY STABLE; PANEL WILL NOT BUCKLE OR WARP LIKE WOOD SHEATHING; NO MOISTURE CURING ISSUES LIKE STRUCTURAL CONCRETE
 - INSTALLS FAST AND EASY: CIRCULAR SAW CUTS; SCREWS FOR FASTENING
 - ONLY TOTALLY NON-COMBUSTIBLE PRE-ENGINEERED PANEL AVAILABLE
 - MEETS CRITERIA OF ASTM E136-12 FOR USE IN ALL TYPES OF NON-COMBUSTIBLE CONSTRUCTION.

For Specification Assistance or questions contact your local Delta Rep Group Team Member

Delta Rep Group	Wayne Heironimus	727-512-8581	Wayne@deltarepgroup.com
Delta Rep Group	Dawn Holsinger	727-420-3112	Dawn@deltarepgroup.com
Delta Rep Group	Justin Burnham	813-597-7797	Justin@deltarepgroup.com