<u>Comparison Chart</u> <u>LED Lights vs. Incandescent Light Bulbs vs. CFLs</u>

Energy Efficiency & Energy Costs	Light Emitting Diodes (LEDs)	Incandescent	
	• • • •	Light Bulbs	Compact Fluorescents (CFLs)
Life Span (average)	50,000 hours	1,200 hours	8,000 hours
Watts of electricity used (equivalent to 60 watt bulb). LEDs use less power (watts) per unit of light generated (lumens). LEDs help reduce	6 - 8 watts	60 watts	13-15 watts
greenhouse gas emissions from power plants and lower electric bills			
Kilo-watts of Electricity used (30 Incandescent Bulbs per year equivalent)	329 KWh/yr.	3285 KWh/yr.	767 KWh/yr.
Annual Operating Cost (30 Incandescent Bulbs per year equivalent)	\$32.85/year	\$328.59/year	\$76.65/year
Environmental Impact	Light Emitting Diodes (LEDs)	Incandescent Light Bulbs	Compact Fluorescents (CFLs)
Contains the TOXIC Mercury	No	No	Yes - Mercury is very toxic to your health and the environment
RoHS Compliant	Yes	Yes	No - contains 1mg-5mg of Mercury and is a major risk to the environment
Carbon Dioxide Emissions (30 bulbs per year) Lower energy consumption decreases: CO2 emissions, sulfur oxide, and high-level nuclear waste.	451 pounds/year	4500 pounds/year	1051 pounds/year

Important Facts	Light Emitting Diodes (LEDs)	Incandescent Light Bulbs	Compact Fluorescents (CFLs)
Sensitivity to low temperatures	None	Some	Yes - may not work under negative 10 degrees Fahrenheit or over 120 degrees Fahrenheit
Sensitive to humidity	No	Some	Yes
On/off Cycling Switching a CFL on/off quickly, in a closet for instance, may decrease the lifespan of the bulb.	No Effect	I Some	Yes - can reduce lifespan drastically
Turns on instantly	Yes	Yes	No - takes time to warm up
Durability	can handle jarring	idiace or filament can	Not Very Durable - glass can break easily
Heat Emitted	3.4 btu's/hour	85 btu's/hour	30 btu's/hour
Failure Modes	Not typical	l Some	Yes - may catch on fire, smoke, or omit an odor
<u>Light Output</u>	Light Emitting Diodes (LEDs)	Incandescent Light Bulbs	Compact Fluorescents (CFLs)
Lumens	Watts	Watts	Watts
450	4-5	40	9-13
800	6-8	60	13-15
1,100	9-13	75	18-25
1,600	16-20	100	23-30
2,600	25-28	150	30-55