



# D260PDDZ

DUAL PRESSURE \ DUAL CAPACITY \ TIER 4 FINAL \ DEUTZ ENGINE \ PORTABLE COMPRESSOR



260CFM/100PSI 185CFM/150PSI



# SPECIFICATIONS

## Compressor

Model	D260PDDZ
Rated Delivery @ Rated Pressure	260 CFM @ 100 psi - 185 CFM @ 150 psi 7.4 m <sup>3</sup> /min @ 6.9 bar - 5.2 m <sup>3</sup> /min @ 10.4 bar
Operating Pressure Range	70 psi (4.8 bar) - 150 psi (12 bar)
Estimated Weight, Serviced	2,500 lbs
Dimensions L x W x H (in")	134" x 55" x 70"

## Engine

Type	Diesel
Make & Model	DEUTZ TD2.9L4 Tier 4 Final (Turbo)
Idle Speed	1750 RPM
Fuel Tank Capacity	29 gal (109.8 L)
Horsepower @ rated RPM	74 hp
Full Load Speed	2500 RPM @ 260 CFM 1900 RM @ 185 CFM

### 260 CFM \ 100 psi

#### QTY Pneumatic Tool and Operation

3x	90 lb class Paving Breakers for large demolition
4x	60 lb class Paving Breakers for large demolition
4x	40 lb class Paving Breakers for Bridge deck repair
5x	30 lb class Paving Breakers for light demolition
6x	30 lb class 8" Rivet Busters for Bridge Deck and medium demolition
5x	35 lb class 11" Rivet Busters for Bridge Deck and heavy demolition
8x	15 lb class 3" Chipping Hammers for light demolition and concrete restoration
1x	SP5-48 Air Gun for crack blowing, snow and debris removal
2x	SP5-48-70 Air Guns for crack blowing, snow and light debris removal



SPB-90: 90 lb Paving Breaker

### 185 CFM \ 150 psi

#### Sandblasting and pipe testing:

Will run a # 5 or 5/16" nozzle up to 140 psi at the tank

Will run a #6 or 3/8" nozzle up to 100 psi at the tanks

## FEATURES

- » 127mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter with Safety Elements - External Access
- » Multiple Service Connections
- » Oil Level Sight Gauge
- » Side by Side Coolers for Compressor and Engine
- » DEUTZ TD2.9L4 Tier 4
- » Steel Fuel Tank
- » Cooler Access Panel for Cleaning
- » Safety Chains
- » 15" Wheels & Radial Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Tool Boxes in Each Side with Lockable Handles
- » Galvanneal Enclosure
- » Galvanized Wheel Wells and Internal Panels
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and Protection System
- » Automatic Blowdown Valve
- » Stop, Turn and Tail Lights
- » Unloaded Starting
- » High-Low Selector Switch

## CONTROLLER

### Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- » Compressor temperature
- » Discharge pressure
- » Engine oil pressure
- » Engine Coolant temperature
- » Voltmeter
- » Tachometer
- » Fuel level - low fuel warning and shutdown
- » Fault Codes
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet

## Sullivan-Palatek, Inc.

1201 West US Highway 20  
Michigan City, IN 46360

219.874.2497

sullivan-palatek.com

info@palatek.com