



Pool Deck Coatings

CSI Division 3: Concrete - Decorative & Repair



elite crete systems

Engineered High Performance Surfaces & Flooring



Pool Deck Coatings are polymer modified to act as surface repair or an aesthetic finish that can be applied to new or existing concrete surfaces. The coating is actually stronger than concrete and can withstand vehicular traffic and harsh temperatures (extreme hot or cold).

BENEFITS

- Virtually unlimited designs, patterns, textures and color options.
- Non-slip even when wet.
- Can create the authentic look and feel of any stone, brick, tile, wood and even just plain new concrete.
- Available in any color combination to match surrounding design.
- Cost effective compared to: full depth stamped concrete, pavers, brick, real stone or integrally colored concrete.
- Extreme durability for high traffic areas.
- Very low maintenance.
- Highly resistant to deicing salts, freeze/thaw climates, extreme heat, wet conditions and UV rays.
- Quick installation time.
- Can be installed pre or post construction.
- For new or existing concrete surfaces.



TECHNICAL DATA

PROPERTY	RESULT
Compressive Strength	
1 day	1350 to 1425 psi
7 days	3655 to 3750 psi
28 days	4565 to 4800 psi
Flexural Strength	
7 days	875 to 990 psi
28 days	1415 to 1450 psi
Tensile Strength	
7 days	350 to 375 psi
28 days	700 to 750 psi
Abrasion Loss	
Unsealed	0.17 to 0.19%
Density	
7 days	1.17 to 1.19 g/cm ³
28 days	1.89 to 1.95 g/cm ³
Shear Bond	
7 days	320 to 335 psi
28 days	575 to 595 psi
Cohesive Strength	
7 days	52 to 58 psi
28 days	98 to 103 psi
Impact Resistance	
7 days	16 to 19 inch/lbs.
28 days	28 to 29 inch/lbs.

Variance in results due to different applications and thickness.



6 Old Orchard Lane, Unit 100
Kingston, MA 02364
781-214-0333 Office 781-636-1118 Fax
contactus@royalepoxyfloors.com
www.royalepoxyfloors.com

The information herein is general information to assist our customers in determining whether our products are suitable for their specific applications. Our products are intended for sale to commercial and industrial customers. We require that customers should inspect and test our products before use to satisfy themselves as to the content and suitability for the applications they intend to use our products for. Nothing herein shall constitute any warranty expressed or implied, including any warranty of merchantability or fitness for a particular purpose, nor is replacement of our materials and in no event shall we be liable for incidental or consequential damages.