



S30 Ash Tray Cup Holder Installation Manual



Index:

1. Disclaimer
2. Parts List
3. Installation Guide

Disclaimer

A vehicle modified with MilkFab Engineering products is intended for off road use only. It is the purchaser's responsibility to check and comply with all local, state, and federal laws prior to operating vehicle. Installation and use of performance products may also affect and void warranty. MilkFab Engineering shall not be liable for direct, indirect, incidental, or consequential damage to persons or property that might be claimed as a result from installation, improper installation, and failure of part including claims for delay, loss of profit, or labor.

Parts List

Parts Included

Quantity	Description
1	MilkFab Ash Tray Cup Holder Insert
2	Front Clip Mounting Screws

Additional Parts Needed

Quantity	Description
1	Front Spring Clip from Original Ash Tray

Installation Guide

WARNING! Extreme caution should be taken when performing ANY maintenance or performance upgrades to your vehicle. Please observe and abide by any Warning or Caution labels placed on the various components and tools used when servicing your vehicle. If you have any questions regarding the installation or the various components included with the MilkFab S30 Ash Tray Cup Holder kit, consult with a Professional Mechanic or contact MilkFab Engineering for more information.

Disassembly:

****BEFORE YOU BEGIN!****

Remove all contents from the MilkFab S30 Ash Tray Cup Holder kit and verify that ALL necessary hardware is present.

1. First remove the existing ash tray from the center console by pulling up on the front part of the ashtray.
2. Remove the front spring clip from the original ashtray by removing the two phillips head screws.



3. After the front spring clip is removed from the ash tray, set it aside and ready your cup holder insert(s).

Installation:

****note****

It may be necessary to bend the front spring clip outward for the cup holder to fit snug into the ash tray location.

Do Not attempt to bent the clip while attached to the cup holder, it will remove the threads from the holes.

4. Attach the spring clip on the front of the cup holder insert using the provided hardware. Tighten the screws to a snug fit ensuring that you do not over tighten. **Once snug, Do Not continue to tighten.**



5. Install cup holder the opposite way that the ashtray was removed.
6. Enjoy a celebratory drive with your favorite (non-alcoholic) beverage!