

## **RA-42W** LOW ADHESION BACKSIDE FOR MASKING TAPES

**RA-42W** is a water based release coating and low adhesion backside (LAB) designed for tapes with paper as a substrate.

Provides an easy-to-moderate release from adhesives that are based on acrylic, natural rubber, SBR or SIS block copolymers. Typical tape backings used with **RA-42W** are latex-impregnated crepe and flat papers.

**RA-42W** are ready to use or may be diluted with water to 20-40% total solids, depending on the paper, adhesive, and coating method that you choose. Coating methods include Mayer rod, rotogravure roll, knife over roll, and various slot/roll configurations.

Recommendation for laboratory evaluation for saturated crepe is as follows: Draw down the emulsion as is, or dilute with water using a #6 Mayer rod and dry in air oven at 100-150°C for 5 minutes or until dry. Dry coating weights may be in the 1-10 g/sm range depending on the paper's porosity and degree of crepe and adhesive.

In plant scale operations, release properties develop by flashing off water at 120-175°C (250-350°F) for 2-10 seconds, depending on web speed, oven length, drying air temperature and velocity, and oven configuration.



TYPICAL PROPERTIES	
APPEARANCE	Μιικγ Γιουιρ
TOTAL SOLIDS	40-42%
рН	8

<b>UNWIND ADHESION VALUE</b> - g/2"(5cm) BASED ON PREMIUM OPP PACKING TAPE WITH SIS-BASED PSA	
GREEN (OFF-SLITTER)	EASY - 300
AGE 150°F (65°C) FOR 72 HR	MODERATE - 450
AGE 120°F (49°C) AT 90% RH FOR 72HR	MODERATE - 400
SHELF STORAGE 12 MONTHS	MODERATE - 400

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be accurate, but their accuracy or completeness are not guaranteed. Before using, user shall determine the suitability of any products for user's intended use, and user assumes all risk and liability whatsoever in connection therewith. Hitac Adhesives and Coatings Company disclaims all warranties, both express or implied, including all warranties of merchantability and fitness for a particular purpose.



HITAC ADHESIVES AND COATINGS COMPANY 14722 SPRING AVENUE, SANTA FE SPRINGS, CA 90670 TEL: 562-802-8834 | FAX: 562-921-7363 | ORDERS@HITACADHESIVES.COM | WWW.HITACADHESIVES.COM

©2016 HITAC ADHESIVES AND COATINGS COMPANY. ALL RIGHTS RESERVED. REV20161212-0.0 NO PART OF THIS DOCUMENT MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING, OR OTHERWISE, WITHOUT PRIOR WRITTEN PERMISSION OF HITAC ADHESIVES AND COATINGS COMPANY