

7.2 Panel

Commercial Roof and Wall Panel



Symmetrical and strong for contemporary design.

Available in 24 and 26 ga., our 7.2 panel is a great choice for both commercial and industrial applications. This exposed fastener panel can be installed horizontally or vertically. It's symmetrical, repeating pattern gives the classic deep-rib look that architects love, and is great for canopies and carports.

7.2 panel is available in both 36" and 28.8" coverage.

- Excellent load and spanning strength.
- Available in 36" and 28.8" coverage.
- Ideal for canopies, carports, and low-pitch commercial roofs.



RECOMMENDED
1/2:12
PITCH
AND ABOVE

24 GAUGE
26

36" OR
28.8"
OVERALL
COVERAGE

1 1/2"
MAXIMUM
RIB HEIGHT



WWW.CENTRALSTATESCO.COM

Copyright © 2024, Central States Manufacturing, Inc., All Rights Reserved.
CentralGuard® is a trademark of Central States® Manufacturing, Inc.
Galvalume® is a registered trademark of BIEC International, Inc.

FLYR_72_240412

Choose CentralGuard® for the best protection and a lifetime warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Available on our Prime panels, the CentralGuard name is a guarantee that you have the best protection and a lifetime paint warranty.

Choose Prime for the perfect balance of fade protection, rust blocking, and dent resistance. Upgrade to Ultra for projects that demand the ultimate dent resistance.

	OUR BEST SELLER! PRIME CentralGuard	ULTIMATE DENT RESISTANCE ULTRA CentralGuard
FADE PROTECTION		
Paint Warranty	LIFETIME	
Paint Thickness	THICKER 1.0 mil	
Fade Warranty	30-YEAR	
Fade Protection	✓✓	
RUST BLOCKING		
Advanced Rust Blocking	✓	✓
Perforation Warranty	50-YEAR	50-YEAR
Substrate Thickness	1.60 mil	1.60 mil
DENT RESISTANCE		
Advanced Dent Resistance	✓✓	✓✓
Steel Thickness	THICK	THICKEST
Steel Gauge	26 ga.	24 ga.

7.2 (36" Coverage)



7.2 (28.8" Coverage)



MINIMUM SPECIFICATIONS FOR PRIME PAINTED PANELS

GAUGE

26 ga. | 24 ga.

STEEL THICKNESS

26 ga. 0.0185" | 24 ga. 0.023"

PAINT THICKNESS

Top coat paint: .70 mil
 Top coat primer: .30 mil
 Bottom coat backer: .35 mil
 Bottom coat primer: .35 mil

TOTAL THICKNESS

26 ga. 0.0202" | 24 ga. 0.0247"

RUST PROTECTANT SUBSTRATE

Galvalume® AZ50

STEEL STRENGTH

80,000 PSI (26 ga.) | 50,000 PSI (24 ga.)

PAINT SYSTEM

SMP

WARRANTY

Lifetime limited paint adhesion
 30-yr. chalk and fade
 50-yr. Galvalume perforation

COLOR AVAILABILITY

36" COVERAGE PRIME

- Brilliant
- Burnished Slate
- Charcoal
- Galvalume
- Gray
- Light Stone

36" COVERAGE ULTRA

- Galvalume

28.8" COVERAGE PRIME

- Brilliant
- Brown
- Burgundy
- Burnished Slate
- Colony
- Copper Metallic
- Crimson
- Charcoal
- Desert
- Fern
- Gallery
- Galvalume
- Gray
- Hawaiian
- Hunter
- Light Stone
- Polar
- Rustic
- Tan

Find more information at
centralstatesco.com