

# LED Gas Station Canopy

## Hyper Series



### DESCRIPTION

Designed for superior performance and durability, our LED Gas Station Canopy Light delivers industry-leading efficiency at 170 lm/W, making it one of the highest-performing fixtures on the market.

Built with a rugged die-cast aluminum housing and equipped with six strategically placed vents, it ensures excellent heat dissipation for long-lasting reliability. The IP67 rating provides complete protection against dust and water ingress, ideal for outdoor and demanding environments.

A frosted glass lens minimizes glare for comfortable visibility, while the sleek white finish offers a clean, modern look that complements any installation.

Perfect for gas stations, this versatile fixture is also an excellent choice for any indoor or outdoor flat ceiling applications.

### FEATURES

- Die-Cast Aluminum Housing
- Marine-Grade Powder Coating
- Frosted Tempered Glass Lens
- 304 Stainless Steel Hardware
- High-Efficiency Heat Sink
- 0-10V Dim to Off
- Mid-Body Vent Design Optimizes Airflow and Cooling

### MARKETS

- Gas Station
- Warehouses
- Cold Storages
- Parking Garage
- Underpass
- Hallways

### CERTIFICATIONS



# LED Gas Station Canopy

## Hyper Series

### SPECIFICATIONS

#### PERFORMANCE

Efficacy (LPW): 170  
CRI: 80  
Operating Temp: -22 °F to 122 °F (-30 °C to 50 °C)

#### LIFESPAN

Life (@L70): 85,000 hours  
Warranty: 5 years

#### PHYSICAL

Finish: Marine-Grade Matte Powder Coating  
Color: White  
Housing: Die-Cast Aluminum

#### ELECTRICAL

Input Voltage: 120-277V (277-480V Optional)  
Input Frequency: 50/60Hz  
PF: ≥.95  
THD: ≤ 20%  
Surge Protection: 6KA  
Dimming: 0-10V  
Minimum Dimming: Dim to Off  
Aux. Voltage: 12VDC  
Driver Class: Class P  
Whip/Cord: 2 ft  
Sensor: Optional Photocell / Dimming Motion / Bluetooth

#### OPTICAL

Standard Lens: Frosted  
Lens Material: Tempered Glass

#### MOUNTING

Flush Mount  
3/4" Pendant Mount

#### INDUSTRY STANDARDS/RATINGS


IP Rating: IP67  
IK Rating: IK06  
Location: Wet  
Outdoor Rated: Yes  
UL/ETL: UL  
DLC: 5.1  
FCC: Yes  
RoHS: Yes  
CE: Yes

SKU	Wattage	Current Draw	Lumens
X-GSC-90W	90W	0.75A@120V 0.33A@277V 0.19A@480V	15,300
X-GSC-120W	120W	1A@120V 0.44A@277V 0.25A@480V	20,400
X-GSC-150W	150W	1.25A@120V 0.55A@277V 0.32A@480V	25,500

# LED Gas Station Canopy

## Hyper Series

### DIMENSIONS / WEIGHT



### ORDERING INFORMATION

#### X - GSC - Wattage - CCT

X	GSC	90W	30
		120W	35
		150W	40
			45
			50
			57

Example: X-GSC-150-50 (150W GSC Model with 5000K Color Temperature)

Note: 5000K is stocked locally.

# LED Gas Station Canopy

## Hyper Series

### ACCESSORIES



U-S-PSDMS-T



U-S-BLMS-T



U-S-RC

### SENSORS & CONTROLS

U-S-RE	Receptacle for Plug&Play Sensor
U-S-PSDMS-T	3rd Gen Plug&Play Dimming Motion Sensor
U-S-BLMS-T	Bluetooth Plug&Play Dimming Montion Sensor
U-S-RC	Remote for Step Dimming Motion Sensors

### HIGH VOLTAGE INPUT OPTIONS

U-RD-150W-480V	277-480V (≤150W) Driver Swap
----------------	------------------------------