

# LED UFO High Bay

## Industrial Series



### DESCRIPTION

Engineered with advanced LED technology, the Industrial Series UFO High Bay delivers superior efficiency, longevity, and performance. Rated IP67 for wet locations, this fixture provides high light output while consuming less energy than standard high bays. Integrated 0-10V dimming allows for precise brightness control, optimizing energy savings and illumination as needed.

Constructed with a one-piece aluminum heat sink for exceptional thermal management, this fixture is built for durability and long-term reliability. Optional accessories include clear lens, 40W backup battery, trunnion mount and 3/4" pendant mount adapter.

Ideal for commercial and industrial environments, it's perfect for warehouses, supermarkets, retail spaces, gyms, garages, and general task lighting applications.

### FEATURES

- Die-Cast Aluminum Housing
- Marine-Grade Powder Coating
- Tempered Glass Lens
- 304 Stainless Steel Hardwares
- High-Efficiency Heat Sink
- 0-10V Dim to Off

### MARKETS

- Warehouses
- Cold Storages
- Exhibit Halls
- Shopping Centers
- Indoor Arenas
- Gymnasiums

### CERTIFICATIONS



# LED UFO High Bay

## Industrial Series

### SPECIFICATIONS

#### PERFORMANCE

Efficacy (LPW): 165  
CRI: 80  
Operating temp: -22°F to 122°F (-30°C to 50°C)

#### LIFESPAN

Life (@L70): 65,000 hours  
Warranty: 5 years

#### PHYSICAL

Finish: Marine-Grade Matte Powder Coating  
Color: Black (White optional)  
Housing: Die-Cast Aluminum

#### ELECTRICAL

Input Voltage: 120-277V (277-480V Optional)  
Input Frequency: 50/60Hz  
PF: ≥.95  
THD: ≤ 20%  
Surge Protection: 4KA  
Dimming: 0-10V  
Minimum Dimming: Dim to Off  
Aux. Voltage: 12VDC  
Driver Class: Class P  
Whip/Cord: 4 ft  
Sensor: N/A

#### OPTICAL

Standard Lens: Frosted  
Optional Lens: Clear  
Lens Material: Tempered Glass (Polycarbonate optional)

#### MOUNTING

Hanging Ring (included)  
Trunnion Bracket  
3/4" Pendant Mount Adapter

#### INDUSTRY STANDARDS/RATINGS


IP Rating: IP67  
IK Rating: IK06  
Location: Wet  
Outdoor Rated: Yes  
UL/ETL: UL  
DLC: 5.1  
FCC: Yes  
RoHS: Yes  
CE: Yes

SKU	Wattage	Current Draw	Lumens
U-UHBHO-100	100W	0.84A@120V 0.37A@277V 0.21A@480V	16,500
U-UHBHO-150	150W	1.25A@120V 0.55A@277V 0.32A@480V	24,750
U-UHBHO-240	240W	2A@120V 0.87A@277V 0.5A@480V	39,600

# LED UFO High Bay

## Industrial Series

### DIMENSIONS / WEIGHT



Wattage	Diameter	Height	Weight
100W / 150W	13.2"	6.7"	12 lbs
240W	17"	6.7"	20 lbs

### ORDERING INFORMATION

#### U - UHBHO - Wattage - CCT

U	UHBHO	100	30
		150	35
		240	40
			45
			50
			57

Example: U-UHBHO-150-50 (150W UHBHO Model with 5000K Color Temperature)

Note: 4000K and 5000K are stocked locally.

# LED UFO High Bay

## Industrial Series

### ACCESSORIES

#### MOUNTING OPTIONS

<b>U-UHBHO-YBR-100/150</b>	Yoke Bracket for 100&150W
<b>U-UHBHO-YBR-240</b>	Yoke Bracket for 240W
<b>U-MH-PM-HB</b>	3/4" Pendant Mount for High Bays

#### HIGH VOLTAGE INPUT OPTIONS

<b>U-RD-150W-480V</b>	277-480V ( $\leq 150W$ ) Driver Swap
<b>U-RD-240W-480V</b>	277-480V ( $\leq 240W$ ) Driver Swap

#### LENS OPTIONS

<b>U-UHBHO-CPL</b>	Clear Polycarbonate Lens for UHBHO
<b>U-UHBHO-FPL</b>	Frosted Polycarbonate Lens for UHBHO



#### BACKUP BATTERY OPTIONS

<b>U-EI-HB-25-C</b>	25W Emergency Inverter (for All High Bays)
<b>U-EI-HB-40-C</b>	40W Emergency Inverter (for All High Bays)