

LED Tunable UFO High Bay

Hyper Series - Sensor Ready

**WATT/CCT**
SELECTABLE

DESCRIPTION

Engineered with cutting-edge LED technology, the Sensor-Ready Tunable UFO High Bay offers exceptional efficiency, extended lifespan, and versatile functionality. Designed for wet locations with an IP67 rating. Featuring an integrated sensor receptacle, it supports plug-and-play compatibility with dimming motion sensors—maximizing energy savings and ensuring future-ready adaptability.

The fixture is built with a robust, one-piece aluminum heat sink and a center vent to promote passive airflow and superior thermal management.

Optional accessories include a frosted lens, standard or Bluetooth-enabled motion sensors, emergency backup battery, and a 3/4" pendant mount adapter.

Ideal for warehouses, retail spaces, gyms, garages, and other commercial or industrial applications.

FEATURES

- Wattage Selectable
- 4000K/5000K/5700K CCT Selectable
- Sensor Ready
- Die-Cast Aluminum Housing
- Marine-Grade Powder Coating
- Frosted Fire-Rated Polycarbonate Lens
- 304 Stainless Steel Hardware
- High-Efficiency Heat Sink
- 0-10V Dim to Off

MARKETS

- Warehouses
- Cold Storages
- Exhibit Halls
- Shopping Centers
- Indoor Arenas
- Gymnasiums

CERTIFICATIONS



LED Tunable UFO High Bay

Hyper Series - Sensor Ready

SPECIFICATIONS

PERFORMANCE

Efficacy (LPW): 170
CRI: 80
Operating temp: -22°F to 122°F (-30°C to 50°C)

LIFESPAN

Life (@L70): 85,000 hours
Warranty: 5 years

PHYSICAL

Finish: Marine-Grade Matte Powder Coating
Color: Black (White optional)
Housing: Die-Cast Aluminum

ELECTRICAL

Input Voltage: 120-277V (277-480V Optional)
Input Frequency: 50/60Hz
PF: ≥.95
THD: ≤ 20%
Surge Protection: 4KA
Dimming: 0-10V
Minimum Dimming: Dim to Off
Aux. Voltage: 12VDC
Driver Class: Class P
Whip/Cord: 4 ft
Sensor: Optional Photocell / Dimming Motion / Bluetooth

OPTICAL

Standard Lens: Frosted
Optional Lens: Clear
Lens Material: UV-Resistant Polycarbonate
Fireproof Rating: V0

MOUNTING

Hanging Ring (included)
3/4" Pendant Mount Adapter

INDUSTRY STANDARDS/RATINGS


IP Rating: IP67
IK Rating: IK08
Location: Wet
Outdoor Rated: Yes
UL/ETL: UL
DLC: 5.1
FCC: Yes
RoHS: Yes
CE: Yes

SKU	Wattage	Current Draw	Lumens
X-TUHB-150W	100/120/150W Tunable	Up to 1.25A@120V 0.55A@277V 0.32A@480V	25,000@150W
X-TUHB-240W	150/200/240W Tunable	Up to 2A@120V 0.87A@277V 0.5A@480V	40,000@240W
X-TUHB-320W	200/240/320W Tunable	Up to 2.7A@120V 1.2A@277V 0.67A@480V	54,000@320W

LED Tunable UFO High Bay

Hyper Series - Sensor Ready

DIMENSIONS / WEIGHT



Wattage	Diameter	Height	Weight
150W	11.5"	7"	5.9 lbs
240W	13.5"	7.1"	7.8 lbs
320W	15.5"	7.2"	9.6 lbs

ORDERING INFORMATION

X - TUHB - Wattage

X	TUHB	150W 240W 320W
---	------	----------------------

Example: X-TUHB-150W (150W TUHB Model with 4000/5000/5700K Selectable Color Temperature)

Note: 3000K is available by customize order.

LED Tunable UFO High Bay

Hyper Series - Sensor Ready

ACCESSORIES



U-S-PSDMS-T



U-S-BLMS-T

SENSORS & CONTROLS

U-S-PSDMS-T	3rd Gen Plug&Play Dimming Motion Sensor
U-S-BLMS-T	Bluetooth Plug&Play Dimming Motion Sensor

MOUNTING OPTIONS

U-MH-PM-HB	3/4" Pendant Mount for High Bays
-------------------	----------------------------------

HIGH VOLTAGE INPUT OPTIONS

U-RD-150W-480V	277-480V ($\leq 150W$) Driver Swap
U-RD-240W-480V	277-480V ($\leq 240W$) Driver Swap
U-RD-320W-480V	277-480V ($\leq 320W$) Driver Swap

LENS OPTIONS

U-TUHB-CPL	Clear Polycarbonate Lens for TUHB
-------------------	-----------------------------------



BACKUP BATTERY OPTIONS

U-EI-HB-25-C	25W Emergency Inverter (for All High Bays)
U-EI-HB-40-C	40W Emergency Inverter (for All High Bays)