

# LED Tunable Wall Pack

## Industrial Series - with Smart Photocell



### DESCRIPTION

This non-cutoff LED Wall Pack combines the familiar look of a traditional fixture with the performance and efficiency of advanced LED technology. It delivers bright, uniform illumination—making it an ideal HID replacement—while offering substantial energy savings and a long 85,000-hour rated lifespan to minimize maintenance.

Built with a rugged die-cast aluminum housing and an Impact&UV-resistant polycarbonate lens, this fixture is engineered for durability.

A pre-installed smart photocell allows for dusk-to-dawn functionality, as well as wattage and color temperature adjustments, even the hold time after sunset—all easily controlled via remote. Installation is simple, mounting directly to a standard junction box—making it an excellent choice for retrofit applications.

### FEATURES

- Wattage Selectable
- 3000K/4000K/5000K CCT Selectable
- Smart Photocell Sensor Preinstalled
- Die-Cast Aluminum Housing
- Marine-Grade Powder Coating
- Fire-Rated Polycarbonate Lens
- 304 Stainless Steel Hardwares
- Internal High-Efficiency Heat Sink
- 0-10V Dim to Off

### MARKETS

- Wet Environments
- Tunnel Roads
- Wall-side Pathways
- Security Lighting
- Alleyways
- Underground Parking

### CERTIFICATIONS



# LED Tunable Wall Pack

## Industrial Series - with Smart Photocell

### SPECIFICATIONS

#### PERFORMANCE

Efficacy (LPW): 130  
CRI: 80  
Operating Temp: -22 °F to 131 °F (-30 °C to 55 °C)

#### LIFESPAN

Life (@L70): 85,000 hours  
Warranty: 5 years

#### PHYSICAL

Finish: Marine-Grade Matte Powder Coating  
Color: Dark Bronze  
Housing: Die-Cast Aluminum

#### ELECTRICAL

Input Voltage: 120-277V (277-480V Optional)  
Input Frequency: 50/60Hz  
PF: ≥.95  
THD: ≤ 12%  
Surge Protection: 6KA  
Dimming: 0-10V  
Minimum Dimming: Dim to Off  
Aux. Voltage: 12VDC  
Driver Class: Class P  
Whip/Cord: Internal  
Sensor: Smart Photocell(Included)

#### OPTICAL

Standard Lens: Anti-Glare  
Lens Material: UV-Resistant Polycarbonate  
Fireproof Rating: V0

#### MOUNTING

Direct Wall Mount

#### INDUSTRY STANDARDS/RATINGS


IP Rating: IP65  
IK Rating: IK08  
Location: Wet  
Outdoor Rated: Yes  
UL/ETL: UL  
DLC: 5.1  
FCC: Yes  
RoHS: Yes  
CE: Yes

SKU	Wattage	Current Draw	Lumens
U-IWP-40	20/24/28/32/36/40W Tunable	Up to 0.34A@120V 0.15A@277V 0.13A@480V	5,320@40W
U-IWP-90	45/54/63/72/81/90W Tunable	Up to 0.75A@120V 0.33A@277V 0.19A@480V	11,880@90W

# LED Tunable Wall Pack

## Industrial Series - with Smart Photocell

### DIMENSIONS / WEIGHT



Wattage	Length	Width	Height	Weight
40W	14"	7.5"	9"	6.4 lbs
90W	14"	7.5"	9"	6.8 lbs

### ORDERING INFORMATION

#### U - IWP - Wattage

U	IWP	40 90
---	-----	----------

Example: U-IWP-90 (90W IWP Model with 3000/4000/5000K Selectable Color Temperature)

Note: Remote control sold separately. Complimentary with purchase of 5 or more wall packs.

# LED Tunable Wall Pack

## Industrial Series - with Smart Photocell


### ACCESSORIES



U-IWP-RC

#### SENSORS & CONTROLS

U-IWP-RC	Remote Control for Tunable Wall Pack
----------	--------------------------------------



#### GLARE SHIELDS

U-IWP-SHLD	Shield for IWP Series Wall Pack
------------	---------------------------------

#### HIGH VOLTAGE INPUT OPTIONS

U-BD-150W-480V	277-480V ( $\leq 150W$ ) Driver Swap
----------------	--------------------------------------



#### BACKUP BATTERY OPTIONS

U-EI-8-C	8W Emergency Inverter
U-EI-15-C	15W Emergency Inverter
U-EI-20-C	20W Emergency Inverter

#### FINISH COLORS

U-CP-BLK	Black Finish for HFL model
U-CP-WHT	White Finish for HFL model
U-CP-GRY	Grey Finish for HFL model