

The Laundry Jet Slide Port is our latest manual port design. It is aimed as a economic entry level port while still retaining the functionality and style of the Laundry Jet brand and matches perfectly with modern design. It provides the simplest, easy to use, manual open functionality. Constructed of durable plastic The Slide Port is simply mounted by screws, to the wall. It is opened by just sliding the port door open. It can be installed in 4 different orientations depending on your desired location giving maximum flexibility. For example you can install it to open to the left because of a door jam on the right and vice a versa including up and down if required for maximum design and installation flexibility. Once opened, the dirty laundry, bed sheets and even damp towels are simply fed into the now open port and drawn away to the laundry room. Once the user has fed the last item and the cycle has finished, they can gently slide the door closed ready for the next use.



Tech Data

|   |
|---|
| Manual Slide opening                                    |
| White plastic finish, mounted by screwing to wall.      |
| Cat 5 cable   |
| RJ 45 connectors  |
| 12 volt   |
| Airflow CFM 1000 ( 28m3)                                |
| Speed approx. 35-40 mph (56-65 kmh)                     |
| Soft slide action, available to slide right left and up |
| 22 DB at port (whisper quiet)                           |
| Auto Timer shut off                                     |
| Uses 6" ( 159 mm) PVC SDR sched 35 pipe                 |
| Compatible with the Laundry Jet Return Unit             |
| Max distance from laundry room 200ft (60m)              |
| Buy with mount Kit (wave port kit)                      |
| Weight 2.5 lb (.8 kg)                                   |
| 3-year warranty   |
| Must be installed by certified installer                |
| Installer online certification course at                |

<https://www.proprofs.com/quiz-school/story.php?title=mtgynjy5nq9mb9>