

Tool Setting Probe **Z**-Nano IR



Extremely precise infrared probe – flexible tool setting probe with linear working principle for monitoring of smallest tools • Tool breakage detection • Tool length measurement


- Axes compensation
- · Solution for machines with pallet changer

Your benefit:

- Extremely fast tool breakage detection
- No subsequent damage due to tool breakage
- Fast ROI
- No-wear, optoelectronic measuring mechanism
- Compact and robust design

Linear working principle

Due to the linear working principle the probe provides a minimal and torque-free measuring force. Even the most sensitive and smallest tool diameters can be measured extremely precise.







Fast tool breakage detection on horizontal machining centre with pallet changer



Z-Nano IR and TC54-10 in DUO-Mode



Many accessories available: chip protection, cleaning nozzle and mounting system, etc.



Exchangeable measuring surface

Technical data

Protection class	IP68
Approach direction	-Z
Meas. force vertical mounting *	2.2 N with chip protection: 2.4 N
Meas. force horizontal mounting *	$3.0~\mathrm{N}$ with chip protection: $3.2~\mathrm{N}$
Max. stroke	10 mm
Trigger point *	1 mm
Repeatability	0.5 μm 2σ
Max. probing speed	2 m/min
Min. tool diameter **	> 0.1 mm/with chip protection: 0.2 mm
Signal transmission Range	Infrared $\pm 60^{\circ}$ in Z, 360° in X/Y
Mass	290 g
Battery (2 pieces)	Saft Lithium LS14250 (½ AA, 3.6 V) 1200 mAh

- * Measuring force with chip protection & additional spring: see data sheet
- ** Depending on geometry and material of tool. Probing force must not result in damage of tool



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

Blum-Novotest Ltd.

Unit 15 Granary Wharf Business Park Wetmore Road, Burton upon Trent Staffordshire, DE14 1DU United Kingdom

Phone: +44 1283 569691 Fax: +44 1283 563687 info@blum-novotest.co.uk Blum-Novotest, Inc.

4144 Olympic Boulevard Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 solutions@blum-novotest.us