

Innovation  
for a Better Life

# CHANGE YOUR ENERGY CHARGE YOUR LIFE



LG Home Battery  
**RESU**



Compact Size  
& Space Saving

The compact and sleek design of the RESU allows you to place it anywhere you want, both indoors and outdoors.



Reliable  
Performance

The RESU provides reliability for your home with its industry leading longevity.



Proven Safety

The safety of LG Chem's lithium-ion battery is proven in the automotive and ESS markets.



 **LG Chem**  
www.lgesspartner.com

The ees Award is one of the most prestigious awards presented annually at ees Europe, the largest exhibition for batteries and energy storage systems in Europe, with the purpose to pay tribute to pioneering products and solutions for energy storage system.



## 48V



Models		RESU3.3	RESU6.5	RESU10	RESU13
Total Energy [kWh] <sup>1)</sup>		3.3	6.5	9.8	13.1
Usable Energy [kWh] <sup>2)</sup>		2.9	5.9	8.8	12.4
Capacity [Ah]		63	126	189	252
Nominal Voltage [V]		51.8			
Voltage Range [V]		42.0-58.8			
Max Power [kW]		3.0	4.2	5.0	5.0
Peak Power [kW] (for 3 sec.)		3.3	4.6	7.0	7.0 11.0 (Backup Mode)
Dimension [W x H x D, mm]		452 x 403 x 120	452 x 656 x 120	452 x 484 x 227	452 x 626 x 227
Weight [kg]		31	52	75	99
Enclosure Protection Rating		IP55			
Communication		CAN2.0B			
Certificates	Cell	UL1642			
	Product	UL1973 / TUV (IEC 62619) / CE / FCC / RCM			TUV(IEC 62619)/CE/FCC/RCM

1) Total Energy is measured at the initial stage of battery life under the condition as follows : Temperature 25°C

2) Usable Energy is based on battery cell only

• Compatible Inverter Brands : SMA, Ingeteam, GoodWe, Sungrow, Victron Energy, Selectronic - More brands to be added

### RESU PLUS



**RESU Plus is an expansion kit specially designed for 48V models of the RESU series. With RESU Plus, RESU3.3/6.5/10 are cross-connected with each other, and RESU13 is connected with the same model.**

- Dimension : 216 x 156 x 121 (W x H x D, mm)
- Number of Expandable Battery Units : Up to 2EA
- IP55

## 400V



Models	RESU7H		RESU10H	
	Type-R	Type-C	Type-R	Type-C
Total Energy [kWh] <sup>1)</sup>	7.0		9.8	
Usable Energy [kWh] <sup>2)</sup>	6.6		9.3	
Capacity [Ah]	63		63	
Voltage Range [V]	350-450	430-550	350-450	430-550
Max Power [kW]	3.5		5.0	
Peak Power [kW]	5.0 (for 5 sec.)	5.0 (for 10 sec.)	7.0 (for 10 sec.)	
Dimension [W x H x D, mm]	744 x 692 x 206	744 x 907 x 206	744 x 907 x 206	744 x 907 x 206
Weight [kg]	75	87	97	99.8
Enclosure Protection Rating	IP55			
Communication	RS485	CAN2.0B	RS485	CAN2.0B
Certificates	Cell	UL1642		
	Product	TUV (IEC 62619) / CE / FCC / RCM	TUV (IEC 62619) / CE / RCM	UL1973 / TUV (IEC 62619) / CE / FCC / RCM

1) Total Energy is measured at the initial stage of battery life under the condition as follows : Temperature 25°C

2) Usable Energy is based on battery cell only

• Noise Level : < 40dBA

• Compatible Inverter Brands : SMA, SolarEdge, Fronius, Huawei - More brands to be added