

Wineries and Breweries

JRZL-Series Positive Displacement Pumps



Applications:

- Must and Lees
- Whole berries
- Transfer
- Bottling

Sizes:

- 1" to 10"

Material:

- 316L

Features:

- Front loading seals
- Various rotor options
- 1"- 4" models stainless steel gear box standard
- 3A & EHEDG
- 100% CIPable

BC/BP- Series Centrifugal Pumps



Applications:

- Pump over
- Transfer
- Tank cleaning

Sizes:

- Inlet 1½" to 6"
- Outlet 1½" to 4"

Materials:

- 316L
- Buna, EPDM, Silicone and FKM elastomers

Features:

- Impeller retainer or threaded impeller nut options
- Stamped volute
- Wet ends, motor pump units and carts
- 3A & CIPable

B5101 and B5115-Series Butterfly Valves



Applications:

- Isolation
- Control

Sizes:

- ½" to 8"

Materials:

- B5101: 316L
- B5115: 304

Features:

- B5101
- Variable actuator and control packages
 - Multiple handle options
 - 3 Seat materials available

B5115

- Silicone seat material only
- Manual handle only, cannot be actuated

BV2C-Series Ball Valves



Applications:

- Isolation
- Control
- Diversion

Sizes:

- ½" to 4"

Material:

- CF8M

Features:

- Various actuator and control packages
- 5 encapsulated seat materials available
- ISO5211 mounting pad

Wineries and Breweries

TV-Series Tank Vent Valves



Application:

- Secondary tank protection during filling or draining of tanks

Features:

- PVC with stainless dome
- 2" and 3" clamp connections on same valve
- 304 stainless dome
- Stainless steel valve
- Stainless steel screen
- 2", 3" and 4"

Topping Gun, Gauges, Sample Valves, Sight Glasses and Spray Balls



Topping Gun



Pressure Gauges



Sight Glasses



Sample Valves



Sight Glasses



Spray Balls

Strainers



Applications:

- Filtering
- Removing hops from wort or beer

Sizes:

- 1" to 3"

Material:

- 316L

Features:

- Inline
- Side entry and side outlet
- Dual strainer assemblies using ball or butterfly valves

JRZW120 Wine Pump



Applications:

- Must and lees
- Transfer
- Bottling

Size:

- 2" clamp

Materials:

- 316L
- EPDM rubber heli-lobe

Features:

- Maximum flow: 66 GPM
- Maximum working pressure: 87 PSI
- Mounted on a cart with flat free wheels or casters
- Nord adjustable speed gearmotor

Dixon, founded in 1916, is a premier manufacturer and supplier of hose couplings, valves, dry-disconnects, swivels, and other fluid transfer and control products. The company's global reach includes a wide range of products for numerous industries including petroleum exploration, refining, transportation, chemical processing, food & beverage, steel, fire protection, construction, mining and manufacturing. Dixon's strategic objective is to create solutions that make products safer, leak-free, longer lasting, and always available.

dixonvalve.com • *Customer Service:* **800.789.1718**

Dixon Sanitary

N25 W23040 Paul Road, Pewaukee, WI 53072

Fax: 800.789.4046

sanitarysales@dixonvalve.com

For complete catalog and literature downloads go to dixonvalve.com



You Tube



Dixon
Customer Service

