

Resealing Decorative Concrete



Resealing every 3 to 5 years is essential to maintaining the life of your stamped concrete. The more sun that the area receives, the more frequently the process needs to occur.

Materials Needed

<p>Broom</p>		<p>Purchased at any general retail store</p>
<p>Paint Roller - 3/8 to 3/4 nap roller</p>		<p>Purchased at any home improvement store</p>
<p>Traz 25</p>		<p>Can be purchased at White Cap Supply 16405 S. Grove Rd Lansing, MI 48906</p>
<p>Xylene</p>		<p>Purchased at any home improvement store</p>

Steps

Note: Ensure that the area remains free of objects and foot or pet traffic during the entirety of the process.

Step 1	Sweep area from all dirt and debris
Step 2	Thoroughly wash the area with a pressure washer or a high-pressure hose nozzle
Step 3	Wait for the area to fully dry and use a broom or a leaf blower to clear any remaining debris
Step 4	If done within 3 to 5 years Mix 60% Traz 25 and 40% Xylene
	If done past 5 years Mix 70% Traz 25 and 30% Xylene
Step 5	Using the roller, apply a thin and even layer of the mixture on the concrete surface.
Step 6	Wait for 24 hours before moving furniture, or resuming use of the area

B&B Decorative Concrete would be happy to assist in resealing your concrete.