




300-C METAL CEILING
SYSTEM



BENEFITS

- Monolithic appearance
- Concealed suspension system
- 100% downward accessibility with panel removal tool
- Good acoustical performance in Perforation
- Available in Galvanized (GI), Aluminum (Alum.) and


APPLICATION AREAS

- Office
- Healthcare
- Education
- Transport
- Retail
- Foyers
- Corridors



COLOR SELECTION

Solid Color



White
9003



Black
9005



OPTIONAL COLOR

RAL Colors Available
on request*



Wood Finish*





*Available upon request


#Due to printing limitations, shades colors may vary from actual product.

For more color & perforation options or suspension information, please contact MCRA sales representative

PRODUCT SELECTION

300 C PANEL	PLAIN	PERFORATED	PERFORATED	PERFORATED
	 PLAIN	 2.5mm PERFORATED	 2.2mm PERFORATED	 1.8mm PERFORATED
<p>GALVANISED</p> <p>300 x 30 x 0.5mm ✓ ✓ ✓ ✓</p> <p>ALUMINIUM</p> <p>300 x 30 x 0.7mm ✓ ✓ ✓ ✓</p> <p>CUSTOMIZED LENGTH</p> <p>GI / ALU ✓ ✓ ✓ ✓</p>				

Customized CNC Designs as per requirement in GI, ALU. & SS:



Noise Reduction Coefficient (NRC)



Light Reflectance (LR)



Humidity Resistance (RH)



Demount ability

PERFORMANCE



Fire classification

Galvanized metal ceilings Class 0 / Class 1, BS 476, Part 6 & 7
 Aluminum metal ceilings Class 0 / Class 1, BS 476, Part 6 & 7

Light Reflectance



	Illumination	LRV Standard (%)	LRV Batch (%)	Delta (%) with correction factor
Powder coated Galvanized Steel	Daylight/Fluorescent - 10o Obs	80.3	72.6	7.7
	Daylight/Fluorescent - 2o Obs	83.3	72.7	7.6
	Tungsten - 10o Obs	80.2	72.6	4.6
	Tungsten - 2o Obs	83.2	72.7	7.5
Pre-coated aluminum	Daylight/Fluorescent - 10o Obs	80.3	75.6	1.7
	Daylight/Fluorescent - 2o Obs	83.3	75.7	4.6
	Tungsten - 10o Obs	80.2	75.6	1.6
	Tungsten - 2o Obs	83.2	75.7	4.5



ISO 9001:2015
 This icon demonstrates PR Ceiling Products ability to consistently provide products and services that meet customer and regulatory quality management system requirements.



ISO 45001:2018
 PR CEILING PRODUCTS provides an internationally-recognized framework for managing occupational health and safety risks. It enables organizations to systematically assess hazards and implement risk control measures, leading to reduced workplace injuries, illnesses and incidents.



ISO 14001:2015
 PR CEILING PRODUCTS is an internationally agreed standard that sets out the requirements for an environmental management system, DIN EN ISO 14001:2015, Requirements with guidance for use.

PHYSICAL DATA for 300-C Galvanized / Aluminum

Material
Hot dip Galvanized Steel/Aluminum

SURFACE FINISH
Powder coating/Pre-coating

THICKNESS
Galvanized Steel - 0.5mm
Aluminum - 0.7mm

Material Strength/Grade
Galvanized Steel of 120/180 gsm zinc coated
Aluminum Alloy: AA5050, AA3105 or AA1050

Coating
Powder Coated Microns: 60 microns to 80 microns
Pre-Coated Polyester Paint: Front Coating 20 microns to 25 microns, back Coating 5 microns to 8 microns.

RECOMMENDED SUSPENSION SYSTEM
Galvanized 300-C Carrier
Weight: 1RMT = 0.750 KG

WEIGHT
Size: Galvanized 300 x 30 x 0.50mm
Galvanized Steel \cong 5.5 Kg / 4.76 Kg
(Per SQM kg with GI Carrier/ Without Carrier)

Size: Aluminum 300 x 30 x 0.70mm
Aluminum \cong 2.90 Kg / 2.68 Kg
(Per SQM kg with GI Carrier / Without Carrier)

DATA for Accessories

GI 300-C Carrier: Thickness 0.70mm, Height 62mm, Width 20mm, Length 3000mm


GI 300-C Carrier Jointer:
Thickness 0.50mm

Wall Angle GI Material: 24x24mm, Thickness 0.40mm, Length 3000mm


Edge Profile GI Material: 24x24mm, Thickness 0.40mm, Length 3000mm

GI Rod 4mm / GI Threaded Rod 6mm

INSTALLATION AND ASSEMBLY DETAIL



1. 300 C Panel
2. 300C Carrier
3. Threaded rod 6mm
4. Bullet Fastener



CONTACT US:

P.R. CEILING PRODUCTS
(Head Office)

Plot no A-10/18, Near DPS School Main Gate, Meerut Road Industrial Area,
Ghaziabad -201003 e-mail: info@prceilingproduct.com, sales@prceilingproduct.com

Branches:

Delhi

Mumbai

Lucknow

Agra

+91 93508 52066 / +91 82720 81991

+91 70390 23676 / +91 99209 68086

+91 93413 92190

+91 99277 78086



www.prceilingproduct.com