



Replacement Cobalt Jobber Drill Bits



GOLD-P DRILLS

DLGP195 SERIES

HSS-E, STRAIGHT SHANK DRILLS, GOLD-P COATED

HSS-E SPIRALBOHRER, GOLD-P BESCHICHTET
Folets GOLD-P HSS-E queue cylindrique revêtus, série courte
PUNTE IN HSS-E, GAMBO CILINDRICO, GOLD-P

JOBBER
KURZ
COURTE
CORTA

► **Flute Geometry** : Right hand helix
 ► **Point Angle** : 135°, under 1.6mm : Normal point
 1.6mm & over : Split point
 ► **Surface treatment** : Bright body, TiN coating on working area
 ► **Application** : Drilling stainless steels, difficult to cut materials such as titanium alloys and inconel.

► **Nutenform** : Rechtsspirale
 ► **Spitzenwinkel** : 135°, unter 1.6mm : Normalanschiff
 1.6mm & über : Kreuzanschiff
 ► **Oberfläche** : Blank mit TiN-Beschichtung im Arbeitsbereich
 ► **Anwendung** : Tiefe Bohrungen in legierten und legierten Stählen, Grauguss, Temperguss, Aluminium- und Magnesiumlegierungen






under 1.6mm 1.6mm & over

DIN 338

HSS-E

33°

h8

135°

P.219



EDP No.	Drill Diameter		Flute Length		Overall Length	
	D1	L1	L1	L2	L2	L2
DLGP195010	1.0	12	12	34	34	34
DLGP195011	1.1	14	14	36	36	36
DLGP195012	1.2	16	16	38	38	38
DLGP195013	1.3	16	16	38	38	38
DLGP195014	1.4	18	18	40	40	40
DLGP195015	1.5	18	18	40	40	40
DLGP195016	1.6	20	20	43	43	43
DLGP195017	1.7	20	20	43	43	43
DLGP195018	1.8	22	22	46	46	46
DLGP195019	1.9	22	22	46	46	46
DLGP195020	2.0	24	24	49	49	49
DLGP195021	2.1	24	24	49	49	49
DLGP195022	2.2	27	27	53	53	53
DLGP195023	2.3	27	27	53	53	53
DLGP195024	2.4	30	30	57	57	57
DLGP195025	2.5	30	30	57	57	57
DLGP195026	2.6	30	30	57	57	57
DLGP195027	2.7	33	33	61	61	61
DLGP195028	2.8	33	33	61	61	61
DLGP195029	2.9	33	33	61	61	61
DLGP195030	3.0	33	33	61	61	61
DLGP195031	3.1	36	36	65	65	65
DLGP195032	3.2	36	36	65	65	65
DLGP195033	3.3	36	36	65	65	65
DLGP195034	3.4	39	39	70	70	70
DLGP195035	3.5	39	39	70	70	70
DLGP195036	3.6	39	39	70	70	70
DLGP195037	3.7	39	39	70	70	70
DLGP195038	3.8	43	43	75	75	75
DLGP195039	3.9	43	43	75	75	75
DLGP195040	4.0	43	43	75	75	75
DLGP195041	4.1	43	43	75	75	75
DLGP195042	4.2	43	43	75	75	75
DLGP195043	4.3	47	47	80	80	80
DLGP195044	4.4	47	47	80	80	80
DLGP195045	4.5	47	47	80	80	80
DLGP195046	4.6	47	47	80	80	80
DLGP195047	4.7	47	47	80	80	80
DLGP195048	4.8	52	52	86	86	86
DLGP195049	4.9	52	52	86	86	86
DLGP195050	5.0	52	52	86	86	86
DLGP195051	5.1	52	52	86	86	86
DLGP195052	5.2	52	52	86	86	86
DLGP195053	5.3	52	52	86	86	86
DLGP195054	5.4	57	57	93	93	93
DLGP195055	5.5	57	57	93	93	93
DLGP195056	5.6	57	57	93	93	93
DLGP195057	5.7	57	57	93	93	93
DLGP195058	5.8	57	57	93	93	93
DLGP195059	5.9	57	57	93	93	93
DLGP195060	6.0	57	57	93	93	93
DLGP195061	6.1	63	63	101	101	101

Unit : mm