

型号(Model): LSJ25L 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 19 毛重kg(Gross weight): 22

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 380X420X740 包装尺寸mm(Packaging size): 400X470X750

冷冻功率(Cold power): 240W 热时功率(Heat power): 800W



# 技术参数 Technical parameter

型号(Model): LSJ25LS

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 19 毛重kg(Gross weight): 22

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 380X420X740

包装尺寸mm(Packaging size): 400X470X750 冷冻功率(Cold power): 240W

热时功率(Heat power): 800W



# 技术参数 Technical parameter

型号(Model): LSJ25LX2S

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 27 毛重kg(Gross weight): 30

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

外形尺寸mm(Shape size): 380x650x740 包装尺寸mm(Packaging size): 400x700x750

冷冻功率(Cold power): 350W



LSJ25LX2\$

# JUICE DISPENSER | 9L



# JUICE DISPENSER |12L











LSJ9LX2



LSJ9LX3 LSJ9LX4



LSJ12LX1



LSJ12LX2







LSJ12LX4

Model no	Dimensions (mm)	Voltage (v)	Frequency (Hz)	Cold Power (w)	Cold Temperature Range (°C)	Hot Power (w)	Temperature Range (°C)	N.W (kg)	W.G (kg)
LSJ9LX1	390*210*670	220V-240V   110V-120V	50HZ/60HZ	180	7~12°C	360	52~-58°C	13	15
LSJ9LX2	390*330*670	220V-240V   110V-120V	50HZ/60HZ	280	7~12°C	800	52~-58℃	21	23
LSJ9LX3	390*410*670	220V-240V   110V-120V	50HZ/60HZ	280	7~12°C	800	52~-58°C	27	29
LSJ9LX4	390*530*670	220V-240V   110V-120V	50HZ/60HZ	380	7~12°C	1200	52~-58℃	30	33

Model no	Dimensions (mm)	Voltage (v)	Frequency (Hz)	Cold Power (w)	Cold Temperature Range (°C)	Hot Power (w)	Temperature Range (°C)	N.W (kg)	W.G (kg)
LSJ12LX1	410*350*660	220V-240V   110V-120V	50HZ/60HZ	180	7~12°C	440	52~-58℃	21	24
LSJ12LX2	410*410*660	220V-240V   110V-120V	50HZ/60HZ	280	7~12°C	900	52~-58°C	25	28
LSJ12LX3	600*410*660	220V-240V   110V-120V	50HZ/60HZ	320	7~12°C	1200	52~-58°C	33	36
LSJ12LX4	780*410*660	220V-240V   110V-120V	50HZ/60HZ	380	7~12°C	1500	52~-58°C	40	43

# JUICE DISPENSER | 18L





# JUICE DISPENSER | 25L







LSJ18LX1 LSJ18LX2



LSJ18LX3

Model no	Dimensions (mm)	Voltage (v)	Frequency (Hz)	Cold Power (w)	Cold Temperature Range (°C)	Hot Power (w)	Temperature Range (°C)	N.W (kg)	W.G (kg)
LSJ18LX1N	430*350*740	220V-240V   110V-120V	50HZ/60HZ	180	7~12°C	600	52~-58°C	24	25
LSJ18LX2N	480*460*740	220V-240V   110V-120V	50HZ/60HZ	280	7~12°C	600	52~-58℃	29	31
LSJ18LX3N	700*430*740	220V-240V   110V-120V	50HZ/60HZ	380	7~12°C	600	52~-58°C	37	39







LSJ25LX2S

Model no	Dimensions (mm)	Voltage (v)	Frequency (Hz)	Cold Power (w)	Cold Temperature Range (°C)	Hot Power (w)	Temperature Range (°C)	N.W (kg)	W.G (kg)
LSJ25L	380*420*740	220V-240V   110V-120V	50HZ/60HZ	240	7~12°C	800	52~-58℃	19	22
LSJ25LS	380*420*740	220V-240V   110V-120V	50HZ/60HZ	240	7~12°C	800	52~-58°C	19	22
LSJ25LX2S	380*650*740	220V-240V   110V-120V	50HZ/60HZ	350	7~12°C	1	1	27	30







型号(Model): LSJ20LX1 / LRSJ20LX1 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 23 / 25

毛重kg(Gross weight): 25 / 27

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 420×350×680 包装尺寸mm(Packaging size): 440×380×700

冷冻功率(Cold power): 280W 热时功率(Heat power): 600W

# 技术参数 Technical parameter

型号(Model): LSJ50L / LRSJ50L / LSP50L / LRSP50L

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 冷冻功率(Cold power): 380W 热时功率(Heat power): 600W

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C 加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 500×500×720 包装尺寸mm(Packaging size): 540×540×750

净重kg(Net Weight): 25 / 26 / 26 / 27 毛重kg(Gross weight): 28 / 29 / 29 / 30

# 技术参数 Technical parameter

型号(Model): LSJ20LX2 / LRSJ20LX2 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 29 / 31

毛重kg(Gross weight): 32 / 35 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 600×350×680 包装尺寸mm(Packaging size): 670×420×700

冷冻功率(Cold power): 350W 热时功率(Heat power): 1000W





#### Technical parameter

型号(Model): LSJ10Lx1 / LRSJ10Lx1 / LSP10Lx1 / LRSP10Lx1

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 13 / 14 / 13 / 14

毛重kg(Gross weight): 15 / 17 / 15 / 17 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 210×450×670 包装尺寸mm(Packaging size): 230×460×700

冷冻功率(Cold power): 180W 热时功率(Heat power): 360W



### 技术参数

# Technical parameter

型号(Model): LSJ10Lx3 / LRSJ10Lx3 / LSP10Lx3 / LRSP10Lx3

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 27 / 30 / 33

毛重kg(Gross weight): 30 / 32 / 35 / 35 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 410×450×670

包装尺寸mm(Packaging size): 490×460×700

冷冻功率(Cold power): 320W 热时功率(Heat power): 1000W

#### 技术参数

#### Technical parameter

型号(Model): LSJ10Lx2 / LRSJ10Lx2 / LSP10Lx2 / LRSP10Lx2

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 22 / 24 / 24 / 25

毛重kg(Gross weight): 24 / 26 / 28

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 330×450×670

包装尺寸mm(Packaging size): 370×460×700

冷冻功率(Cold power): 280W 热时功率(Heat power): 800W



#### 技术参数 Technical para

Technical parameter

型号(Model): LSJ10Lx4 / LRSJ10Lx4 / LSP10Lx4 / LRSP10Lx4

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 33 / 36 / 37 / 40 毛重kg(Gross weight): 36 / 38 / 40 / 42

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 540×450×670

包装尺寸mm(Packaging size): 580×460×700

冷冻功率(Cold power): 380W 热时功率(Heat power): 1200W





型号(Model): LSJ9LX1 / LRSJ9LX1 / LSP9LX1 / LRSP9LX1 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 13 / 14 / 13 / 14 毛重kg(Gross weight): 15 / 17 / 15 / 17

加热时平均温度(Hot-beverage temperture): 52℃~58℃

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

外形尺寸mm(Shape size): 390×210×670 包装尺寸mm(Packaging size): 450×230×700

冷冻功率(Cold power): 180W 热时功率(Heat power): 360W



### 技术参数 Technical parameter

型号(Model): LSJ9LX3 / LRSJ9LX3 / LSP9LX3 / LRSP9LX3

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 27 / 30 / 29 / 32 毛重kg(Gross weight): 29 / 32 / 31 / 34 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 410×390×670 包装尺寸mm(Packaging size): 490×450×700

冷冻功率(Cold power): 280W 热时功率(Heat power): 800W

### 技术参数 Technical parameter

型号(Model): LSJ9LX2 / LRSJ9LX2 / LSP9LX2 / LRSP9LX2 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 21 / 24 / 23 / 26 毛重kg(Gross weight): 23 / 27 / 25 / 28 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52°C~58°C 外形尺寸mm(Shape size): 330×390×670 包装尺寸mm(Packaging size): 360×450×700

冷冻功率(Cold power): 280W 热时功率(Heat power): 800W



### 技术参数 Technical parameter

型号(Model): **LSJ9LX4 / LRSJ9LX4 / LSP9LX4 / LRSP-9LX4** 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ

净重kg(Net Weight): 30 / 33 / 35 / 38 毛重kg(Gross weight): 33 / 36 / 38 / 41 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 530×390×670 包装尺寸mm(Packaging size): 580×450×700

冷冻功率(Cold power): 380W 热时功率(Heat power): 1200W





#### Technical parameter

型号(Model): LSJ12LX1 / LRSJ12LX1 / LSP12LX1 / LRSP12LX1 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 21 / 22 / 23 毛重kg(Gross weight): 24 / 25 / 25 / 26 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 410×350×660 色装尺寸mm(Packaging size): 480×360×750

冷冻功率(Cold power): 180W 热时功率(Heat power): 440W



# 技术参数

### Technical parameter

型号(Model): LSJ12LX3 / LRSJ12LX3 / LSP12LX3 / LRSP12LX3 电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 33 / 36 / 39 毛重kg(Gross weight): 36 / 38 / 39 / 41 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 600×410×660

包装尺寸mm(Packaging size): 640×450×700

冷冻功率(Cold power): 320W 热时功率(Heat power): 1200W

### 技术参数

### Technical parameter

型号(Model): LSJ12LX2 / LRSJ12LX2 / LSP12LX2 / LRSP12LX2

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 25 / 28 / 27 / 30

毛重kg(Gross weight): 28 / 31 / 30 / 33 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 410×410×660 包装尺寸mm(Packaging size): 470×450×700

冷冻功率(Cold power): 280W 热时功率(Heat power): 900W



#### 技术参数

### Technical parameter

型号(Model): LSJ12LX4 / LRSJ12LX4 / LSP12LX4 / LRSP12LX4

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 40 / 43 / 43 / 46 毛重kg(Gross weight): 43 / 41 / 42 / 44

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 780x410x660 色装尺寸mm(Packaging size): 820x450x700

冷冻功率(Cold power): 380W 热时功率(Heat power): 1500W





### Technical parameter

型号(Model): LSJ12LX1 / LRSJ12LX1 / LSP12LX1 / LRSP12LX1

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 21 / 22 / 23 毛重kg(Gross weight): 24 / 25 / 26 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 410×350×660 包装尺寸mm(Packaging size): 480×360×750

冷冻功率(Cold power): 180W 热时功率(Heat power): 440W

# 技术参数

### Technical parameter

型号(Model): LSJ12LX2 / LRSJ12LX2 / LSP12LX2 / LRSP12LX2

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 25 / 28 / 27 / 30 毛重kg(Gross weight): 28 / 31 / 30 / 33

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 410×410×660 包装尺寸mm(Packaging size): 470×450×700

冷冻功率(Cold power): 280W

热时功率(Heat power): 900W





#### 技术参数

#### Technical parameter

型号(Model): LSJ12LX3 / LRSJ12LX3 / LSP12LX3 / LRSP12LX3

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 33 / 36 / 39 毛重kg(Gross weight): 36 / 38 / 39 / 41 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 600×410×660 包装尺寸mm(Packaging size): 640×450×700

18L系列

冷冻功率(Cold power): 320W 热时功率(Heat power): 1200W



# 技术参数

### Technical parameter

型号(Model): LSJ18LX1 / LRSJ18LX1 / LSP18LX1 / LRSP18LX1

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 24 毛重kg(Gross weight): 25

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 430X350X740 包装尺寸mm(Packaging size): 480X360X750

冷冻功率(Cold power): 180W 热时功率(Heat power): 600W





型号(Model): LSJ18LX2 / LRSJ18LX2 / LSP18LX2 / LRSP18LX2

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 29 毛重kg(Gross weight): 31

冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 480X460X740 包装尺寸mm(Packaging size): 510X470X750 冷冻功率(Cold power): 280W

热时功率(Cold power): 280W 热时功率(Heat power): 600W

#### 技术参数

# Technical parameter

型号(Model): LSJ18LX3 / LRSJ18LX3 / LSP18LX3 / LRSP18LX3

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 37 / 41 / 39 / 44 毛重kg(Gross weight): 40 / 44 / 43 / 47 冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 700×430×740

包装尺寸mm(Packaging size): 750×470×750 冷冻功率(Cold power): 380W

冷冻功率(Cold power): 380W 热时功率(Heat power): 1500W





#### 技术参数 Technical parameter

型号(Model): LSJ18LX1N / LRSJ18LX1N / LSP18LX1N / LRSP18LX1N

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 24 毛重kg(Gross weight): 25

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 430X350X740 包装尺寸mm(Packaging size): 480X360X750

冷冻功率(Cold power): 180W 热时功率(Heat power): 600W

#### 技术参数

#### Technical parameter

型号(Model): LSJ18LX2N / LRSJ18LX2N / LSP18LX2N / LRSP18LX2N

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ 净重kg(Net Weight): 29

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 480X460X740 包装尺寸mm(Packaging size): 510X470X750

冷冻功率(Cold power): 280W 热时功率(Heat power): 600W

毛重kg(Gross weight): 31







Technical parameter

型号(Model): LSJ18LX3N, LRSJ18LX3N,LSP18LX3N,LRSP18LX3N

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 37 毛重kg(Gross weight): 39

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 700X430X740

包装尺寸mm(Packaging size): 750X470X750

冷冻功率(Cold power): 380W

热时功率(Heat power): 600W



### 技术参数

Technical parameter

型号(Model): LSJD18LX2 / LRSJD18LX2 / LSPD18LX2 / LRSP-18LX2

电压(Voltage): 220-240V/110-115V

频率(Frequency): 50/60HZ

净重kg(Net Weight): 29 / 31 / 31 / 34 / 34 / 37

毛重kg(Gross weight): 32 / 35 / 34 / 37 冷冻时平均温度(Cold-beverage temperture): 7°C~12°C

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 480×460×740 包装尺寸mm(Packaging size): 510×470×750

冷冻功率(Cold power): 280W

热时功率(Heat power): 1200W



# 技术参数

Technical parameter

型号(Model): LSJ18LX1 / LRSJ18LX1 / LSP18LX1 / LRSP18LX1

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ

净重kg(Net Weight): 24 / 25 / 25 / 26 毛重kg(Gross weight): 27 / 28 / 28 / 29

加热时平均温度(Hot-beverage temperture): 52℃~58℃

外形尺寸mm(Shape size): 430×350×740

包装尺寸mm(Packaging size): 480×360×750 冷冻功率(Cold power): 180W

热时功率(Heat power): 600W



#### 技术参数

Technical parameter

型号(Model): LSJD18LX3 / LRSJD18LX3 / LSPD18LX3 / LRSPD18LX3

电压(Voltage): 220-240V/110-115V 频率(Frequency): 50/60HZ

淨重kg(Net Weight): 37 / 41 / 39 / 44

毛重kg(Gross weight): 40 / 44 / 43 / 47

冷冻时平均温度(Cold-beverage temperture): 7℃~12℃

加热时平均温度(Hot-beverage temperture): 52℃~58℃ 外形尺寸mm(Shape size): 700×430×740

包装尺寸mm(Packaging size): 750×470×750

冷冻功率(Cold power): 380W 热时功率(Heat power): 1500W



Unique 10L and 20L series, which is with very large flow rate, small pieces particles such as fruit, pudding, chocolate, soya-bean milk availably.

Super strong, virtually unbreakable bowls and covers,removable Bowl, easy to clean.

Electro magnetic pump / silent stirring redactor

Unique evaporator, faster start up

Better design allow easier cleaning and less maintenance.