



AERIAL LIFTS



Purpose

The purpose of this program is to define the requirements for safely operating an aerial lift device.

Scope

This policy shall cover all aerial lift devices used on Veracity Field Services (the company) property or used by a Veracity Field Services employee or consultant.

Key Responsibilities

Supervisors

- Shall ensure that all aerial devices are properly operated by trained personnel.
- Shall ensure that aerial lift devices are designed and constructed in conformance with applicable requirements of the American National Standards for “Vehicle Mounted Elevating and Rotating Work Platforms” ANSI A92.2-1969, including appendix.

Employees

- Shall follow all aspects of this program.

Procedure

- Aerial lifts may be “field modified” for uses other than those intended by the manufacturer provided the modification has been certified in writing by the manufacturer or by an equivalent entity.
- Lift controls shall be tested each day prior to use to determine that such controls are in safe working conditions. Tests shall be made at the beginning of each shift during which the equipment is to be used to determine that the brakes and operating systems are in proper working condition.
- Only authorized persons shall operate an aerial lift and boom and basket load limits specified by the manufacturer shall not be exceeded.
- Aerial lifts shall have a working back-up alarm audible above the surrounding noise level or the vehicle is backed up only when an observer (spotter) signals that it is safe to do so.
- The minimum clearance between electrical lines and any part of the equipment (i.e. crane or load) shall be 10 feet for lines rated 50 kV or below.
- Employees shall always stand firmly on the floor of the basket, and shall not sit or climb on the edge of the basket or use planks, ladders, or other devices for a work position.
- An approved fall restraint system shall be worn when working from an aerial lift. The fall restraint system must be attached to the boom or basket. An approved fall restraint system shall be attached to the boom or basket when working from an aerial lift and it is not permitted to be attached to adjacent poles or structures.
- All employees or consultants who operate an aerial lift device shall be trained in the safe operation of the



specific device they will operate. Training must conform to all OSHA requirements.