



Fan coil units Catalogue

All Seasons
°CLIMATE COMFORT

- Heating
- Air Conditioning
- Applied Systems
- Refrigeration





Daikin Europe N.V.

About Daikin

Daikin has a worldwide reputation based on over 85 years' experience in the successful manufacture of high quality air conditioning equipment for industrial, commercial and residential use. Daikin's much envied quality quite simply stems from the close attention paid to design, production and testing, as well as aftersales support. To this end, every component is carefully selected and rigorously tested to verify its contribution to product quality and reliability.

Fan Coil Units

Fan Coil Units are a highly efficient means of turning a water chiller, heat pump or hot water boiler into an efficient, quiet air conditioning system. These units are an effective solution to provide a comfortable environment for both commercial and residential applications.

Daikin offers a wide range of Fan Coil Units for both concealed and exposed applications. Three models are available in flexible application. The only moving part in the units is the fan, making them ideal for use in offices, hotels and at home. The goal is to obtain the right solution, both technically and aesthetically.

Flexible solutions

Fan Coil Units in combination with chillers and or boilers can be used to provide a broad range of solutions that can be tailored to local conditions such as climate, primary fuel market or building insulation. In warmer climates or when a building is well insulated, Fan Coil Units with a chiller (2-pipe system) can handle both cooling and heating. Here the chiller is capable of operating in cooling as well as heat pump mode. In more severe climates, a boiler can be added (4-pipe system) allowing optimal cooling in the summer using the chiller, and efficient heating in the winter via the boiler. Adding to the flexibility when designing applied systems applications, is the ability to equip the Fan Coil Unit with an optional electric heater. In situations where it is not economical to operate a boiler and where a chiller in heat pump mode is also not desirable, the electric heater can quickly heat up a room. The combinations made possible by the Daikin range of Fan Coil Units allow a chiller-based solution to be optimally designed for just about any application and price range.



Table of Contents

About Daikin	02
Fan Coil Units - Product Portfolio	04
Fan Coil Units - Accessories	05
Fan Coil Units - Control Systems	06
Cassette units	
FWC-BT/BF	08
FWF-BT/BF	09
FWC-AT/AF	10
FWF-CT	11
Concealed ceiling units	
FWB-BT	12
FWB-JT/JF	13
Wall mounted unit	
FWT-BT	14
Flexi type units	
FWL-DT/DF	16
FWM-DT/DF	17
FWD-AT/AF	18
Floor standing unit	
FWV-DT/DF	19

FAN COIL UNITS - PRODUCT PORTFOLIO

FAN COIL UNITS - ACCESSORIES

Type: FWM-DT/DF, FWL-DT/DF, FWW-DT/DF	1	2	3	4	6	8	10	FWW	FWL	FWM
Description										
Additional single row heat exchanger	ESRH02A6	ESRH03A6		ESRH06A6		ESRH10A6		x	x	x
Electric heater	EEH01A6	EEH02A6	EEH03A6		EEH06A6		EEH10A6	x	x	x
2-pipe 3-way valve		E2MV03A6		E2MV06A6		E2MV10A6	x	x	x	
4-pipe 3-way valve		E4MV03A6		E4MV06A6		E4MV10A6	x	x	x	
Fan stop thermostat			YFSTA6				x	x	x	
Air intake & discharge grille	EAIDF02A6	EAIDF03A6	EAIDF06A6		EAIDF10A6		-	-	x	
Supporting feet		ESFV06A6			ESFV10A6	x	-	x		
Supporting feet + grille	ESFG2A6	ESFG3A6	ESFG6A6		ESFG10A6	x	-	-		
Fresh air intake	EFA2A6	EFA3A6	EFA6A6		EFA10A6	x	-	-		
Rear panel	ERP2V2A6	ERP3V6A6	ERP6V6A6		ERP10V10A6	x	x	-		
Control electromechanical		ECFWMB6				x	x	x		
Electronic controller		FWEC1A, FWEC2A, FWEC3A				x	x	x		
Master slave option		EPIMSB6				x	x	x		
Vertical drainpan		EDPVA6				x	x	x		
Horizontal drainpan		EDPH46				-	x	x		
On board installation kit		FWECKA				x	x	-		
Temperature sensor kit		FWTSKA				x	x	x		
Relative humidity sensor kit		FWHSKA				x	x	x		
On board FCU controller installation kit		FWECKA				x	x	-		

Type: FWB-BT	2-4	5-7	8-10
Description			
Additional heat exchanger	EAH04A6	EAH07A6	EAH10A6
3-way valve add. h/e		E2MV307A6	E2MV310A6
3-way valve cooling h/e		Factory mounted	
2-way valve add. h/e	E2MV207A6		E2MV210A6
2-way valve cooling h/e		Factory mounted	
Electric Heater		Factory mounted	
Fan stop thermostat		YFSTA6	
Power interface	-	-	EPIB6
Master slave interface		EPIMSB6	
Electronic controller		FWEC1A	
		FWEC2A	
		FWEC3A	
Temperature sensor kit		FWTSKA	
Relative humidity sensor kit		FWHSKA	
On board installation kit		FWECKA	

Type: FWB-JT/JF	02 - 11
Description	
2-pipe 3-way valve	MCWCN
4-pipe 3-way valve	MCWHN

Type: FWD-AT/AF	4	6	8	10	12	16	18
Description							
Electric heater: small	(1)	EDEH04A6	EDEHS06A6	EDEHS10A6	EDEHS12A6	EDEHS18A6	
Electric heater: big		EDEH04A6	EDEHB06A6	EDEHB10A6	EDEHB12A6	EDEHB18A6	
2-pipe 3-way valve	(2)	ED2MV04A6		ED2MV10A6	ED2MV12A6	ED2MV18A6	
4-pipe 3-way valve		ED4MV04A6		ED4MV10A6	2xED2MV12A6	2xED2MV18A6	
Vertical Drainpan			EDDPV10A6		EDDPV18A6		
Horizontal Drainpan			EDDPH10A6		EDDPH18A6		
Fan stop thermostat			YFSTA6				
Fresh air intake		EDMFA04A6	EDMFA06A6	EDMFA10A6	EDMFA12A6	EDMFA18A6	
Electronic controller	(3)			FWEC1A			
				FWEC2A			
				FWEC3A			
Power interface				EPIB6			
Master slave interface				EPIMSA6			
Temperature sensor kit				FWTSKA			
Relative humidity sensor kit				FWHSKA			

- Requires electronic controller
- For FWD 12,16,18AT/AF only motor valve (piping not included)
- Water probe included
- Optional, electrical installation box with earth terminal KJB21A is required, if controller wires need to be installed in the wall.
- Requires electrical installation box with earth terminal KJB311A.
- Requires electrical installation box KJB411A.
- Requires installation box KRP1H98. (FWC)
- Requires installation box KRP1BA101 (FWF)
- Requires electrical installation box with earth terminal KJB21A, if built in the wall.
- Requires valve control PCB EKRP1C11
- I-touch:
 - Not allowed to use the i-touch for an installation with both fan coils and VRV units.
 - Can not be used in combination with fan coil units, that use MOD bus communication.
 - No Ainet or telephone connection possible.»
- Only 1 of these 4 options can be installed on 1 indoor unit.
- Max. 1 KRP1H98 box can be mounted on the unit. Max. 2 PCB's can be mounted in 1 KRP1H98 box. (FWC)
- Max. 2 KRP1BA101 boxes can be mounted on the unit. Max. 1 PCB can be mounted in 1 KRP1BA101 box. (FWF)

TYPE	FWC-BT/BF	FWF-BT/BF
Description		
Decoration Panel (RAL 9010 - grey sealings) 4-way blow	-	BYFQ60B
Decoration Panel - Standard (RAL 9010 - grey sealings) Round flow		
Decoration Panel - White (RAL 9010 - white sealings) Round flow	BYCQ140CW1	
Sealing member of air discharge outlet	BYCQ140CW1W	
Panel spacer	-	KDBHQ55C140
Long-life filter	KAFP551K160	KAFQ44BA60
Fresh air intake kit - Direct installation type	-	KDDQ44XA60
Fresh air intake kit (20% fresh air) - Direct installation type	KDDQ55C140-1 (*20) / KDDQ55C140-2 (*20)	-
Remote controller - Wireless - H/P	BRC7F532F (*18)	BRC7E530 (*18)
Remote controller - Wireless - C/O	BRC7F533F (*18)	BRC7E531 (*18)
Remote controller - Wired		BRC315D7 (*4)
Central remote controller		DCS302CA51 (*5)
Electrical box with earth terminal (3 blocks)		KJB311A
Unified on/off controller		DCS301BA51 (*9)
Electrical box with earth terminal (2 blocks)		KJB212A
Schedule timer	DST301BA51 (*6)(*9)	DST301BA51 (*6)(*9)
Wiring adapter for electrical appendices (1)	KRP2A52 (*7) (*12)	KRP2A52 (*9) (*12)
Wiring adapter for electrical appendices (2)	KRP4AA53 (*7) (*12)	KRP4AA53 (*9) (*12)
Installation box for adapter PCB	KRP1H98 (*13)	KRP1BA101 (*17)
Remote sensor	KRCS01-4	KRCS01-1
Intelligent touch controller	DCS601C51C(*6) (*11)	DCS601C51C (*6) (*11)
Electrical installation box		KJB411A
Optional PCB for MOD-bus connection	EKFCMBCB7 (*8) (*12)	EKFCMBCB7 (*8) (*12)
2-way valve - On/Off	EKMV2C09B7 (*8) (*10) (*15)	EKMV2C09B7 (*8) (*10) (*16)
3-way valve - On/Off	EKMV3C09B7 (*8) (*10) (*15)	EKMV3C09B7 (*8) (*10) (*16)
Valve control PCB		EKRP1C11
Remote "On/Off" and "forced off" kit		EKROROA (*17)

Description	material	FWT-BT	FWF-CT	FWC-AT	FWC-AF
Standard wired remote controller with LCD	MERCA	x	x	x	x
Simplified wired remote controller (cooling only)	SRC-COA	x	x	x	-
Simplified wired remote controller (heat pump)	SRC-HPA	x	x	x	x
Wireless controller for cooling only	WRC-COB	x	x	x	-
Wireless controller for heat pump	WRC-HPB	x	x	x	x
Decoration panel (600x600) including wireless controller H/P 2pipes	DCP600TB	-	x	-	-
Decoration panel (900x900 / 2-pipe) including wireless controller H/P 2pipes	DCP900TB	-	-	x	-
Decoration panel (900x900 / 4-pipe) including wireless controller H/P 4pipes	DCP900FB	-	-	-	x

- 2-pipe unit: 1 x valve kit + 1 x installation box for PCB KRP1H98 + 1 x valve control PCB EKRP1C11
- 4-pipe unit: 2 x valve kit + 1 x installation box for PCB KRP1H98 + 1 x valve control PCB EKRP1C11 (FWC)
- 2-pipe unit: 1 x valve kit + 1 x installation box for PCB KRP1BA101 + 1 x valve control PCB EKRP1C11
- 4-pipe unit: 2 x valve kit + 1 x installation box for PCB KRP1BA101 + 1 x valve control PCB EKRP1C11 (FWF)»
- This option is needed to create T1 T2 wire.
- It is possible to change the operation mode, but this will not have an impact on the water temperature. (No feed back to water source) It is not possible to select the "auto airflow" setting.
- Dry operation can be selected with this remote control, but this function is not available on the FWC model.
- All options are supplied as kit.
- Both parts of the fresh air intake are needed for each unit.

FAN COIL UNITS - CONTROL SYSTEMS

The fan coil units
can be operated by
different controllers
according
to the model.



ECFWMB6

ELECTROMECHANICAL BUILT-IN CONTROLLER

- > Fan speed selector
- > Manual cooling/heating changeover.
- > ON/OFF valves can also be controlled with ECFWMB6



BR315D7

WIRED REMOTE CONTROLLER

- > to control each fan coil unit independently
- > cooling and heating function
- > ON/OFF timer function



BR7E532F

INFRARED REMOTE CONTROLLER

- > to control each fan coil unit independently
- > cooling and heating function



FWEC1A

ELECTRONIC CONTROLLER

- > Control of on-off valves for two or four pipes systems
- > Control of auxiliary heating element
- > Cooling/heating switching in the following modes: local or remote manual (centralised), automatic (depending on water temperature (optional) or air temperature)
- > Possibility, by means of clean contacts, of remote centralised cooling/heating switching and external activation
- > Temperature sensor kit (accessory FWTSKA)
- > Economy function (setpoint correction by 2.5°C and forcing of the fan to run at minimum available speed)
- > Composed by:
 - Ic display
 - keyboard
- > On board and wall mounted installation.
- > Same as FWEC1A with following additional functions:
 - 1) humidity management:
 - display of relative humidity
 - dehumidification function
 - (cooling mode) Manual activation
 - 2) serial communication interface (RS485 bus)
 - possibility to set up a master-slave system up to 247 slave units, in which one of the controls plays the role of master and manages all the other slave units. (modbus protocol)



FWEC2A

- > Composed by:

Ic display
keyboard

- > On board and wall mounted installation.

- > Same as FWEC1A with following additional functions:

- 1) Back light
- 2) Proportional valve control (two voltage outputs for the proportional valves)
- 3) Voltage contact 0-10V (same as 2)
- 4) Time clock and weekly schedule (on / off or setpoint air)
- 5) Integration in BMS (already included in the FWEC2A version)
- 6) Two digital outputs (voltage free) to manage electric heaters with the weekly schedule



MERCA

STANDARD WIRED REMOTE CONTROLLER

- › Fan speed
- › Sleep function
- › Swing
- › Temperature setting
- › Operating mode
- › LCD display
- › ON/OFF switch
- › Real time clock
- › Timer active
- › Timer ON/OFF



SRC-COA



SRC-HPA

SIMPLIFIED WIRED REMOTE CONTROLLER FOR COOLING ONLY & HEAT PUMP

- › Temperature display
- › Temperature setting
- › Timer switch setting
- › ON/OFF switch
- › Fan speed
- › Operating mode
- › Swing
- › "Sleep" function



WRC - COB/HPB

WIRELESS CONTROLLER FOR COOLING ONLY & HEATPUMP

- › LCD display
- › Temperature setting
- › Operating mode
- › Timer switch setting
- › Turbo mode
- › Swing
- › "Sleep" function
- › Real time clock
- › ON/OF switch
- › Fan speed

FWC-BT/BF

Round flow cassette



FWC-BT/BF



BRC315D7



BRCE532F



- > 360° air discharge ensures uniform air flow and temperature distribution
- > Modern style decoration panel in white (RAL9010)
- > Fresh air intake for healthy living
- > Comfortable horizontal air discharge ensures draughtfree operation and prevents ceiling soiling
- > Possibility to shut 1 or 2 flaps for easy installation in corners
- > Standard drain pump with 850mm lift



INDOOR UNITS				2-PIPE				4-PIPE			
				FWC06BT	FWC07BT	FWC08BT	FWC09BT	FWC06BF	FWC07BF	FWC08BF	FWC09BF
Cooling capacity	Total capacity	High	kW	5.0	5.6	6.3	7.2	4.9	5.6	6.3	7.2
	Sensible capacity	High	kW	3.4	4.0	4.5	5.3	3.4	3.9	4.4	5.2
Heating capacity	2-Pipe	High	kW	6.3	7.1	8.3	9.5	-			
	4-Pipe	High	kW	-				6.2	6.8	7.8	8.8
Power input	High	W		40	46	58	76	41	47	59	77
Dimensions	Unit	HxDxD	mm	288x840x840				288x840x840			
Weight	Unit	kg		26				29			
Water pressure drop	Cooling	kPa		15	19	26	34	15	19	25	32
	Heating	kPa		15	19	26	34	24	30	38	47
Fan	Type	Turbo fan				Turbo fan					
	Air flow rate	High	m³/h	1,062	1,236	1,518	1,776	1,032	1,200	1,476	1,746
Sound power level	High	dBA		36	39	44	49	36	39	44	49
Sound pressure level	High	dBA		24	28	32	37	24	28	32	37
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240				1~/50/220-240			



FWF-BT/BF



BRC315D7



BRC7E532F

- > Modern stylish decoration panel in white (RAL9010)
- > Fresh air intake kit available
- > Comfortable horizontal air discharge ensures draughtfree operation and prevents ceiling soiling
- > Possibility to close 1 or 2 flaps for different air flow patterns
- > Drainpump standard mounted (lift: 750mm)



INDOOR UNITS				2-PIPE				4-PIPE			
				FWF02BT	FWF03BT	FWF04BT	FWF05BT	FWF02BF	FWF03BF	FWF04BF	FWF05BF
Cooling capacity	Total capacity	High	kW	1.7	2.8	3.3	4.0	1.7	2.3	2.8	3.5
Sensible capacity				1.3	1.7	2.1	2.7	1.3	1.3	1.7	2.3
Heating capacity	2-Pipe	High	kW	2.6	3.4	4.1	5.3				
	4-Pipe	High	kW		-			3.1	3.3	3.9	4.8
Power input	High		kW		67	70	89	67	62	74	93
Dimensions	Unit	HxWxD		mm	285x575x575			285x575x575			
Weight	Unit	kg		19	19	19	19	19	20	20	20
Water pressure drop	Cooling	kPa		6	19	31	42	6	13	21	33
	Heating			6	19	31	42	12	6	9	13
Fan	Type	Turbo fan				Turbo fan					
	Air flow rate	High	m³/h	468	468	660	876	468	438	618	822
Sound power level	High		dBA	40	40	44	49	40	42	46	51
Sound pressure level	High		dBA	27	27	33	39	27	29	35	41
Power supply	Phase / Frequency / Voltage	Hz / V		1~ / 50 / 220-240				1~ / 50 / 220-240			

* Height includes switch box



FWC08AAT



WRC-COB/HPB



SRC-COA/HPA



- > Wide operating range
- > Quiet operation with auto-swing comfort
- > Easy to install and maintain
- > Flexibility (2-pipe or 4-pipe)
- > 3 speed fan motor
- > Double-intake centrifugal fans
- > 4 way air discharge and air swing
- > Air suction from underneath
- > High power air flow
- > Slim front panel and aesthetic design
- > Removable washable air filter (self-extinguishing class 1)
- > Built-in high pressure drain pump (up to 700mm condensate water can be pumped)
- > Infrared remote controller as standard with decoration panel kit

INDOOR UNITS			2-PIPE					4-PIPE					
			FWC07AT	FWC08AT	FWC10AT	FWC11AT	FWC12AT	FWC02AF	FWC03AF	FWC04AF	FWC05AF	FWC06AF	
Power input	High	W	127	151	164	192	253	122	138	153	184	232	
Capacity	Cooling	Total	High kW	6.63	7.50	8.80	9.95	10.80	3.81	3.96	4.63	5.01	
	Cooling	Sensible	High kW	4.90	5.40	6.40	7.10	7.70	3.40	3.52	4.07	4.40	
	Heating	(2-pipe)	High kW	8.40	9.50	11.00	12.00	12.90	-	-	-	4.54	
	Heating	(4-pipe)	High kW	-	-	-	-	10.55	10.99	12.51	13.48	13.77	
Dimensions	Height x Width x Depth		mm	335x820x821									
Machine weight			kg	31	32	35	38	40	31	32	35	38	40
Sound level	Sound power	High	dBA	52	55	60	61	64	52	55	60	61	64
Water flow	Cooling		l/h	1,140	1,290	1,514	1,711	1,858	655	681	796	862	888
	Heating		l/h	1,140	1,290	1,514	1,711	1,858	-	-	-	-	-
Water pressure drop	Cooling		kPa	24.8	30.8	41.6	52.2	69.3	3.56	3.78	4.94	5.7	5.96
	Heating		kPa	21.4	26.8	35.3	45.2	64.1	-	-	-	-	-
Fan	Air flow rate	High	m³/h	1,310	1,380	1,560	1,740	1,840	1,310	1,380	1,560	1,740	1,840
Standard heat exchanger	Water volume		l	2.69									
Water connections	Std. heat exchanger		inch	3/4"									
Current power input	High	A		0.52	0.64	0.68	0.79	1.06	0.53	0.61	0.67	0.8	1.02
Required power supply	1~220-240V/50Hz												



FWF-CT




MERCA



SRC-COA/HPA



WRC-COB/HPB



- > Quiet operation with auto-swing comfort
- > Easy to install and maintain
- > 4 way air discharge and air swing
- > Slim front panel and aesthetic design
- > Removable washable air filter (self-extinguishing class 1)
- > Built-in high pressure drain pump (up to 700mm condensate water can be pumped)
- > Wireless controller as standard with decoration panel kit

INDOOR UNITS				FWF02CT	2-PIPE	FWF03CT	FWF04CT
Power input	High		W	63		64	79
Capacity	Cooling	Total	High kW	2.49		4.10	4.54
	Cooling	Sensible	High kW	1.91		2.93	3.37
	Heating	(2-pipe)	High kW	3.52		4.69	5.28
Dimensions	Height x Width x Depth			mm			
Machine weight				kg	22	23	
Sound level	Sound power			dBA	52	54	56
Water pressure drop	Cooling			kPa	19.00	27.00	29.00
	Heating			kPa	17.00	24.00	27.00
Fan	Air flow rate	High	m³/h	646		680	748
Water connections	Std. heat exchanger			inch	3/4		
Current input	High		A	0.27		0.28	0.34
Required power supply				1~/220-240V/50Hz			



FWB04BT



FWEC1, 2, 3A

- › Low sound power levels and electrical absorption thanks to plastic impeller, ABS winding staircase and improved electric motor
- › Compact dimensions, can easily be mounted in a narrow ceiling void
- › 3, 4 or 6 stage row cooling coil
- › Drain pan to collect the condensate from: heat exchanger and regulating valves
- › 7-speed electrical motors (with thermal protection on windings)
- › All 7 speeds pre-wired in the factory in the terminal block of the switch box
- › The air filter can easily be removed for cleaning



INDOOR UNITS				2-PIPE								
		FWB02BT	FWB03BT	FWB04BT	FWB05BT	FWB06BT	FWB07BT	FWB08BT	FWB09BT	FWB10BT		
Cooling capacity	Total capacity	High kW	2.61	3.14	3.49	5.08	5.45	6.47	7.57	8.67	10.34	
	Sensible capacity	High kW	1.88	2.16	2.34	3.6	3.87	4.4	5.23	5.96	6.9	
Heating capacity	2-Pipe	High kW	5.47	6.01	6.47	10.31	11.39	12.28	15.05	16.85	18.78	
	4-Pipe	High kW		3.14			5.99			12.8		
Power input	High			79			154			294		
Dimensions	Unit	HxDxW mm	239x1,039x609			239x1,389x609			239x1,739x609			
Weight	Unit	kg	23	24	26	31	33	35	43	45	48	
	Operation weight	kg	24	26	28	33	35	38	45	48	52	
Heat exchanger	Water volume	l	1.1	1.5	2.2	1.6	2.1	3.2	2.1	2.8	4.2	
Additional heat exchanger	Water volume	l		0.4			0.6			1.7		
Water flow	Cooling	l/h	448	539	598	873	936	1,111	1,299	1,488	1,774	
	Heating	l/h	480	527	567	904	999	1,077	1,319	1,479	1,647	
	Additional heat exchanger	l/h		275			526			1,123		
Water pressure drop	Cooling	kPa	8	14	11	15	8	14	21	26		
	Heating	kPa	7	10	8	12	7	10	16	15	18	
	Additional heat exchanger	kPa			3			5		8		
Fan	Type		Centrifugal - forward blades - directly coupled on fan motor									
	Air flow rate	High m³/h		400			800			1,200		
	Available pressure	High Pa		71			65			59		
Sound power level	High	dBA		56			59			69		
Sound pressure level	High	dBA		44.5			47.5			57.5		
Piping connections	Drain OD	mm					16					
Water connections	Std. heat exchanger	inch					3/4			1		
	Add. heat exchanger	inch										
Power supply	Phase / Frequency / Voltage	Hz / V					1~ / 50 / 230					
Current input	High	A		0.36			0.73			1.28		



FWB02JT/JF



FWEC1, 2, 3A



- > Wide operating range
- > Quiet operation via enlarged fan wheels
- > Easy maintenance: filter can be removed from both sides and beneath (maximum filter size is 400mm)
- > Flexibility (2-pipe or 4-pipe)
- > 4-speed fan motor
- > Direct driven centrifugal fans
- > Flexibility via interchangeable water connection side
- > High power air flow
- > Available static pressure of 30 Pa
- > Extended drain pan as standard
- > Standard Filter
- > Standard Plenum
- > Insulated with self-extinguishing class 1 heat insulation
- > Electronic room thermostat

INDOOR UNITS				2-PIPE											4-PIPE								
				2-PIPE					4-PIPE						4-PIPE								
Indoor units		02	03	04	05	06	07	08	09	10	11	02	03	04	06	07	08	10					
Cooling capacity	Total capacity	High	kW	1.64	2.67	2.99	3.34	4.81	5.31	6.16	7.26	8.49	8.99	1.67	2.67	3.03	4.88	5.33	6.53	8.21			
	Sensible capacity	High	kW	0.94	1.88	1.95	2.07	3.40	4.15	4.39	5.06	6.37	6.41	0.97	1.83	1.93	3.41	4.01	4.91	6.28			
Heating capacity	2-Pipe	High	kW	2.16	3.62	3.97	4.11	6.30	7.47	8.09	9.64	11.57	11.71	2.12	3.69	3.87	6.40	7.52	9.01	11.09			
	4-Pipe	High	kW											2.49	3.92	4.43	6.70	8.16	9.56	11.68			
Power input	High		W	34	53	57	54	86	121	117	134	164	166	34	51	54	84	117	137	163			
Dimensions	Unit	HxWxD		mm	251x814 x590	251x984 x590	251x1,114x590	251x1,314 x590	251x1,564x590	251x1,664 x590	251x1,924x590	251x1,814 x590	251x984 x590	251x1,114 x590	251x1,314 x590	251x1,564 x590	251x1,664 x590	251x1,924 x590					
Weight	Unit	kg		kg	20.0	23.0	28.0	31.0	33.0	44.0	48.0	52.0	50.0	56.0	22.0	27.0	31.0	36.0	48.0	52.0	56.0		
	Operation weight	kg		kg	20.7	24.0	29.1	32.5	34.4	45.8	50.4	54.6	52.4	59.1	22.9	28.3	32.5	37.9	50.4	54.6	59.1		
Heat exchanger	Water volume	l		l	0.69	0.95	1.14	1.52	1.44	1.82	2.42	2.62	2.36	3.14	0.92	1.26	1.52	1.92	2.42	2.62	3.14		
Water flow	Cooling	l/h		386	549	739	803	1,022	1,109	1,383	1,523	1,764	1,910	386	530	724	986	1,138	1,296	1,660			
	Heating	l/h		386	549	738	802	1,020	1,107	1,336	1,524	1,764	1,911	387	530	725	985	1,139	1,299	1,660			
Water pressure drop	Additional heat exchanger	l/h						-					269	391	493	663	820	924	1,142				
	Cooling	kPa		10.91	8.34	15.64	11.22	31.31	12.56	7.62	9.83	21.71	16.81	10.95	8.24	15.67	29.95	9.24	12.49	19.38			
	Heating	kPa		8.86	6.76	12.84	9.21	25.87	11.13	6.57	8.60	18.56	14.46	8.94	6.64	12.84	24.16	7.89	9.67	16.50			
Fan	Additional heat exchanger	kPa						-					10.66	24.73	41.72	81.63	25.31	31.33	50.03				
	Type	Direct driven centrifugal fan (forward-curved blades)hot-galvanised steel																					
	Air flow rate	High	m³/h	262	428	431	428	757	945	950	1,066	1,463	1,341	220	424	437	747	898	1,112	1,385			
Sound power level	Available pressure	High	Pa						30								30						
	High	dBA		47.5	52	49	50		52		55	55.5	56	47	52	50	52		55	56			
Sound pressure level	High	dBA		35.5	40	37	38		40	39.5	43	43.5	44	35	40	38	40	39.5	43	44			
Piping connections	Drain	OD	mm	714	884		1,014		1,214		1,464		1,564		1,824		714	884	1,014	1,214	1,464	1,564	1,824
Water connections	Std. heat exchanger	inch							3/4								3/4						
Power supply	Phase / Frequency / Voltage	Hz / V							1~ / 50 / 220-240								1~ / 50 / 220-240						
Current input	High	A		0.15	0.24	0.26	0.25	0.39	0.55	0.53	0.61	0.75		0.15	0.23	0.25	0.38	0.53	0.62	0.74			

FWT-BT

Wall mounted unit



FWT05, 06BT



MERCA



SRC-COB/HPB



WRC-COB/HPB



- > Wide operating range
- > Easy installation and maintenance
- > 3-speed fan motor
- > Double-intake centrifugal fans
- > Excellent air flow and air distribution
- > Flexibility via interchangeable water connection side
- > High power air flow
- > Insulated with self-extinguishing class 1 heat insulation
- > Removable washable air filter (self-extinguishing class 1)
- > Slim and compact aesthetic design
- > Wireless remote control up to 9m distance, availability of a wired or simplified controller
- > LED indicator gives an indication on the (normal or wrong) operation of the unit

INDOOR UNITS				2-PIPE								
		FWT02BT	FWT03BT	FWT04BT	FWT05BT	FWT06BT						
Cooling capacity	Total capacity	High kW	2.34	2.78	3.22	4.54	5.28					
	Sensible capacity	High kW	1.74	2.03	2.35	3.65	4.33					
Heating capacity	2-Pipe	High kW	3.02	3.75	4.10	6.01	6.74					
Power input	High W		24	25	29	66	69					
Dimensions	Unit HxWxD mm	260x799x198		260x899x198		304x1,062x222						
Weight	Unit kg	10		12		16						
	Operation weight kg	10		13		17						
Heat exchanger	Water volume l	0.49		0.57		0.85						
Water flow	Cooling l/h	402		478		781		908				
	Heating l/h	402		478		781		908				
Water pressure drop	Cooling kPa	48.3		64.7		69.3		69.3				
	Heating kPa	42		58.6		60.6		70.6				
Fan	Type	Direct drive cross flow fan										
	Air flow rate m³/h	467		510		586		1,121				
Sound power level	High dBA	53		55		61		64				
Sound pressure level	High dBA	40		39		42		50				
Piping connections	Drain OD mm	16		16		20						
Water connections	Std. heat exchanger inch	1/2										
Power supply	Phase / Frequency / Voltage Hz / V	1~ / 50 / 220-240										
Current input	High A	0.11		0.13		0.29		0.30				



FWL-DT/DF

Flexi type unit



FWL03DT/DF



FWL03DT/DF



FWEC1, 2, 3A



ECFWMB6

- > Low sound power levels and electrical absorption thanks to plastic impeller, ABS winding staircase and improved electric motor
- > Quick fixing system for wall or ceiling mounted installation
- > Pre-assembled 3-way/4-port ON/OFF valves are available
- > Valve packages are insulated, no extra drain pan required
- > Valve packages contain balancing valves and sensor pocket
- > Fast-on connections for electrical options : no tools needed
- > Quick removal of washable filter
- > Electric heater : no relay up to 2kW capacity
- > Electronic controller with water probe, available in standard, advanced and advanced plus version



INDOOR UNITS				2-PIPE							4-PIPE						
	Total capacity	High	kW	FWM01DT	FWM02DT	FWM03DT	FWM04DT	FWM06DT	FWM08DT	FWM10DT	FWM01DF	FWM02DF	FWM03DF	FWM04DF	FWM06DF	FWM08DF	FWM10DF
Cooling capacity	Total capacity	High	kW	1.54	2.09	2.93	4.33	4.77	6.71	8.02	1.46	1.90	2.87	4.33	4.67	6.64	7.88
	Sensible capacity	High	kW	1.20	1.51	2.11	3.15	3.65	4.91	5.96	1.14	1.51	2.07	3.15	3.57	4.85	5.85
Heating capacity	2-Pipe	High	kW	2.14	2.57	3.81	5.63	6.36	7.83	10.03	-	-	-	-	-	-	-
	4-Pipe	High	kW					-			1.90	2.10	3.08	5.05	5.30	7.91	9.30
Power input	High		W	37	53	56		98		137	175	37	53	56	98	137	175
Dimensions	Unit	HxDxW	mm	564x774x226	564x984x226	564x1,194x226	564x1,404x251	564x774x226	564x984x226	564x1,194x226	564x1,404x251						
Weight	Unit		kg	20	21	27	32	33	44		21	22	28	34	35		46
Heat exchanger	Water volume		l	0.5	0.7	1		1.4		2.1	0.5	0.7	1		1.4		2.1
Additional heat exchanger	Water volume		l				-				0.2	0.3		0.4			0.6
Water flow	Cooling		l/h	265	359	504	745	820	1,154	1,343	251	327	494	745	803	1,142	1,355
	Heating		l/h	265	359	504	745	820	1,154	1,343	196	182	286	396	465	694	816
Water pressure drop	Cooling		kPa	13		11	12	14	12	19	13		11	12	14	12	19
	Heating		kPa	9	11	9		10	9	16	7	8	5		10	8	9
Fan	Type			Centrifugal multi-blade, double suction							Centrifugal multi-blade, double suction						
	Air flow rate	High	m³/h	319	344	442	706	785	1,011	1,393	307	327	431	690	763	998	1,362
Sound power level	High		dBA	45	50	47	52	56	58	64	45	50	47	52	56	58	64
Water connections	Std. heat exchanger		inch				1/2			3/4			1/2				3/4
Power supply	Phase / Frequency / Voltage		Hz / V				1 / 50 / 230						1 / 50 / 230				
Current input	High		A	0.17	0.24	0.25	0.44	0.43	0.60	0.76	0.17	0.24	0.25	0.44	0.43	0.60	0.76



FWM01, 02DT/DF



FWM01, 02DT/DF



FWEC1, 2, 3A

- > Low sound power levels and electrical absorption thanks to plastic impeller, ABS winding staircase and improved electric motor
- > Quick fixing system for wall or ceiling mounted installation
- > Pre-assembled 3-way/4-port ON/OFF valves are available
- > Valve packages are insulated, no extra drain pan required
- > Valve packages contain balancing valves and sensor pocket
- > Fast-on connections for electrical options : no tools needed
- > Quick removal of washable filter
- > Electric heater: no relay up to 2kW capacity
- > Electronic controller with water probe, available in standard, advanced and advanced plus version



INDOOR UNITS				2-PIPE							4-PIPE						
	FWM01DT	FWM02DT	FWM03DT	FWM04DT	FWM06DT	FWM08DT	FWM10DT	FWM01DF	FWM02DF	FWM03DF	FWM04DF	FWM06DF	FWM08DF	FWM10DF			
Cooling capacity	Total capacity	High	kW	1.54	2.09	2.93	4.33	4.77	6.71	8.02	1.46	1.90	2.87	4.33	4.67	6.64	7.88
	Sensible capacity	High	kW	1.20	1.51	2.11	3.15	3.65	4.91	5.96	1.14	1.51	2.07	3.15	3.57	4.85	5.85
Heating capacity	2-Pipe	High	kW	2.14	2.57	3.81	5.63	6.36	7.83	10.03	-	-	-	-	-	-	-
	4-Pipe	High	kW				-				1.90	2.10	3.08	5.05	5.30	7.91	9.30
Power input	High		W	37	53	56	98		137	175	37	53	56	98	137	175	
Dimensions	Unit	HxWxD	mm	535x584x224	535x794x224	535x1,004x224	535x1,214x249	535x584x224	535x794x224	535x1,004x224	535x1,214x249						
Weight	Unit		kg	14	15	19	23		32	15	16	20	25			34	
Heat exchanger	Water volume		l	0.5	0.7	1	1.4		2.1	0.5	0.7	1	1.4			2.1	
Additional heat exchanger	Water volume		l			-				0.2	0.3	0.4				0.6	
Water flow	Cooling		l/h	265	359	504	745	820	1,154	1,343	251	327	494	745	803	1,142	1,355
	Heating		l/h	265	359	504	745	820	1,154	1,343	196	182	286	396	465	694	816
Water pressure drop	Cooling		kPa	13		11	12	14	12	19	13		11	12	14	12	19
	Heating		kPa	9	11	9	10	9	16	7	8	5	10	8	9		
Fan	Type	Centrifugal multi-blade, double suction							Centrifugal multi-blade, double suction								
	Air flow rate	High	m³/h	319	344	442	706	785	1,011	1,393	307	327	431	690	763	998	1,362
Sound power level	High		dBA	45	50	47	52	56	58	64	45	50	47	52	56	58	64
Piping connections	Drain	OD	mm			17							17				
Water connections	Std. heat exchanger		inch			1/2		3/4				1/2			3/4		
Power supply	Phase / Frequency / Voltage		Hz / V			1~ / 50 / 230							1~ / 50 / 230				
Current input	High		A	0.17	0.24	0.25	0.44	0.43	0.60	0.76	0.17	0.24	0.25	0.44	0.43	0.60	0.76

FWD-AT/AF

Flexi type unit



FWD04AT/AF



FWD04AT/AF



FWEC1,2,3A



- > Quick fixing system for wall or ceiling mounted installation
- > Straight duct connector is mounted to discharge side
- > Electronic controller with water probe, available in standard, advanced and advanced plus version
- > The air filter can easily be removed for cleaning

INDOOR UNITS				2-PIPE							4-PIPE						
	FWD04AT	FWD06AT	FWD08AT	FWD10AT	FWD12AT	FWD16AT	FWD18AT	FWD04AF	FWD06AF	FWD08AF	FWD10AF	FWD12AF	FWD16AF	FWD18AF			
Cooling capacity	Total capacity	High	kW	3.90	6.20	7.80	8.82	11.90	16.40	18.30	3.90	6.20	7.80	8.82	11.90	16.40	18.30
	Sensible capacity	High	kW	3.08	4.65	6.52	7.16	9.36	12.80	14.10	3.08	4.65	6.52	7.16	9.36	12.80	14.10
Heating capacity	2-Pipe	High	kW	4.05	7.71	9.43	10.79	14.45	19.81	21.92	4.49	6.62	9.21	15.86	-	21.15	-
	4-Pipe	High	kW	-	-	-	-	-	-	-	234	349	443	714	1,197	1,197	1,197
Power input	High		W	234	349	443	714	1,197	234	349	443	714	1,197	1,197	1,197	1,197	1,197
Dimensions	Unit	HxWxD	mm	280x754x559	280x964x559	280x1,174x559	352x1,174x718	352x1,384x718	280x754x559	280x964x559	280x1,174x559	352x1,174x718	352x1,384x718	352x1,174x718	352x1,384x718	352x1,174x718	352x1,384x718
Weight	Unit		kg	33	41	47	49	65	77	80	35	43	50	52	71	83	86
Heat exchanger	Water volume		l	1.06	1.42	1.79	2.38	2.5	4.02	5.03	1.06	1.42	1.79	2.38	2.50	4.02	5.03
Additional heat exchanger	Water volume		l	-	-	-	-	-	-	-	0.35	0.47	0.59	1.42	1.72	1.72	1.72
Water flow	Cooling		l/h	674	1,064	1,339	1,514	2,056	2,833	3,140	674	1,064	1,339	1,514	2,056	2,833	3,140
	Heating		l/h	674	1,064	1,339	1,514	2,056	2,833	3,140	349	581	808	1,392	1,856	1,856	1,856
Water pressure drop	Cooling		kPa	17	24	16	26	34	45	17	24	16	26	34	45	45	45
	Heating		kPa	14	20	13	21	28	37	9	15	13	12	16	16	16	16
Fan	Type	Centrifugal multi-blade, double suction										Centrifugal multi-blade, double suction					
	Air flow rate	High	m³/h	800	1,250	1,600	2,200	3,000	800	1,250	1,600	2,200	3,000				
	Available pressure	High	Pa	66	58	68	64	97	145	134	63	53	63	59	92	138	128
Sound power level	High		dBA	66	69	72	74	78	66	69	72	74	78				
Piping connections	Drain	OD	mm	16							16						
Water connections	Std. heat exchanger		inch	3/4				1				3/4				1	
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 230							1~ / 50 / 230						
Current input	High		A	0.95	1.58	1.97	3.21	5.37	0.95	1.58	1.97	3.21	5.37				

FWV-DT/DF

Floor standing unit



FWV01, 02DT/DF



FWEC1, 2, 3A



ECFWMB6

- › Low sound power levels and electrical absorption thanks to plastic impeller, ABS winding staircase and improved electric motor
- › Quick fixing system for wall mounted installation
- › Pre-assembled 3-way/4-port ON/OFF valves are available
- › Valve packages are insulated, no extra drain pan required
- › Valve packages contain balancing valves and sensor pocket
- › Fast-on connections for electrical options : no tools needed
- › Quick removal of washable filter
- › Electric heater : no relay up to 2kW capacity
- › Electronic controller with water probe, available in standard, advanced and advanced plus version



INDOOR UNITS				2-PIPE							4-PIPE						
	Total capacity	High	kW	FWV01DT	FWV02DT	FWV03DT	FWV04DT	FWV06DT	FWV08DT	FWV10DT	FWV01DF	FWV02DF	FWV03DF	FWV04DF	FWV06DF	FWV08DF	FWV10DF
Cooling capacity	Total capacity	High	kW	1.54	2.09	2.93	4.33	4.77	6.71	8.02	1.46	1.90	2.87	4.33	4.67	6.64	7.88
	Sensible capacity	High	kW	1.20	1.51	2.11	3.15	3.65	4.91	5.96	1.14	1.51	2.07	3.15	3.57	4.85	5.85
Heating capacity	2-Pipe	High	kW	2.14	2.57	3.81	5.63	6.36	7.83	10.03	-	-	-	-	-	-	-
	4-Pipe	High	kW					-			1.90	2.10	3.08	5.05	5.30	7.91	9.30
Power input	High		W	37	53	56		98		137	175	37	53	56	98	137	175
Dimensions	Unit	HxWxD	mm	564x774x226	564x984x226	564x1,194x226		564x1,404x251		564x774x226	564x984x226	564x1,194x226	564x1,404x251				
Weight	Unit	kg	kg	19	20	25	30	31		41	20	21	26	32	33		44
Heat exchanger	Water volume		l	0.5	0.7	1		1.4		2.1	0.5	0.7	1	1.4			2.1
Additional heat exchanger	Water volume		l					-			0.2	0.3	0.4			0.6	
Water flow	Cooling	l/h	265	359	504	745	820	1,154	1,343	251	327	494	745	803	1,142	1,355	
	Heating	l/h	265	359	504	745	820	1,154	1,343	196	182	286	396	465	694	816	
Water pressure drop	Cooling	kPa	13		11	12	14	12	19	13	11	12	14	12	19		
	Heating	kPa	9	11	9		10	9	16	7	8	5	10	8	9		
Fan	Type	Centrifugal multi-blade, double suction												Centrifugal multi-blade, double suction			
	Air flow rate	High	m³/h	319	344	442	706	785	1,011	1,393	307	327	431	690	763	998	1,362
Sound power level	High	dBA		45	50	47	52	56	58	64	45	50	47	52	56	58	64
Piping connections	Drain	OD	mm				16							16			
Water connections	Std. heat exchanger	inch				1/2			3/4				1/2			3/4	
Power supply	Phase / Frequency / Voltage	Hz / V		1 / 50 / 230							1 / 50 / 230						
Current input	High	A		0.17	0.24	0.25	0.44	0.43	0.60	0.76	0.17	0.24	0.25	0.44	0.43	0.60	0.76



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

FSC

ECPEN11-410

Daikin products are distributed by:

Daikin Europe N.V. participates in the Eurovent Certification programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.