

USING



YOU CAN:



BUILD VALUE



ADD INTEREST



**ACCENT
ACCENT
INTERIORS
INTERIORS**



CANT READ - PLEASE SEND



BISON BUILDING SOLUTIONS

5360 Genesee St.
Bowmansville, NY 14026
(716) 650-4533

**YOU DESIGN IT,
WE COVER IT!**

- > LIGHTWEIGHT AND DURABLE
- > NO SPECIAL TOOLS OR SKILLS REQUIRED
- > INTERIOR OR EXTERIOR
- > APPLY TO MOST SOLID SURFACES



The Do-It Yourself Brick Veneer

**YOU DESIGN IT,
WE COVER IT!**




CANT READ - PLEASE SEND

EASY TO USE



1 Apply FLEXEBRICK™ mortar, prime surface if needed.



2 Press bricks in place, leaving 3/8 spacing.



3 FLEXEBRICK™ can be easily cut using scissors or a sharp knife.



4 Corner bricks are available for outside corners.



5 Smooth the joints with a damp paint brush.

TOOLS REQUIRED:

1. Line Level or Laser
2. Level 3/16 in. Notched Trowel
3. Scissors
4. 3/8 in. Flat Paint Brush

PROJECT ESTIMATOR

BOXES NEEDED

	3 FT	4 FT	5 FT	6 FT	7 FT
5 FT	1 15 sq. ft	2 20 sq. ft	2 25 sq. ft	2 30 sq. ft	3 35 sq. ft
6 FT	2 18 sq. ft	2 24 sq. ft	2 30 sq. ft	3 36 sq. ft	3 42 sq. ft
8 FT	2 24 sq. ft	3 32 sq. ft	3 40 sq. ft	4 48 sq. ft	4 56 sq. ft
10 FT	2 30 sq. ft	3 40 sq. ft	4 50 sq. ft	4 60 sq. ft	5 70 sq. ft
12 FT	3 36 sq. ft	4 48 sq. ft	4 60 sq. ft	5 72 sq. ft	6 84 sq. ft
14 FT	3 42 sq. ft	4 56 sq. ft	5 70 sq. ft	6 84 sq. ft	7 98 sq. ft

TOOLS REQUIRED: 8" x 6" wall = 4 boxes

NOTES:

One (1) Box of FLEXEBRICK™ Flat Brick contains 90 bricks and will cover 15 sq. ft.

FLEXEBRICK™ 6-Packs are available. Each package provides 1 sq. ft of coverage.

Use FLEXEBRICK™ Corners to cover all right angles in your project. One (1) Box of corner brick provides eight (8) linear feet.

In order to obtain proper adhesion FLEXEBRICK™ Mortar must be used. The 11lb pail will cover up to 20 sq. ft and the 44lb pail will cover up to 80 sq. ft. Mortar color can enhance the look of your project.

SURFACE APPLICATIONS

APPLY ALMOST ANYWHERE

BASE SURFACE	USE INDOORS	USE OUTDOORS
Dry Wall	Yes*	N/A
Stucco	After leveling surface	After leveling surface
Sheet Material (Wood)	Yes**	No**
Sheet Material (Plastic/Foam)	Yes	Yes, use only outdoor rated foam or plastic
Concrete/Concrete Board	Yes*	Yes*
Masonry/Poured Concrete	After leveling surface	After leveling surface
Any Rigid Semi-Smooth Surface	Yes*	Yes* (Outdoor quality surface only)
Traffic areas such as Sidewalks & Driveways	No	No

* Before applying FLEXEBRICK™ we strongly recommend you pre-treat the base surface, using a primer. Use any standard water based acrylic primer. We also recommend using mesh on joint seams to prevent cracks.

** Chip board, particle board of any type, luan, OSB, and tongue and groove planking are unsuitable substrates to directly install FLEXEBRICK™ over. These materials tend to swell, warp, and delaminate when exposed to moisture. For these applications, we recommend covering the wood with exterior sheet metal material.

FLEXEBRICK™ is not suitable for high traffic areas.



The Do-It Yourself Brick Veneer

PRODUCTS INCLUDE:



FLAT BRICK

AVAILABLE COLORS: Flamed Grey, Burned Red, Firehouse, Sierra, Alaskan White

BRICK SIZE: 7 5/8 X 2 5/8"



CORNER BRICK

AVAILABLE COLORS: Flamed Grey, Burned Red, Firehouse, Sierra, Alaskan White

BRICK SIZE: 7 5/8 X 3 5/8" X 2 5/8"



AVAILABLE COLORS: Grey, Sand (Light Grey)

BUCKET SIZE: 11 lb. pail up to 20 sq. ft.; 44 lb. pail up to 80 sq. ft.

* Failure to use genuine FLEXEBRICK™ Mortar/Adhesive voids all warranties, written or implied. Full warranty conditions are available upon request.