

## King of the Farm

1. Weight: 12,000lb
2. 16 MPH (16.1 mph will result in a DQ) Speed board will be required at the event with this class
3. 3,000 RPM. (Any tractor found to be over the allowed RPM limit will be disqualified.) Tractor must have an ISSPRO single magnetic pickup attached to the front of the engine to measure engine RPM's. The lead from the pickup to the rear of the tractor is to be made of 14-16 gauge wire attached to a 110V, 3-prong female electrical outlet. The 2 wires from the pickup need to be attached to the 2 main spades, not the ground spade, of the electrical outlet. This outlet receptacle needs to be mounted next to the rear mounted air shutoff cable. Wire must be one continuous wire that is visible with no splices. If you compete at sanctioned events with Pull-Off Productions, this system must be attached and in working order.
4. No cubic inch limit
5. Wide Front end only
6. Side Shields
7. Roll Bar or Cage
8. Helmet
9. Ag Tires only. Sizes 18.4 / 20.8 - 38 or 42 only (no cut tires)
10. Air Shut Off required
11. Tractor must have an operator controlled fuel shut-off valve (not the injection pump shut-off).
12. Wheelie Bars Required. ( See general rules for)
13. Turbo size 2.8 (T-4 base)
14. Seat belt Required. (Five-point harness and helmet required with a roll cage)
15. Driver must wear long pants and leather work shoes.
16. Cross bolts in the exhaust. (See general rules for requirement)
17. Stock Wheelbase
18. Chassis rules follow Ag stock chassis, engine and frame configuration.
19. Drawbar height 20" maximum. Drawbar length no shorter than 18" from center of rear axle. Drawbar must be rigid with no movement allowed. (No vertical hitches or clevis allowed). Built pulling hitches are allowed.
20. No weights pass the rear tires
21. Motor driven fans must be shrouded.
22. No water injection, No intercoolers
23. Newer Electronic tractors allowed as long as they meet all other rules.
24. Minimum Age for this class 16
25. Pull-Off Productions reserves the right to make any changes to these rules.

## **ECIPA TOO HOT TO FARM RULES**

General Rules:

- 1) Too Hot To Farm tractors must have 200# of moveable weight. Compeng weights are listed below:
  - 12,000lbs with non-cut res
  - 11,000lbs with cut res
- 2) All ECIPA Too Hot To Farm tractors will be of a stock chassis, engine and frame configuraon. Any deviaon from this must get board approval.
- 3) Engine must be 650 CID or less.
- 4) RPM – 3000 RPM maximum, no RPM tolerance or grace allowed. RPMS will be electronically checked. All Too Hot To Farm tractors must have a magnec pickup aached to the front of the engine to measure engine RPM. The lead wires from the pickup to the rear of the tractor are to be made of 14 or 16- gauge wire, and aached to a 110-volt, 3 prong female electrical outlet. The 2 wires from the pickup need to be aached to the 2 main spades, not the ground spade (round). This pickup cannot be used to supply RPM to a tachometer used on the tractor. Do not supply voltage, or ground to the wires, or the plug. The outlet receptacle needs to be mounted next to the rear mounted air shutoff cable.
- 5) Maximum re sizes 20.8 x 38 or 18.4 x 42 only.
  - Cut res are legal, but must compete at 11,000lbs.
- 6) PTO/HYD. – not required.
- 7) Water Injecon into air intake allowed.
- 8) Diesel fuel must test 150 or under on ECIPA fuel test
- 9) 16-mile per hour speed limit enforced. There will be no grace, 16.1mph or over will result in a DQ. Speed will be policed by a digital radar sign or pace tractor if needed.
- 10) No weight protruding beyond the rear res. Hitch must be free and clear and able to reach with hook without excessive work. Sled operator has the right to decline the hook to any tractor regarding this maer.
- 11) Plasc radiator fans are recommended but not mandatory.
- 12) Wheelie bars are mandatory and must be the same dimensions as limited pro stock.
- 13) ROPS, side shields & steel flywheels mandatory.
- 14) 9 bolt U-style clamps on hubs prohibited.
- 15) All contestants must wear, seatbelt, full length pants and shirt.
  - MUST wear a helmet and neck brace if the tractor has a roll cage.
- 16) In the event of a DQ due to exceeding the 16 mph speed limit, the contestant will be awarded last place points.
- 17) ECIPA reserves the right to make any changes at any me to these rules.
- 18) All other general and contest rules are strictly enforced.

Turbo Rules:

- 1) Add-on turbochargers are allowed and must be shielded with a minimum of .060" thick steel shield the full length of internal rotang assembly.
- 2) Air shut offs are mandatory.