

Fab-Form Form Release

- Ready to Use Release Agent
- Non-Staining Formulation
- Chemical Release
- Contains No Waxes
- Will Not Transfer

DESCRIPTION AND USE

FAB-FORM is a ready to use, non-staining chemical form release primarily designed for use on wooden forms. By reacting with the alkalinity in Portland Cement, a release barrier is created, facilitating easy removal of formwork. It does not contain waxes.

ADVANTAGES

FAB-FORM will not transfer to the concrete surface, nor interfere with later surface treatments such as painting or tiling. Because there is no transfer of concrete, form build-up is eliminated. FAB-FORM resists rainwater penetration and protects from grain raising.

APPLICATION

On new wooden forms, two or more coats of FAB-FORM are recommended as a sealer. On previously used forms, only dusting to remove any powder deposit is required prior to application. Apply as supplied by brush, roller or spray to a clean surface. DO NOT DILUTE.

CAUTION

FAB-FORM contains petroleum solvents and should be handled accordingly. Adequate ventilation should be provided and prolonged inhalation of vapors should be avoided. Materials must be kept away from fire or flame. Goggles are advised to avoid eye irritation. Consult the Material Safety Data Sheet before using this product.

COVERAGE

Depending on condition of forms, coverage will usually range from 800 to 1000 square feet per gallon.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 3-B 08/'03

Bulletin 3-B — 08/'03