

Fab-Weld Bonding Agent

- **Latex-Based**
- **Re-emulsifies**
- **Improves Strength**
- **Apply to Substrate**
- **Use as Admixture**

DESCRIPTION AND USE

FAB-WELD is a re-emulsifying latex admixture and bonding agent for concrete and plaster. It is designed to improve not only bond but also tensile and flexural strengths.

ADVANTAGES

FAB-WELD is a multi-purpose bonding adhesive and sealing compound. It will provide a bond for new concrete to old, both for surfacing and patching. As an admixture, it imparts extra elasticity, toughness and impact resistance. Floors incorporating FAB-WELD have greater resistance to the action of oil, grease and acid, and will not dust.

APPLICATION

All surfaces to receive FAB-WELD as a bonding agent or to be patched or surfaced with FAB-WELD modified mortar should be free from loose material, oil, grease, dirt, etc.

To use as a bonding agent apply by brush to a clean surface. FAB-WELD will dry normally in 15 to 30 minutes. The topping or patching mortar may be applied to wet or dry FAB-WELD since the dried film will be reactivated by the moisture in the mix.

To use as an admixture, use 2 gallons of FAB-WELD per sack of cement. Add the FAB-WELD to the mixing water. Apply topping or patch only to clean, sound surfaces, which have been coated with FAB-WELD.

LIMITATIONS

Do not use FAB-WELD where concrete is permanently wet or totally immersed.

COVERAGE

One gallon of FAB-WELD will cover about 200 square feet.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 2-B
08/'03

Bulletin 2-B — 08/03

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456