

Fabrikem® Powder Release Agent



- Facilitates Easier Release
- Extends Life of Imprinting Tools
- Reduces Labour for Imprinting
- 12 Standard Colours
- Custom Colours Available

DESCRIPTION AND USE

FABRIKEM® RELEASE AGENT is a dry shake material engineered to facilitate the use and release of stamp tools for imprinting during the plastic set stage of concrete. FABRIKEM® RELEASE AGENT is formulated with blended, UV stable, high quality synthetic pigments, micronized aggregates, hydrophobic materials and admixtures providing easy release of imprint tools and rich accent colors. FABRIKEM® RELEASE AGENT increases imprint tool life and reduces imprinting labor. It is available in 30 lb. pails and in a wide assortment of colors. FABRIKEM® RELEASE AGENT is designed for use on all interior and exterior stamped concrete, imprinted horizontal and vertical surfaces.

APPLICATION

Installation Instructions

Upon completing final troweling of integral colored or color hardened concrete, apply a light even coat of FABRIKEM® RELEASE AGENT over the area to be imprinted. Allow bleed water to dissipate before broadcasting RELEASE AGENT on surface. RELEASE AGENT shall be applied in one or more broadcasts. Use "hand broadcast" method applying evenly and consistently. It is generally recommended that the RELEASE AGENT be a complimentary contrasting color, usually darker than the concrete. Recommended application rate is 30 lbs. per 800 square feet. Never trowel RELEASE AGENT into the surface, as this will cause discoloration and reduce concrete strength. Do not add water to surface while imprinting over RELEASE AGENT. In some instances RELEASE AGENT may be used in conjunction with FABRIKEM® LIQUID RELEASE. Contractors should test this method and perfect their techniques before attempting installation.

Cleaning

Once concrete has set, remove excess RELEASE AGENT with soft bristle broom or vacuum or in some instances hose off with clean water. Take care not to damage the surface before concrete has reached final set. After the concrete has reached initial cure, wash the surface, scrubbing with broom and commercial degreaser. Surface is sufficiently clean when water on the surface no longer beads. Finishing: All colored and imprinted concrete surfaces should have a sealer or water repellent coating applied to protect the finish from moisture and oxidization. Apply FABRIKEM® CURE & SEAL as soon as possible. Follow up with FABRIGLAZE® High Solids Sealer after 28 days. Follow FABRIKEM® technical bulletins for selected product.

LIMITATIONS

Protect all surfaces that are not intended to receive RELEASE AGENT. Take caution when using during windy conditions or where rapid air movement exists. Use a commercial grade detergent to facilitate the removal in unwanted areas. Never leave excess residue of RELEASE AGENT on a substrate that is to be covered with concrete or other surface finishes.

Consult product Material Safety Data Sheet before using.

Bulletin 153-A
01/15

COVERAGE

Coverage for FABRIKEM® RELEASE AGENT is approximately 800 square feet per pail.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 153-A — 01/15

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456