

Fabrikem® Versaguard

- Removes Encrustations
- Safe Around Steel Parts
- Removes Lime & Mineral Deposits
- Easy Application & Rinsing

DESCRIPTION AND USE

VERSAGUARD removes encrusted concrete, cement and cement dust from concrete tools, forms, molds, masonry equipment, concrete trucks, slides and chutes. VERSAGUARD acts quickly to dissolve concrete and cement while protecting exposed metal parts.

ADVANTAGES

- Won't attack metal (steel) parts
- Removes encrusted concrete and cement quickly
- Removes lime and mineral deposits quickly

APPLICATION

VERSAGUARD can be sprayed from all plastic pump type-sprayer, rolled, brushed or flooded.

To remove concrete, use product undiluted. Spray liberally onto areas, allow VERSAGUARD to dwell for several minutes and rinse surface with water. Although VERSAGUARD won't attack metal surfaces, they should be thoroughly rinsed.

For excessively encrusted concrete, spray VERSAGUARD liberally to the affected area and agitate the surface with a brush or broom to ensure VERSAGUARD comes in contact with all the cement/concrete. Allow VERSAGUARD 5-10 minutes to react and then rinse with water.

LIMITATIONS

VERSAGUARD will not attack metal surfaces but may cause some discolouration when in contact with metal. Avoid galvanized or chrome surfaces. Consult product Material Safety Data Sheet before using. Re-apply as required.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when they are applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 91-A
01/'15

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456