

Fabrikem® White Out

- Corrective Treatment
- Enhanced Aesthetics
- Gloss Enhancement
- Improved Appearance
- Extended Service Life

Bulletin 194-A
04/'14

DESCRIPTION AND USE

FABRIKEM® WHITE OUT is used to remove “blushing” in solvent-based sealers that have been applied over concrete with excess moisture content or under conditions in which premature drying occurred prior to full penetration of the sealer. FABRIKEM® WHITE OUT dissolves acrylic sealers and allows trapped moisture to dissipate enabling the sealer to penetrate into the concrete substrate. Once the FABRIKEM® WHITE OUT has dried, the surface is ready to be re-sealed (if required).

ADVANTAGES

FABRIKEM® WHITE OUT helps to remove unsightly whitening in solvent base sealers and restore the aesthetic of the underlying substrate. Spot touch ups of affected areas can often be performed without requiring the re-sealing of the entire surface.

APPLICATION

Cover the affected area by spraying or pouring and scrub in with solvent compatible brush. Repeat if necessary until blush has disappeared. If required, apply a new coat of sealer to area. Ambient and substrate temperatures must be above 4°C but below 30°C during and immediately following application.

A test panel in an inconspicuous place is always advisable before undertaking full scale application. Variations in conditions such as surface profile, porosity, and underlying state can impact the final appearance. A test panel helps predict what the finished project will look like and whether or not the desired effect is achievable.

COVERAGE

Coverage will vary depending upon substrate condition and porosity and application requirements to achieve desired effect. Typical coverage is about 200 square feet per gallon; however a test panel will determine more precise coverage for the actual surface to be treated.

LIMITATIONS

FABRIKEM® WHITE OUT should not be applied to surfaces which have been excessively wet or rained on during any of the three preceding days or if rain is expected within four hours following application. The surface and ambient temperatures should be a minimum of 4°C (40° F) and expected to remain so for at least 24 hours following application.

Protect all surrounding and adjacent surfaces. Do not to allow FABRIKEM® WHITE OUT to reach surfaces such as shrubbery, landscaping, glass, or aluminium. Do not let this product come in contact with any surface which is susceptible to deterioration through solvent interaction. All painted surfaces must be protected.

Goggles are advised to avoid eye irritation. **AVOID CONTACT WITH SKIN.** Keep away from ignition sources and use only in well ventilated areas. Consult the product MATERIAL SAFETY DATA SHEET before using.

GUARANTEE

FABRIKEM® WHITE OUT is manufactured with the finest raw materials, under exacting care to produce a product of the highest quality. FABRIKEM MANUFACTURING LTD., as always, guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection and other factors beyond the manufacturer's control cannot be held to be the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 194-A — 04/'14

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456