

Fabriplug

- Quick Setting
- Stops Running Water
- Non-Shrink
- Waterproof
- High Strength

Bulletin 65-B
08/'03

DESCRIPTION AND USE

FABRIPLUG is a quick set, hydraulic cement that instantly stops running water through concrete and masonry substrates. Its special non-shrink formulation actually causes the material to expand, locking into the treated area. FABRIPLUG normally sets in 3 to 5 minutes depending on ambient conditions and water temperature.

In addition to stopping running water, FABRIPLUG can also be used to grout pipe, conduit, or anchor bolts.

ADVANTAGES

Because FABRIPLUG is quick setting, running water can be controlled. This also means that it can be used underwater. FABRIPLUG is nonmetallic and will therefore not rust or otherwise deteriorate.

Its extremely high strength means that FABRIPLUG will last even in the toughest of conditions.

COVERAGE

One pound of FABRIPLUG will fill approximately 17 cubic inches.

APPLICATION

Areas to be sealed with FABRIPLUG must be structurally sound. All loose and friable material should therefore be removed. Cut out areas to a minimum width of $\frac{3}{4}$ inches ensuring that the channel is undercut or straight cut. Never use a V cut since the expansive properties of FABRIPLUG will cause the material to push itself out of the channel.

Thoroughly flush the areas to be treated to ensure that all dust, etc. has been removed.

Where hydrostatic pressure is present, mix a small quantity of FABRIPLUG to a stiff mortar consistency and hold until it begins to warm. Force the material into the prepared area and hold for several minutes.

FABRIPLUG should be kept moist for at least 15 minutes after placing.

LIMITATIONS

FABRIPLUG is a temperature sensitive material — high temperatures accelerate the set; low temperatures retard the set. Special procedures are therefore required to use FABRIPLUG in extreme conditions. Consult the manufacturer for specific details.

CAUTION

FABRIPLUG is highly alkaline and is therefore irritating to eyes and skin. Avoid contact with eyes and skin. In case of contact, thoroughly flush with large amounts of water and call physician immediately. DO NOT RUB EYES. Wash thoroughly after handling. Do not take internally. Keep out of reach of children. Keep product dry. Consult Material Safety Data Sheet before using this product.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 65-B — 08/'03

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456