

Fabriseal®

- Waterproof
- Cement-Based
- Suitable for Submersion
- Textured Finish
- Available in Grey or White

Bulletin 64-C
08/'03

DESCRIPTION AND USE

FABRISEAL® is a waterproof, cement based coating designed for both above and below-grade applications. It is suitable for use on concrete and masonry walls, foundations, pools, and cisterns, FABRISEAL® can be applied over shotcrete (gunite) to give a smoother, waterproof finish. The product is available in either a regular or fine grade depending upon the degree of protection required and the desired aesthetic appearance.

ADVANTAGES

FABRISEAL® is similar in formulation to concrete, it actually becomes an integral part of the substrate. Its chemical make-up also causes FABRISEAL® to stand up well under continual submersion in water.

APPLICATION

Surfaces to be treated must be sound and clean, free from all efflorescence, form treatments, laitance, dust, dirt, chalk, vegetable growth, or anything which could inhibit the bonding performance of the material. Surface imperfections should be ground or patched if a decorative finish is required. Rusted or corroded metal and form ties should be cut back approximately ¾" - 1" and patched with FABRIPATCH®.

Mix FABRISEAL® with clean, potable water. For added bonding performance use one part of FABRIBOND A mixed with three parts of water. One pail of FABRISEAL® requires approximately 2 gallons of liquid.

Mix FABRISEAL® to a heavy pancake batter consistency. Allow the material to fatten for about 10 minutes then remix. Best results are obtained when a paddle mixer and drill are used.

Surfaces to be treated should be dampened prior to the application of FABRISEAL®. If the surface becomes dry or if the mix begins to pull during application, redampen the surface. Do not re-temper or thin FABRISEAL®.

CAUTION

FABRISEAL® is highly alkaline and is therefore irritating to eyes and skin. Avoid contact with eyes and skin. In case of contact, thoroughly flush with large amounts of water and call physician immediately. DO NOT RUB EYES. Wash thoroughly after handling. Do not take internally. Keep out of reach of children. Keep product dry. Consult Material Safety Data Sheet before using this product.

LIMITATIONS

Do not apply FABRISEAL® to frozen or frost-filled surfaces or when the temperature is below 4°C or expected to fall below 4°C within 24 hours.

Care should be taken to avoid overdampening walls in cooler weather. Conversely, additional fogging may be required in warmer weather. FABRISEAL® may require fog misting when applied in warm or windy weather to prevent rapid drying. Allow FABRISEAL® to cure for seven days before filling tanks, pools, cisterns and reservoirs. Do not apply FABRISEAL® over painted surfaces. Freshly placed masonry, concrete, or stucco must be cured for a minimum of 28 days.

COVERAGE

FABRISEAL® (Regular) is normally applied at a rate of 2#/yd² per coat. FABRISEAL® (Fine) is normally applied at a rate of ½ - 1#/yd².

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 64-C — 08/03

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com


FABRIKEM
Toll Free: 800-441-7456