

Fabrishield® Natural Stone Enhancer



- Highlighted Finish
- Enhanced Aesthetics
- Water Repellent
- Improved Appearance
- Extended Service Life

DESCRIPTION AND USE

FABRISHIELD® NATURAL STONE ENHANCER is designed for use on natural stone and concrete surfaces requiring an enriching of the integral colour. It is a VOC compliant blend of penetrating ingredients (silane/siloxane monomers and oligomers) which intensify the colour of treated surfaces without leaving a slippery surface film. The low VOC's (< 45 grams per litre) make it an environmentally responsible selection.

ADVANTAGES

FABRISHIELD® NATURAL STONE ENHANCER is specifically designed for use on natural stone and concrete surfaces and is fully compatible with the constituent components found in these materials. Faded and weathered appearances can be rejuvenated without the need for costly and wasteful removal and replacement. They are part of a family of integrated solutions formulated to clean, enhance, and protect stone, concrete, and hardscape surfaces.

APPLICATION

Surfaces to be treated must be clean and free of defects. A range of FABRIKEM® CLEANERS are available to address such issues as efflorescence, rust, oil and grease, or moss and algae. Surfaces to be treated must be thoroughly dry and no precipitation (or adjacent irrigation) expected for at least 24 hours following application. Ambient and substrate temperatures must be above 4°C but below 30°C during and immediately following application.

A test panel in an inconspicuous place is always advisable before undertaking full-scale application. Variations in conditions such as surface condition, porosity, profile, and underlying colour can influence the final appearance. A test panel helps predict what the finished project will look like and whether or not the desired effect is achievable.

Once surface preparation and testing have been completed, apply the product in a uniform manner, consistent with the technique employed in preparing the test panel. FABRISHIELD® NATURAL STONE ENHANCER can be applied by brush, roller or low-pressure spray (hand pump type). Care must be taken in the overlap of these products to avoid ribboning of the edges of each pass. Failure to feather the overlap zone can lead to localized intensification of darkening or colouration.

COVERAGE

Coverage will vary depending upon substrate condition and porosity and application requirements to achieve desired effect. Typical coverage is about 100 square feet per gallon; however, a test panel will determine more precise coverage for the actual surface to be treated.

Bulletin 134-A
06/'20

LIMITATIONS

FABRISHIELD® NATURAL STONE ENHANCER should not be applied to surfaces which have been excessively wet or rained on during any of the three preceding days or if rain is expected within twenty-four hours following application. The surface and ambient temperatures should be a minimum of 4°C (40° F) and expected to remain so for at least 24 hours following application.

It is advisable to protect all surrounding and adjacent surfaces. Do not to allow FABRISHIELD® NATURAL STONE ENHANCER to reach surfaces such as shrubbery, landscaping, glass, or aluminium. Should contact occur, clean of within 30 minutes of application. All painted surfaces should be protected.

Goggles are advised to avoid eye irritation. **AVOID CONTACT WITH SKIN.** Consult the product SAFETY DATA SHEET before using.

GUARANTEE

FABRISHIELD® NATURAL STONE ENHANCER is manufactured with the finest raw materials, under exacting care to produce a product of the highest quality. FABRIKEM MANUFACTURING LTD., as always, guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection and other factors beyond the manufacturer's control cannot be held to be the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

LEED INFORMATION

VOC's = <45 g/l
Manufactured in Langley BC
0% Recycled Content (Consumer and/or Industrial)

Bulletin 134-A – 06/'20

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com


FABRIKEM
Toll Free: 800-441-7456