

Fabritone® Tiquing Stain

- Integral Colouration
- Variegated Colours
- Natural Appearance
- Earth Tone Colour Range

DESCRIPTION AND USE

Fabritone® Tiquing Stain is a colouring treatment for decorative concrete surfaces. Fabritone® Tiquing Stain is applied to stamped and imprinted concrete to provide secondary colour and accent to create the authentic appearance of stone and tile finishes. Fabritone® Tiquing Agent can be used in new decorative concrete applications or to revitalize weathered concrete surfaces. Fabritone® Tiquing Agent is available in a variety of colours that can be mixed together in countless concentrations to achieve infinite customized and varying results.

ADVANTAGES

Fabritone® Tiquing Stain is easily applied and offers maximum control of the colouring process. This product is water-based and non-hazardous. The concrete character is highlighted producing the look of authentic, natural elements of nature. Shades produced from each of the colours are unique to each surface and vary over the area stained. These variegations, variances and colour shifts are both natural and desirable in this colouration system.

APPLICATION

Inspect all surfaces to ensure that they are sound, free of dirt and other contaminants. Existing concrete should be at least 28 days old. Surface preparation and cleaning is important for obtaining desirable results. A light acid wash is desirable prior to application to ensure that there is some surface suction available. Remove loose material, scaling and oxidized particles from surface.

Apply Fabritone® Tiquing Stain by sprayer and at coverage rates established by testing to achieve the desired results.

COVERAGE

Fabritone® Tiquing Stain is available in 1 gallon and 5 gallon containers and yields 200 - 400 square feet per gallon depending on desired result. **TEST PANELS ARE IMPERATIVE.**

Bulletin 47-B
06/'20

LIMITATIONS

Fabritone® Tiquing Stain should not be applied to tight steel trowelled concrete as there must be sufficient absorption to draw the product into the surface.

Product will slightly darken in colour as it dries. Once it has dried, surfaces treated with Fabritone® Tiquing Stain should be sealed with an appropriate Fabriglaze® product to provide long term durability and surface abrasion resistance. Contact the manufacture for specific product recommendations.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when they are applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 47-B — 06/20

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456