FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

SECTION 01 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Fabrikem® Manufactured Stone Cleaner Type 110		
Recommended Use Masonry Cleaning Compound		
Manufacturer's Name Fabrikem Manufacturing Ltd. 20361 Duncan Way, Langley, BC V3A 7N3		
Supplier's Name	Fabrikem Manufacturing Ltd. 20361 Duncan Way, Langley, BC V3A 7N3	
Phone Number	604-532-3883 (Monday to Friday; 0800-1600 Pacific Time)	
Preparation Date of SDS 21 November 2019		
Revision Date of SDS	te of SDS 21 February 2020	
SDS Prepared By WHMIS Team		
CANUTEC Emergency Number	C Emergency Number 613-996-6666 (Transport Emergencies)	

SECTION 02 HAZARD IDENTIFICATION

Hazard	d SKIN CORROSION/IRRITATION Category 1			
Classification	SERIOUS EYE DAMAGE/EYE IRRITATION Category 1			
Label Elements				
Symbols				
Signal Word	Danger			
Hazard Statements	H290 May be corrosive to metals.			
	H314 Causes severe skin burns and eye damage.			
Precautionary	P201 Obtain special instructions before use.			
Statements	P202 Do not handle until all safety precautions have been read and understood.			
	P234 Keep only in original container.			
	P260 Do not breathe mist, vapours or spray.			
	P262 Do not get in eyes, on skin, or on clothing.			
	P264 Wash face, hands, and any exposed skin thoroughly after handling.			
	P280 Wear protective gloves, protective clothing, eye protection, and face protection.			
	P310 Immediately call a POISON CENTER or doctor/physician.			
	P320 Specific treatment is urgent (see first aid treatment section 04 below).			
	P301 +P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
	P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin.			
	P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
	P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position			
	comfortable for breathing.			
	P310 Immediately call a POISON CENTER or doctor/physician.			
	P390 Absorb spillage to prevent material damage.			
	P363 Wash contaminated clothing before reuse.			
	P405 Store locked up.			
	P403 + P233 Store in a well-ventilated place. Keep container tightly closed.			
	P501 Dispose of contents/container in accordance with all federal, provincial, and/or			
	local regulations including the Canadian Environmental Protection Act.			
Other Hazards				

FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

SECTION 03 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	Concentration	Synonyms
Urea Monohydrochloride	506-89-8	10 - 30	Urea Hydrochloride
Phosphoric Acid	7664-38-2	7 - 13	Orthophosphoric acid

SECTION 04 FIRST AID MEASURES

Route of	
Exposure	
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen.
Skin Contact	Get immediate medical advice/attention. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye Contact	Get immediate medical advice/attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	Get immediate medical advice/attention. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person.
Self-protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.
Most Important Symptoms & Effects	Aspiration into the lungs may occur during ingestion or vomiting, resulting in lung injury. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Corrosive to eye tissue and may cause severe damage and blindness. Coughing, shortness of breath, headaches and confusion may occur. Causes vomiting, nausea, and diarrhea. Vapors may cause pulmonary edema. Corrosive! May cause severe pain in the mouth, chest and abdomen, leading to cough, vomiting and collapse. Contact with the skin may cause severe irritation, burns or tissue destruction. Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Can cause chemical bronchitis. May cause adverse eye effects such as conjunctivitis or corneal damage.
Immediate Medical Attention & Special Treatment	Obtain medical assistance.
Note to Physicians	Treatment based on sound judgment of physician and individual reactions of patient.

SECTION 05 FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Foam. Dry powder. Carbon dioxide.
Unsuitable Extinguishing Media	Not Available.

FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

Hazardous Combustion Products	Heat may liberate corrosive and toxic Hydrogen Chloride gas. Hydrogen
	Chloride is denser than air and will accumulate in low lying areas. In the
	event of a fire oxides of nitrogen and carbon may be released.
Special Fire Fighting Procedures	Firefighters should wear self-contained breathing apparatus and full
	firefighting turnout gear. Use personal protection equipment.

SECTION 06 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures	Wear appropriate personal protective equipment (impervious gloves, safety glasses, protective clothing, face-shield). Ventilate area. Only enter area with PPE. Stop or reduce leak if safe to do so.	
Environmental Precautions Prevent further leakage or spillage if safe to do so. Should not be release the environment. Do not allow to enter into soil/subsoil. Prevent produentering drains.		
Methods and Materials for	SMALL SPILLS: Contain and soak up spill with absorbent material which does not	
Containment and Cleaning Up	react with spilled chemical. Put material in suitable, covered, labeled containers. Neutralize with soda ash (sodium carbonate) or lime over area of spill. Flush area with water. Do not get water inside containers. Contaminated absorbent material may pose the same hazards as the spilled product. LARGE SPILLS: prevent contamination of waterways. Dike and pump into suitable containers. Clean up residual with absorbent material, place in appropriate container and flush with water. Spilled material may cause floors and contact surfaces to become slippery. Neutralize with soda ash (sodium carbonate) or lime over area of spill.	

SECTION 07 HANDLING AND STORAGE

Precautions for Safe Handling	Use proper equipment for lifting and transporting all containers. Use sensible	
	industrial hygiene and housekeeping practices. Wash thoroughly after handling.	
	Avoid all situations that could lead to harmful exposure. Avoid generating	
	vapours, fumes, or mists. Prevent the release of vapours, fumes, or mists into	
	the workplace air. Inspect containers for damage or leaks before handling. If the	
	original label is damaged or missing, replace with a workplace label.	
Conditions for Safe Storage	Store in a cool, dry, well-ventilated area, out of direct sunlight and away from	
	heat sources. Keep quantity stored as small as possible. Drums should be	
	vented when received and then at least weekly to relieve internal pressure.	
	Avoid storage with incompatible materials.	

	ontrol						
P 6	arameters			ACGIH	TLV	OSHA	PEL
	Chemical Name		TWA	STEL	TWA	STEL	
ľ	Hydrogen Chloride Phosphoric Acid			2.8 mg/m ³	N/A	7 mg/m ³	N/A
ľ			1 mg/m ³	3 mg/m ³	1 mg/m ³	3 mg/m ³	
EngineeringGeneralMechanical ventilation (dilution or local exhaust), processControlspersonnel enclosure and control of process conditions mu							

FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

		provided in accordance with all fire codes and regulatory
		requirements.
	Local Exhaust	Supply sufficient replacement air to make up for air removed by
		exhaust systems.
	Other	Emergency shower and eyewash must be available and tested in
		accordance with regulations and be in close proximity.
Personal	Gloves	Impervious gloves of chemically resistant material (rubber or PVC)
Protective		should be worn at all times. Wash contaminated clothing and dry
Equipment		thoroughly before reuse.
	Respirator	If the exposure limit is exceeded, a full facepiece respirator with an
		acid gas cartridge may be worn up to 50 times the exposure limit or
		the maximum use concentration specified by the appropriate
		regulatory agency or respirator supplier, whichever is lowest. For
		emergencies or instances where the exposure levels are not known,
		use a full-facepiece positive-pressure, air-supplied respirator.
	Eye	Chemical goggles, full-face shield, or a full-face respirator is to be
		worn at all times when product is handled. Contact lenses should not
		be worn; they may contribute to severe eye injury.
	Footwear	Impervious footwear of chemically resistant material (rubber or PVC)
		should be worn at all times.
	Clothing	RECOMMENDED (resistance to breakthrough longer than 8 hours):
		Butyl rubber, Neoprene rubber, Nitrile.
	Other	

SECTION 09 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid, slightly yellow to amber
Odour	Odourless
Odour Threshold	Not Established
pH	<1
Melting/Freezing Point	-17°C
Initial Boiling Point/Range	100°C
Flash Point	N/A
Evaporation Rate (n-butyl acetate = 1)	Not Established
Flammability	Non-flammable
Lower Flammable/Explosive Limit	N/A
Upper Flammable/Explosive Limit	N/A
Vapour Pressure	Not Established
Vapour Density (air = 1)	1.3 @ 20°C
Relative Density	1.2 – 1.3
Solubility	Completely miscible
Partition Coefficient (n-octanol/water)	Not Established
Auto-Ignition Temperature	N/A
Decomposition Temperature	Not Established
Viscosity	Not Established

SECTION 10 STABILITY AND REACTIVITY

FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

Reactivity	May react with metals to form explosive hydrogen gas. May corrode metals. Reacts with alkalis to generate significant heat.	
Chemical Stability	Stable; heat and contamination could cause decomposition.	
Possibility of Hazardous Reactions	Hazardous polymerization does not occur.	
Conditions to Avoid	High temperatures. Incompatibles.	
Incompatible Material	Avoid contact with oxidizers. This material may be extremely hazardous in contact with chlorates or nitrates. This material is acidic. Contact with hypochlorites (e.g. chlorine bleach, sulfides, or cyanides will liberate toxic gases. Contact with alkaline materials (e.g. aqua ammonia) will generate heat.	
Hazardous Decomposition Products	Thermal decomposition may yield oxides of carbon, nitrogen, and chlorine. Hydrogen gas may be released upon contact with certain metals.	

SECTION 11 TOXICOLOGICAL INFORMATION

Routes of Exposure	Inha	alation, Skin, Eyes, Inge	estion			
Symptoms of Acute Exposure	e Skin	Corrosion/Irritation	Corrosive! Effects on the skin n	nay be delayed and		
	dam	nage may occur withou	ut the onset of pain.			
	Inge	Ingestion Causes severe burns of the mouth, esophagus, and stomach.				
	Inha	Inhalation Causes severe burns to the mouth and throat.				
	Seri	Serious Eye Damage/Irritation Corrosive. May cause permanent eye damage.				
	Cau	Causes blurred vision. Symptoms include pain, redness and tearing.				
Symptoms of Chronic Exposure		Affection/discolouration of the teeth.				
Irritancy of Product		Respiratory tract, skin and eye irritant.				
Other Toxicological Informat	ion					
Ingredient		LD ₅₀	LC ₅₀	TLV		
Hydrogen Chloride		5,010 mg/kg	3,124 ppm (Rat – 1 hr)	0.2 mg/m ³		
Phosphoric Acid		1,530 mg/kg	> 850 mg/m ³ (Rat – 1 hr)	3.0 mg/m ³		
Carcinogenicity:			•			
Chemical Name		IARC	ACGIH	OSHA		
Phosphoric Acid		N/A	N/A	N/A		
Reproductive Toxicity:	No infor	mation available.				
Germ Cell Mutagenicity:	No infor	nformation available.				
Interactive Effects:	No infor	mation available.				

SECTION 12 ECOLOGICAL INFORMATION

Ecc	otoxicity					
	Chemical Name	Ecotoxicity Freshwater Algae Data Not Available		Ecotoxicity Fish Species Data	Toxicity to Microorganisms Not Available	Crustacea Not Available
	Phosphoric Acid			Not Available		
			ľ			
Pe	rsistence & Degradal	oility	No information	available.		
Bioaccumulative Material No Information		Available				
Ot	her Adverse Effects	Effects No information available.				

FABRIKEM® MANUFACTURED STONE CLEANER TYPE 110

SECTION 13 DISPOSAL CONSIDERATIONS

Waste	Dispose in accordance with all federal, provincial, and/or local regulations including the Canadian
Disposal	Environmental Protection Act.

SECTION 14 TRANSPORT INFORMATION

Shipping	Proper Shipping Name: UN 1760, CORROSIVE LIQUID N.O.S. (Contains: Urea Monohydrochloride
Name	and Phosphoric Acid), Class 8, Packing Group II
TDG	UN 1760, CORROSIVE LIQUID N.O.S. (Contains: Urea Monohydrochloride and Phosphoric Acid),
	Class 8, Packing Group II
DOT	UN 1760, CORROSIVE LIQUID N.O.S. (Contains: Urea Monohydrochloride and Phosphoric Acid),
	Class 8, Packing Group II

SECTION 15 REGULATORY INFORMATION

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

SECTION 16 OTHER INFORMATION

24 5-1	24 Fahruary 2020
21 February 2020	21 February 2020

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It is provided solely for the customer's consideration, and verification and Fabrikem Manufacturing Ltd. hereby specifically claims it shall not be held liable for any damage resulting from handling or from contact with the above products.

N/A = Not Available N/E = Not Established