



## MAKE THE FIRST FIX COUNT

### MADE TO MEASURE

- ✓ Manufactured to customer dimensions
- ✓ Any width, any length
- ✓ Any depth subject to practical width and length dimensions
- ✓ Non std shapes e.g L-shapes, (see pg2)

### EASY TO USE

- ✓ Delivered to site ready to install
- ✓ Concrete ties for connection to rebar on sides over 300mm
- ✓ Labelled with drawing reference
- ✓ Reduces waste removal from site

### OFF-SITE MANUFACTURE

- ✓ Manufactured and assembled in a factory environment
- ✓ Structural ply lid with 20mm side rebates. Flat sides accommodated to go against walls where required.

### NO BREAKING OUT

- ✓ Perforations in the steel allow grout to penetrate, providing a profiled key for infill to bond to.
- ✓ No breaking out, no scabbling
- ✓ Saves PM and labour time on site

## MAKE THE FIRST FIX COUNT



Call : 01782 757142



[sales@firstfixformwork.co.uk](mailto:sales@firstfixformwork.co.uk)

# DECK BOX VARIATIONS


**L-SHAPE**

**POLYGON**

**ROUND**

**T-SHAPE**

**TAPERED**

**PLUMB HOLE**

## Technical Information

**Manufacture** : Deck Box frames are galvanised mild steel of European Standard EN10142:2000, coated with zinc by hot-dip processes (Galvatite Z), including iron-zinc alloy (Galvatite ZF). The hot-dip coatings may contain up to 0.002% lead or up to 0.12% antimony. Lids and inserts are 18mm structural plywood. Datasheets for steel and ply are available on request and from the website.

**Personal Protection** : Suitable protective clothing covering all exposed body parts should be worn. Equipment, such as safety spectacles, and cut-resistant gloves, should be worn when handling the metal frames.

**First Aid** : Steel frame skin and eye contact: Possible cuts from steel edges. Treat as other cuts; if required, seek medical attention.