Bevond RS



FLEX 4064

COMPACT ORGANIC WASTE INTO 64 GALLON TOTERS WITH THE BRS FLEX 4064

This robust and reliable compactor features a small footprint and lightweight design. It takes up very little floor space. The 4064 is easy, safe, and convenient to use! The multi-chamber unit offers a top-loading setup, while the single-chamber version is based on the principle "Roll in! Compact! Roll out!"



Safety



KEY BENEFITS

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling means more time for your core activities!

MORE SPACE & ORDER

The 4064 minimizes the space waste takes up and keeps your workspace neat and tidy .

LOWER COST, MORE VALUE

More compaction = less volume to transport. Fewer trips translates to lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of recyclable material.



Why Beyond RS 4064?

- Versatile compaction for many applications
- Hygienic and safe compaction and disposal waste, organics, or mixed recyclables
- Specialized solutions for specific needs





Beyond RS Flex 4064

BRS FLEX 4064 IS OPTIMIZED FOR:

- · Municipal solid waste
- · Compostable material and organic waste
- Mixed Recycling

In-bin compaction solution

BRS FLEX 4064 is an in-bin compactor for standard two-wheeled 64 gallon bins. The 4096 Model is available for 96 gallon bins.

IDEAL FOR ORGANIC MATERIAL

SAFE AND USER-FRIENDLY

is in position.

The 4064 is perfect for the food service sector where organics need to be transported in toters. This unit provides impressive volume reduction, with an average compaction ratio of 3:1.

Model 4064 is user-friendly! The multi-chamber version has a convenient top-loading installation, while the single-chamber version has an easy wheel-in, wheel-out operation. Safety and quality are our hallmarks, and the compactor provides maximum personal safety both for the operator and those in the vicinity. A bin indicator ensures that the machine can only operate when the bin



Designed to fit standard 64 gallon bins.

SMART DESIGN

The 4064 is a robust and stable machine. A quality finish and accessibility make cleaning easy!

SCALABLE SOLUTION

The compactor can be supplemented with additional chambers for rapid compaction. The front door on the single-chamber unit is replaced by an apron for easy transition of the press head from one chamber to the next.





Full protection and no access to moving parts: safety switches on the hatch and the front door/apron



The single-chamber unit with swing door




The multiple-chamber unit equipped with an apron with two handles

DIMENSIONS & SPECIFICATIONS

DIMENSIONS BEYOND RS FLEX 4064						
A	В	с	D	TRANSPORT HEIGHT		
Single: 94" Double: 94"	Single: 30" Double: 60"	Single: 36" Double: 36"	Single: 60"	Single: 83" Double: 83"		

Single: 94"	Single: 30"	Single: 36"	Single: 60"	Single: 83"	
Double: 94"	Double: 60"	Double: 36"		Double: 83"	
MACHINE WEIGHT	Г				8
TOTAL WEIGHT	PRESS UNIT	SINGLE STAND			
Single: 485 Lbs	Single: 265 Lbs	Single: 220 Lbs			
Double: 706 Lbs	Double: 265 Lbs	Double: 220 Lbs			_



TECHNICAL SPECIFICATIONS							
BIN SIZE	CYCLETIME	PRESS FORCE	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER		
64 Gallon	36 seconds	4,400 pounds	62.3 db (A)	IP 55	Single phase 115 V, 60 Hz, 16 A		

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.



