

STREAT *drycom*

On-Line Moisture Control System Dryer Speed Control



Typical DRYCOM On-Line Dryer Moisture Control Applications



For dryer control where it is possible to control the speed of the dryer (and for loose fibre applications preferably the feed hopper too) the DRYCOM Moisture Meter's Integrated Speed Control Module is added to provide full dryer speed control functions.

These systems continuously monitor the moisture content of the product exiting the dryer and regulate the speed of the dryer to ensure the moisture content is maintained at the desired level.

Applications

Some of the applications that DRYCOM can be used for include:

- Loose Fibre
- Bale Moisture
- Non-wovens
- Carpet
- Towelling
- Healthcare and Sanitary Products
- Food Products
- Yarn
- Fabric
- Wood Fibre
- Sliver

Benefits

DRYCOM customers benefit from our vast experience (over 35 years) in the area of moisture measurement and control and receive an appropriate moisture solution that is engineered to suit their requirements.

Benefits include:


- Increased profits
- Increased productivity (20 to 30% in some cases)
- Reduced energy usage per kg of product processed
- Improved downstream processing
- Avoiding over-drying
- Improved and consistent product quality
- Increased average moisture content (resulting in higher sales value)
- Elimination of re-processing
- Elimination of claims from customers
- Reduced shade variations

DRYCOM Moisture Control systems offer solutions to your moisture problems. Due to increased productivity and elimination of customer complaints the payback period is usually a number of months.



Configuration

Moisture is a critical factor in many application areas and processes. By measuring the moisture significant benefits can be obtained. DRYCOM Moisture Control Systems are designed to assist our customers to optimise production processes and maximise productivity, quality, operating efficiencies and profitability.



The DRYCOM system has been applied to processes from Breakfast Cereals, to HealthCare & Sanitary Processes, to conventional Textiles and Non-Woven processing.

DRYCOM Moisture Control systems are precision instruments that use a unique adaptation of the conductivity principle. They are designed to operate in hostile industrial environments and provide our customers with:

- Simple operation.
- Immediate, continuous and accurate on-line moisture measurement
- Up to three independent moisture sensors
- Sensors that measure the entire thickness of product – not just the surface
- Readings not affected by the effects of surface presentation, colour, temperature, normal variations in thickness or density of the product under test
- Readings that take into account the moisture profile in the product.
- Measurement from 0% to approximately 2x the equilibrium moisture for the product under test.
- Enhanced control of startups, batch changes, stoppages, different materials etc.
- Advanced control modes available.
- Multiple 'recipe' selection enabling optimum processing of different products, dryer loadings, etc

Drying Problems solved with DRYCOM

Typical Moisture Related Problems	DRYCOM Solution Offers
Overdrying resulting in lost production or excess energy usage. For every 1% you over-dry productivity drops 2 to 3%,	Increased productivity through processing product at the desired moisture levels.
Under-drying resulting in the need for re-drying of product.	No re-dries required by ensuring product is processed at the desired moisture content levels.
Under-drying resulting in fibre damage in storage due to the moisture content being too high (resulting in product going mouldy or catching fire)	Production of product at the desired level to ensure no fibre damage in storage.
Over-drying resulting in difficulty in future processing causing excess fibre damage, static problems and fly.	Consistent production at the correct moisture levels to optimise future processing (carding, gilling etc).
Poor product quality (often resulting in claims or complaints from clients).	No claims by ensuring production of high and consistent quality product.
Wastage of product due to poor quality.	Greatly improved and consistent quality product.
No records of moisture content.	Reporting functions available in line with ISO standards.
Inefficient use of labour for regular laboratory testing for moisture content.	Optimum deployment of labour to other vital tasks.

Technical Specifications

DRYCOM Moisture Control Systems are precision instruments that have been designed to assist Textile, Food and Related Industry Processors optimise their production processes and maximise productivity, quality, operating efficiencies and profitability.

Measuring Ranges – Non Textiles (examples only, contact us for a complete list)

Product	Regain % Range	Moisture Content % Range
Dried Biscuit	0 to 20	0 to 18
Flaked Wheat	0 to 25	0 to 20
Malt	0 to 20	0 to 18
Meat Meal	0 to 12	0 to 10
Soya Bean Meal	0 to 18	0 to 16
Sunflower Meal	0 to 20	0 to 18
Tobacco	Typically 0 to 30	Typically 0 to 25
Wheat	0 to 25	0 to 20

Measuring Ranges – Textile fibres, sliver, yarn, fabric etc

Fibre	Regain % Range	Moisture Content % Range
Acetate	0 to 13	0 to 12
Acrylic	0 to 4.0	0 to 4.0
Cotton	0 to 25	0 to 20
Cotton/polyester 50/50	0 to 12	0 to 11
Cotton/viscose 50/50	0 to 27	0 to 22
Flax	0 to 25	0 to 20
Jute	0 to 30	0 to 23
Nylon 6	0 to 10	0 to 9
Nylon 66	0 to 10	0 to 9
Polyester	0 to 1	0 to 1
Polypropylene	0 to 0.9	0 to 0.9
Silk	0 to 25	0 to 20
Viscose	0 to 30	0 to 23
Viscose/polyester 50/50	0 to 15	0 to 13
Wool	0 to 35	0 to 26
Wool/nylon 50/50	0 to 25	0 to 20
Wool/polyester 50/50	0 to 17	0 to 15
Wool/viscose 50/50	0 to 30	0 to 23

Specifications

Power Supply	<p>Sensor Hub 24v DC (supplied from Touch-Screen)</p> <p>Touch-Screen Universal Power Supply for 100 to 260 volt, 50 or 60 Hz operation, Power consumption: 30 watts</p>
Dimensions (mm)	<p>Sensor Hub 280 (W) x 170 (H) x 90 (D) 2.5kg</p> <p>Touch-Screen 330 (W) x 280 (H) x 130 (D) 4.4kg</p>
Operator Interface	Full Colour Touch-Screen
Interface	Industrial standard interfaces for connection to other devices (SCADA systems etc)
Moisture Sensors	Wide range available depending on application – contact us for details
Enclosure	Hose-proof and Dust-proof with IP65 rating
Environmental	0°C to 45°C, maximum humidity 90% RH

STREAT *drycom*

Streat Drycom Limited
6 Great Russell Court
Fieldhead Business
Centre
Bradford
BD7 1JZ
UK

Ph: +44 1274 733145

mail@streatdrycom.com
www.streatdrycom.com

DRYCOM

Water Wizardry