

SERIES — ·HUSTLER · HUSTLER

The state of the s



MAGNETIC TOP PIN DECK LIFT SYSTEM

Adjust the deck height between 1.5"-4.5" with your foot.

CAST DECK HANGERS

Designed to help improve durability.

EASY SERVICEABILITY

Flip-up seat pan, removable floor pan, and toolless removable pulley covers to make maintenance easy and simple.

WELDED STEEL DECK

10 GA welded fabricated steel.

SMOOTHTRAK™ STEERING

Precision control designed to help trim and maneuver easily around obstacles.

FRONT AND REAR TIE DOWNS

1.5" x 3" tubular steel fabricated frame with front and rear tie downs.

LESS CLUTTER UNDER SEAT

Provides airflow aiding in keeping transmissions cooler.

TRANSMISSIONS

Serviceable Hydro-Gear® transmissions.

DECK SIZE / ENGINE		
48"	22 HP*	Kawasaki [®] FT691
48" RD	22 HP*	Kawasaki [®] FT691
54"	22 HP*	Kawasaki [®] FT691
54" RD	22 HP*	Kawasaki [®] FT691
60"	24 HP*	Kawasaki [®] FT730

DECK SIZE / ENGINE			
48"	22 HP*	Kawasaki [®] FX691	
54"	22 HP*	Kawasaki [®] FX691	
60"	23.5 HP*	Kawasaki [®] FX730	



MORE FEATURES



HIGH-BACK SUSPENSION SEAT High-back seat with suspension and EVC cushion designed to help take pressure off the tailbone and lower back.



COMMERCIAL-GRADE
KAWASAKI FT ENGINE
Full commercial remote canister
air cleaner



DUAL ROTO-MOLDED FUEL TANKS8.5 gallon fuel capacity and dual fuel gauges.

UPGRADES FOUND ON THE FASTRAK SEX



EXTRA HIGH-BACK SUSPENSION SEAT Higher backrest and more bolstered back cushion



KAWASAKI® FX ENGINE Full commercial remote canister air cleaner



LARGER TRANSMISSIONSHydro-Gear® ZT-3400™



MORE WARRANTY COVERAGE 4YR/1000 HR compared to 4YR/750 HR

ACCESSORIES

(Each sold separately)

- · Mulch kit
- Dump from seat bagger (8 bushels)
- Grass bagger (2-bag powered 7.2 bushels)
- Mesh side bagger (3 bushels)
- Steel side bagger (3.5 bushels)
- · Steering lever extension kit
- Flex Forks[®]
- Light kit
- Stripe kit
- · High vacuum kit









	FASTRAK®	FASTRAK SDX®	
ENGINE			
Manufacturer	Kawasaki [®] FT series	Kawasaki [®] FX series	
	48", 48" rd, 54", 54" rd deck: 22 нр [*] — FT691	48", 54" deck: 22 нр* — FX691	
HP	60" deck: 24 нр* — FT730	60" deck: 23.5 нр* — FX730	
	(Per SAE J1995)	(Per SAE J1995)	
Displacement	48",48" RD, 54": 726 CC FT691 60": 726 CC FT730	Kawasaki: 726 cc	
Cooling	Air cooled		
Engine Warranty	3-у	rear	
DRIVE SYSTEM			
Туре	Dual hydrostatic		
Transmission	Hydro-Gear® ZT-3200	Hydro-Gear® ZT-3400	
Speed	Up to 10 мрн	Up to 10 MPH	
Parking Brakes	Integrated into steering levers		
DECKS	megrated into steering tevers		
Cutting Width	Side-discharge: 48", 54", 60" • Rear-discharge: 48", 54"	Side-discharge: 48", 54", 60"	
Cutting Heights		-4.5"	
Deck Lifts			
Depth	Foot operated 5"		
Blades	3		
		48" deck: 16.50" • 54" deck: 18.50" • 60" deck: 20.50"	
Blade Length	48", 48" RD: 16.50" • 54", 54" RD: 18.50" • 60" deck: 20.50"		
Blade Tip Speed	48", 48" RD: 18,600 • 54", 54" RD: 18,900 • 60": 18,400	48": 18,600 • 54": 18,900 • 60": 18,400	
Spindles		and sealed ball bearings	
Drive	Electric PTO clutch		
Construction	Fabricated 10 GA		
Spindle Mounts	Reinforced 11 GA		
Impact/Trim Areas	11 GA formed chani	nel with rolled edge	
CONSTRUCTION			
Frame		teel tubing	
Front Axle		ealed ball bearings	
Front Caster Wheels	Tapered roller bearings, grease-able		
Front Caster Forks	Fabricated 3/8" steel		
GENERAL			
Seat	High-back suspension seat	Extra high-back suspension seat	
Fuel Capacity	8.5 gallons		
Cupholder	Yes		
Front Tire	13 x 6.5-6	13 x 6.5-6	
	48", 48" RD: 23 x 9.5–10	48" 23 x 9.5–10	
Drive Tire	54", 54" RD, 60": 23 x 11-10	54", 60": 23 x 11–10	
DIMENSIONS	, ,	,	
Woight	48" 910 LBS • 48" RD: 924 LBS • 54": 925 LBS	48":910 LBS • 54":925 LBS • 60":944 LBS	
Weight	54" RD: 933 LBS • 60": 944 lbs	+0 .310 LD3 * J4 .323 LB3 * 00 .344 LB3	
Height	45.5" • 68.7 w/ ROPS up	48.9" • 68.7 w/ ROPS up	
Length	76.7"	76.7"	
Width w/ Chute Up	48": 50" • 48"RD: 48.8" • 54": 55" • 54" RD: 54.8" • 60": 61.1"	48": 50" • 54": 55" • 60": 61.1"	
Tire Width	48": 47.5" • 54" & 60": 51.5"	48": 47.5" • 54" & 60": 51.5"	
	48": 0.6" • 48" RD: 0.7" • 54": 1.6"		
Trim Side	54" RD: 1.6" • 60": 4.6"	48": 0.6" • 54": 1.6" • 60": 4.6"	
PRODUCTIVITY**	2 : 2.5		
Acres Per Hour	48" deck: 3.88 • 54" deck: 4.36 • 60" deck: 4.84	48" deck, 3.88 • 54" deck: 4.36 • 60" deck: 4.84	

Specifications are subject to change without notice.

As rated by the engine manufacturer.

"Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning, and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JÜKÖGYÖ KABUSHIKI-KAISHA. Kohler and command Pro are registered trademarks owned by Kohler Co.

Vanguard is a registered trademark owned by Briggs & Stratton Corporation. Hydro-Gear and ZT-4400 are registered trademarks owned by Hydro-Gear Limited Partnership.

Michelin, X, and Tweel are registered trademarks owned by COMPAGNIE GENERALE DES ESTABLISSMENTS MICHELIN.