



SUPER S



COMMERCIAL

SUPER S



COMPACT STANCE

Perfect for tight spaces and trailering from job-to-job.

PULLEY COVERS

Toolless removable pulley covers for easy maintenance.

VX DECK

Fabricated 7 GA steel deck, engineered for extreme vacuum performance and cut quality.

SERVICE FRIENDLY DESIGN

Designed to make maintenance and service fast and easy.

CUT HEIGHT ADJUSTMENT

Hand operated lever and pin to adjust deck/cutting height.

PARK BRAKE

Hand operated lever to set the park brake.

ADJUSTABLE SPEED CONTROLS

Allows you to go at your own pace for control. Also helps with training new operators.

24" REAR DRIVE TIRES

For superior traction. (48", 52", 60")

SMOOTHTRAK™ STEERING

Precision control designed to help trim and maneuver easily around obstacles.

ADJUSTABLE FOOT PLATFORM

Spring loaded suspension platform designed for all-day comfort.

WIDE OPERATOR PLATFORM

For mowing comfort and operator stability.



AVAILABLE DECK SIZES

ENGINE	DECK SIZES
19 HP*—Kawasaki® FX600	36"
22 HP*—Kawasaki® FX691	48"
27 HP*—Kawasaki® FX850	42", 60"
29.5 HP*—Kawasaki® FX850 EFI	52", 60"

MORE FEATURES



COMPACT STANCE

Perfect for tight spaces and trailering from job-to-job.



SERVICE FRIENDLY DESIGN

Designed to make maintenance and service fast and easy.



SMOOTHTRAK STEERING

Precision control designed to help trim and maneuver easily around obstacles.

VX DECK TECHNOLOGY

Fabricated steel deck engineered to move more grass at high speeds while maintaining cut-quality.

- Made with 7 GA steel and 7 GA wrappers.
- Front edge protected by 11 GA formed channel with rolled edge.
- Ductile cast iron spindles with steel shaft and sealed ball bearings.
- Reinforced 7 GA stamped disc spindle mounts.



ACCESSORIES

(Each sold separately)

- Mulch Kit
- Mesh side bagger (3 bushels)
- Metal side bagger (3.5 bushels)
- Side aluminum bagger (3.5 bushels)
- Light kit
- Stripe kit
- Trash basket
- Cup holder



SUPER S

ENGINE	
Manufacturer	Kawasaki FX series
HP	36" deck: 19 HP - FX600 48" deck: 22 HP - FX691 52", 60" deck: 27 HP - FX850, 29.5 HP - FX850 EFI (Per SAE J1995)
Displacement	603 cc – 852 cc
Cooling	Air cooled
Air Cleaner	FX: Heavy duty air canister
Engine Warranty	3 year
DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	36" deck: Hydro-Gear 10 cc • 48", 52", 60" deck: Hydro-Gear 12 cc
Hydraulic Cooling	36" deck: Parker TL • 48", 52", 60" deck: Parker TL
Speed	36": Up to 8 MPH • 48", 52", 60": Up to 9 MPH
Parking Brakes	Hand operated drum brakes
DECKS	
Cutting Width	Side discharge: 36", 48", 52", 60"
Cutting Heights	1.5"–5.5"
Deck Lift	Hand operated.
Depth	5.5"
Blades	36": 2 • 48", 52", 60": 3
Blade Length	36" deck: 17.86" • 48" deck: 16.50" • 52" deck: 17.86" • 60" deck: 20.50"
Blade Tip Speed	36": 18,700 • 48": 18,500 • 52": 17,700 • 60": 18,400
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 GA Fabricated w/ 7 GA wrappers
Spindle Mounts	36": 7 GA with 11 GA doubler • 48", 52", 60": 7 GA with 7 GA doubler
Impact/Trim Areas	11 GA formed with rolled edge
CONSTRUCTION	
Frame	36": 1.5" x 2" steel tubing • 48", 52", 60": 1.5" x 3" steel tubing
Engine Plate	7 ga with 11 GA jackshift doubler
Operator Platform	7 ga with embossed tread pattern
Front Axle	Fabricated with tapered roller bearings
Front Caster Wheels	Tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 3/8" steel
Operator Pad	Bolstered operator pad
GENERAL	
Fuel Capacity	36": 6.5 gallons • 48", 52", 60": 7.3 gallons
Front Tire	36" 11 x 4-5 • 48", 52": 13 x 5-6 • 60": 13 x 6.5-6
Drive Tire	36: 20 x 8-10 • 48", 52": 24 x 9.5-12 • 60": 24 x 12-12
DIMENSIONS	
Weight	36": 907 LBS • 48": 1144 LBS • 52": 1153–1182 LBS • 60": 1207–1232 LBS
Height	47"
Length	36": 63.5" • 48", 52": 68" • 60": 70.75"
Width w/Chute Up	36": 39" • 48": 49.3" • 52": 52.8" • 60": 61.7"
Tire Width	36" 36.3" • 48", 52": 45.8" • 60": 49"
Trim Side	36": 0" • 48": 1.5" • 52": 3.5" • 60": 5.6"
PRODUCTIVITY**	
Acres Per Hour	36": 2.33 • 48": 3.49 • 52": 3.79 • 60": 4.36

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning, and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JŪKŌGYŌ KABUSHIKI-KAISHA.

Hydro-Gear and ZT-4400 are registered trademarks owned by Hydro-Gear Limited Partnership. Michelin, X, and Tweel are registered trademarks owned by COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN.