



ST50

Compact Track Loader

Do more

The ST50 is the largest and most powerful track loader in the Wacker Neuson lineup. Equipped with a 100 hp Kohler engine, making 368 ft-lb of torque, this machine is a productive workhorse. The extra power enhances the auxiliary flow for improved performance with high flow attachment applications like cold planning and brush clearing.

Highlights


- Controls for Every Operator
- Filter Free After-treatment
- Expansive Maintenance Access


Technical Data

Hydraulic		Operating weight	10,677.0 lb
Flow rate	25.1 gal/mi	Track width	17.7 "
Flow rate max.	37.2 gal/mi	Ground clearance	10.4 "
Auxiliary relief pressure	3,494.5 psi	Engine	
Mechanical - Output Detail	S	Cooling	Water-cooling
Break Out Force Bucket	7,932.4 lbf	Motor type	Diesel engine
Break Out Force Lift Arm	9,371.4 lbf	Cylinder	4.0
Tractive Effort max. at 100% effective force	2 12,582.6 lbf	Cylinder capacity	205.0 Inch3
Travel speed stage 1	6.2 m/H	Operating power	100.6 hp
Travel speed stage 2	9.9 m/H	Operating Engine speed	2,500.0 1/min
Mechanical Details		Battery capacity (nom. value)	950.0 Ah
Overall Length without bucket	117.5 "	Manufacturer	Kohler
Overall Length with Bucket	145.4 "	Operating Fluids	
Overall width without bucket	78.0 "	Fuel Tank capacity	39.9 gal US
Overall height to top of ROPS	84.7 "	Chassis	
Bucket Hinge Pin Height	136.4 "	Tip Load	10,000.2 lb
Angle of departure	31.0 °	Rated Operating Capacity at 50% Tip Load	5,000.1 lb
Bucket dump height at maximum height	108.9 "	Rated Operating Capacity at 35% Tip Load	3,500.9 lb
Bucket dump angle at maximum height	44.0 °	Luau	

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Dimensions





A -1	Overall	longth	with	hugkat
A1	Overall	lengin	VVILII	DUCKEL

A1	Overall length with bucket	145.4 in
B1	Overall length without bucket	117.5 in
C2	Overall width without bucket	78 in
F1	Hinge pin height	136.3 in
G1	Dump height max.	108.9 in
L1	Ground clearance	10.5 in
M1	Angle of departure	31 °

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.