



**WACKER
NEUSON**
all it takes!



SW21 Skid Steer Loader

Power and Performance

The Wacker Neuson SW21 has the power and performance to take on the toughest jobs. Powered by 74hp regeneration-free T4F engine, and available with High Flow hydraulics, the SW21 maximizes the performance of your hydraulic attachments.

Highlights

- Controls for Every Operator
- Maintenance and Filter Free After-treatment
- Expansive Maintenance Access

Technical Data

Hydraulic

Flow rate	20.1 gal/mi
Flow rate max.	10.0 gal/mi
Auxiliary relief pressure	3,494.5 psi

Mechanical - Output Details

Break Out Force Bucket	5,300.1 lbf
Break Out Force Lift Arm	5,000.0 lbf
Tractive Effort max. at 100% effective force	7,636.8 lbf
Bucket Roll Back	1.6 s
Bucket Roll Out	2.1 s
Lift Arm Raise	3.7 s
Lift arm lower	2.5 s
Travel speed stage 1	8.4 m/H
Travel speed stage 2	13.9 m/H

Mechanical Details

Overall Length without bucket	106.6 "
Overall Length with Bucket	134.8 "
Overall width without bucket	65.9 "
Overall height to top of ROPS	81.5 "
Overall height to top of ROPS with large tire option	83.0 "
Bucket Hinge Pin Height	124.0 "
Bucket roll back at ground	125.5 "
Bucket roll back at ground	30.0 °

Bucket roll back at maximum height	30.0 °
Angle of departure	24.0 °
Bucket dump height at maximum height	96.5 "
Bucket dump height at maximum height (large tire option)	97.2 "
Bucket dump angle at maximum height	42.0 °
Operating weight	6,510.3 lb
Ground Clearance (Large Tire Option)	9.1 "
Ground clearance	7.6 "
Dump reach at maximum height	37.9 "
Wheelbase	43.5 "

Engine

Cooling	Water-cooling
Cylinder	4.0
Cylinder capacity	151.5 Inch ³
Operating power	73.8 hp
Operating Engine speed	2,750.0 1/min
Manufacturer	Kohler

Operating Fluids

Fuel Tank capacity	32.8 gal US
--------------------	-------------

Chassis

tires	10 x 16,5
Tip Load	4,199.8 lb
Rated Operating Capacity at 50% Tip Load	2,098.8 lb

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Rated Operating Capacity at 35% Tip 1,468.3 lb

Load

Dimensions

A1	Overall length with bucket	134.9 in
B1	Overall length without bucket	106.6 in
C2	Overall width without bucket	65.9 in
D1	Overall height	81.5 in
E1	Wheelbase	43.5 in
F1	Hinge pin height	124 in
G1	Dump height max.	96.5 in
H1	Dump angle	42 °
I1	Bucket rollback at max. stroke height	30 °
J1	Dump reach	37.9 in
K1	Bucket rollback at ground level	30 °
L1	Ground clearance	7.6 in
M1	Angle of departure	24 °