



**WACKER  
NEUSON**  
*all it takes!*

## SW32

### Skid Steer Loader

#### Productivity Personified

The SW32 is the most powerful and largest Skid Steer Loader in the Wacker Neuson product line. Versatile and comfortable, the SW32, has the speed and control to maximize efficiency. Equipped standard with 2-speed and a color 5.7" multi-function display, allowing in-cab control customizations, the SW32 will enhance productivity on any jobsite.

## Highlights

- Controls for Every Operator
- Filter Free After-treatment
- Expansive Maintenance Access

## Technical Data

### Hydraulic

|                           |             |
|---------------------------|-------------|
| Flow rate                 | 25.1 gal/mi |
| Flow rate max.            | 37.2 gal/mi |
| Auxiliary relief pressure | 3,494.5 psi |

### Mechanical - Output Details

|  |             |
|--|-------------|
| Break Out Force Bucket                       | 7,932.4 lbf |
| Break Out Force Lift Arm                     | 9,371.4 lbf |
| Tractive Effort max. at 100% effective force | 9,711.7 lbf |
| Travel speed stage 1                         | 7.3 m/H     |
| Travel speed stage 2                         | 12.2 m/H    |

### Mechanical Details

|                                      |         |
|--------------------------------------|---------|
| Overall Length without bucket        | 117.5 " |
| Overall Length with Bucket           | 145.4 " |
| Overall width without bucket         | 71.9 "  |
| Overall height to top of ROPS        | 83.2 "  |
| Bucket Hinge Pin Height              | 134.8 " |
| Angle of departure                   | 23.0 °  |
| Bucket dump height at maximum height | 107.8 " |

|                                     |            |
|-------------------------------------|------------|
| Bucket dump angle at maximum height | 44.0 °     |
| Operating weight                    | 8,628.9 lb |
| Ground clearance                    | 8.9 "      |
| Wheelbase                           | 49.9 "     |

### Engine

|                               |               |
|-------------------------------|---------------|
| Cooling                       | Water-cooling |
| Motor type                    | Diesel engine |
| Cylinder                      | 4.0           |
| Cylinder capacity             | 205.0 Inch3   |
| Operating power               | 100.6 hp      |
| Operating Engine speed        | 2,500.0 1/min |
| Battery capacity (nom. value) | 950.0 Ah      |
| Manufacturer                  | Kohler        |

### Operating Fluids

|                    |             |
|--------------------|-------------|
| Fuel Tank capacity | 39.9 gal US |
|--------------------|-------------|

### Chassis

|  |            |
|--|------------|
| Tip Load                                 | 6,400.0 lb |
| Rated Operating Capacity at 50% Tip Load | 3,198.9 lb |

Dimensions

|    |                               |          |
|----|-------------------------------|----------|
| A1 | Overall length with bucket    | 145.4 in |
| B1 | Overall length without bucket | 117.5 in |
| E1 | Wheelbase                     | 49.9 in  |
| F1 | Hinge pin height              | 134.8 in |
| G1 | Dump height max.              | 107.8 in |
| L1 | Ground clearance              | 9 in     |
| M1 | Angle of departure            | 23 °     |