

DQ SMART DT SERİSİ

MODEL NO.	VALVE DIAMETER	MAXIMUM FLOW RATE			CLOSE-OFF PRESSURE	DIFFERENTIAL PRESSURE RANGE	PN RATING	
	MM	L/H	M3/H	GPM	KPA	KPAD		
DQ015TWL2	DN15	1110	1.11	4.89	800	30 - 800	PN25	
DQ015TPL2	DN15	1110	1.11	4.89	800	30 - 800	PN25	
DQ015TWH2	DN15	2650	2.7	11.7	800	35 - 800	PN25	
DQ015TPH2	DN15	2650	2.7	11.7	800	35 - 800	PN25	
DQ020TWL2	DN20	1110	1.11	4.89	800	30 - 800	PN25	
DQ020TPL2	DN20	1110	1.11	4.89	800	30 - 800	PN25	
DQ020TWH2	DN20	2650	2.7	11.7	800	35 - 800	PN25	
DQ020TPH2	DN20	2650	2.7	11.7	800	35 - 800	PN25	
DQ025TWH2	DN25	2650	2.7	11.7	800	35 - 800	PN25	
DQ025TPH2	DN25	2650	2.7	11.7	800	35 - 800	PN25	
DQ032TWH2	DN32	4630	4.6	20.4	800	16 - 800	PN25	
DQ032TPH2	DN32	4630	4.6	20.4	800	16 - 800	PN25	
DQ040TPH2	DN40	13647	13.6	60.1	800	16 - 600	PN25	
DQ050TPL2	DN50	13647	13.6	60.1	800	16 - 600	PN25	